	OLIDO		INFORMATION OLIDBLIEB GLONATURE					
CLIDDI	SUPP LIER NAME		SUPPLIER SIGNATURE  Docusioned by:					
		Cisco Systems Inc.	asher fanturana	4/1/2024				
SUPPL	LIER CONTACT EMAIL  ACCREDITED L	ascummin@cisco.com	ACCREDITED LABORATORY SIGN	IATURE				
LAROI	RATORY NAME	UNH InterOperability Laborator		ATORE				
	RATORY CONTACT EMAIL		Mid. a. la Aburra la	4/1/2024				
LABOI	[2] PRODUCT VE	usgv6-sdoc@iol.unh.ed	u6092CF3\$911F406 [3] PRODUCT ID					
	IOS-XE		Cisco ESR6300 Embedded Se	ries Router				
		[4] PROD	UCT FAMILY					
	APPLICABLE SER	IES HARDWARE	APPLICABLE SERIES SOFTWA	ARE				
ESR	6300		IOS-XE 17.12					
			COMPOSITE SDOC					
	<b>iitary</b> : All of the declared ca ssed by original test results	pabilities of this product are reported in this SDoC.	Composite: Some or all of the capabilities of this product are provided by the use and/or integration of unmodified components that have their own unique SDoCs. All of the relevant referenced SDoCs are identified in section 6 and linked.					
[6] REF	SUPPLIER	PRODUCT ID/STACK ID	CAPABILITY SUMMARY	COMPOSITE SDOC LINK				
i.	Cisco Systems Inc.	Cisco ESR6300 Embedded Series Router/IOS-XE 17.12	USGv6-r1:Router+Core+SLAAC+Addr-Arch+OSPF+OSPF-Auth+Link=Ethernet					
		[7] USGV6-CAPAE	BLE REQUIREMENTS					
U:	SGv6-r1-Capable-Host	USGv6-r1-Capable-Router		pable-NPP				
			S) REFERENCED					
i.	NIST SP 500-267Br1, U	SGv6 Profile						
ii.		[9] SUPPLEMENT	ARY ATTESTATIONS					
That is operat	[9] SUPPLEMENTARY ATTESTATIONS  X This product is fully functional in dual stack environments. That is, no claimed capabilities are invalidated if this product is operated in a dual stack (IPv6 and IPv4) network environment.  X This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4							
unique	nis SDoC contains a capabi e IPv6 stack in the product. ed are documented, and ho hose reported are explained	If not, the stacks/ports not w their IPv6 capabilities differ	All of the products listed in the product family implemented such that their capabilities are iden function across the entire product family. The sp conformance and interoperability test results for of an identified member of this product family are SDoC. The SDoC attests that these tested capalidentical and unmodified for all the products cited.	tical in form and ecific the capabilities e provided in this bilities are				

# **Host Capabilities**

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY				
[44]	CADADILITY	CONFOR	OMANICE.	INTEROPERABILI	TV/FUNCTIONAL	NOTES			
[11] SUPPORTED CAPABILITY	CAPABILITY	CONFOR TEST SELECTION	RESULT ID	INTEROPERABILI' TEST SELECTION	RESULT ID	NOTES			
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F					
-	Core	Core_R1v1.*_C		Core_R1v1.*_I					
-	Extended-ICMP	Self-Test		Self-Test					
-	PLPMTUD	Self-Test		Self-Test					
-	ND-Ext	Self-Test		Self-Test					
-	ND-WL	Self-Test		Self-Test					
-	SEND	Self-Test		Self-Test					
-	SLAAC	SLAAC_R1v1.*_C		SLAAC_R1v1.*_I					
-	PriAddr	Self-Test		Self-Test					
-	DHCP- Stateless	DHCP- Stateless_R1v1 .*_C		DHCP- Stateless_R1v1 .*_I					
-	DHCP-Client	DHCP- Client_R1v1.*_C		DHCP- Client_R1v1.*_I					
-	DHCP-Client- Ext	Self-Test		Self-Test					
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I					
-	DHCP-Prefix- Ext	Self-Test		Self-Test					
-	6Lo	Self-Test		Self-Test					

# **Host Capabilities**

		Self-Test	Self-Test	
-	Happy-Eyeballs			
		Addr-	Addr-	
-	Addr-Arch	Arch_R1v1.*_C	Arch_R1v1.*_I	
		Self-Test	Self-Test	
-	CGA	3311 1331	30/1/301	
-	DNS-Client	Self-Test	Self-Test	
-	URI	Self-Test	Self-Test	
-	NTP-Client	Self-Test	Self-Test	
-	NTP-Server	Self-Test	Self-Test	
-	DNS-Server	Self-Test	Self-Test	
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_I	
-	DHCP-Server- Ext	Self-Test	Self-Test	
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_I	
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I	
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I	
-	SSHV2	Self-Test	Self-Test	
-	TLS	Self-Test	Self-Test	
-	TLS-1.3	Self-Test	Self-Test	
-	Tunneling-IP	Self-Test	Self-Test	

### **Host Capabilities**

-	Tunneling-UDP	Self-Test	Self-Test			
-	XLAT	Self-Test	Self-Test			
-	NAT64	Self-Test	Self-Test			
-	DNS64	Self-Test	Self-Test			
-	SNMP	Self-Test	Self-Test			
-	Tunneling	Self-Test	Self-Test			
-	DiffServ	Self-Test	Self-Test			
-	NETCONF	Self-Test	Self-Test			
-	SSM	Self-Test	Self-Test			
-	Multicast	Multicast_R1v1 .*_C	Multicast_R1v1 .*_I			
-	ECN	Self-Test	Self-Test			
-	Link =	Self-Test	Self-Test			

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
Cisco E	SR6300 Emb	edded Series	Router/IOS-X	E 17.12	USGv6-r1:Router+Core+SLAAC+Addr-Arch+OSPF+OSPF-Auth+Link=Ethernet		
[11] SUPPORTED CAPABILITY	CAPABILITY	CONFOF TEST SELECTION	RMANCE RESULT ID	TEST SELECTION	ITY/FUNCTIONAL RESULT ID	NOTES	
NOTES	IPv6-ONLY			IPv6- ONLY_R1v1.*_F	UNH-IOL/38078	The DUT displayed IPv6 addresses with characters "a", "b", "c", "d", "e", and "f" in uppercase.	
PASS	Core	Core_R1v1.*_C	UNH-IOL/38073	Core_R1v1.*_I	UNH-IOL/38075	This SDoC pertains to the IPv6 stack for the following ports: routed ports	
-	Extended-ICMP	Self-Test		Self-Test			
-	PLPMTUD	Self-Test		Self-Test			
-	ND-Ext	Self-Test		Self-Test			
-	ND-WL	Self-Test		Self-Test			
-	SEND	Self-Test		Self-Test			
PASS	SLAAC	SLAAC_R1v1.*_C	UNH-IOL/38073	SLAAC_R1v1.*_I	UNH-IOL/38075	This SDoC pertains to the IPv6 stack for the following ports: routed ports	
-	PrivAddr	Self-Test		Self-Test			
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I			
-	DHCP-Prefix- Ext	Self-Test		Self-Test			
-	6Lo	Self-Test		Self-Test			
PASS	Addr-Arch	Addr- Arch_R1v1.*_C	UNH-IOL/38074	Addr- Arch_R1v1.*_I	UNH-IOL/38076	This SDoC pertains to the IPv6 stack for the following ports: routed ports	
-	CGA	Self-Test		Self-Test			

-	DNS-Client	Self-Test	Self-Test		
-	URI	Self-Test	Self-Test		
-	NTP-Client	Self-Test	Self-Test		
-	NTP-Server	Self-Test	Self-Test		
-	DNS-Server	Self-Test	Self-Test		
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_I		
-	DHCP-Server- Ext	Self-Test	Self-Test		
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_I		
PASS	OSPF	Self-Test	OSPF_R1v1.*_I	UNH-IOL/38077	This SDoC pertains to the IPv6 stack for the following ports: routed ports
-	OSPF-IPsec	Self-Test	Self-Test		
PASS	OSPF-Auth	Self-Test	OSPF- Auth_R1v1.*_I	UNH-IOL/38077	This SDoC pertains to the IPv6 stack for the following ports: routed ports
-	OSPF-Ext	Self-Test	Self-Test		
-	OSPF-Trans	Self-Test	Self-Test		
-	OSPF-Graceful	Self-Test	Self-Test		
-	ISIS	Self-Test	Self-Test		
-	IS-IS-Auth	Self-Test	Self-Test		
-	IS-IS-Ext	Self-Test	Self-Test		
-	IS-IS-MT	Self-Test	Self-Test		

		Self-Test	BGP_R1v1.*_I	
-	BGP			
-	BGP-Reflect	Self-Test	Self-Test	
-	BGP-Graceful	Self-Test	Self-Test	
-	BGP-FlowSpec	Self-Test	Self-Test	
-	BGP-OV	Self-Test	Self-Test	
-	BGP-VPLS	Self-Test	Self-Test	
-	BGP-EVPN	Self-Test	Self-Test	
-	BGP-6VPE	Self-Test	Self-Test	
-	BGP-MVPN	Self-Test	Self-Test	
-	MPLS	Self-Test	Self-Test	
-	CE-Router	CE_Router_R1v 1.*_C	CE_Router_R1v 1.*_I	
-	VRRP	Self-Test	Self-Test	
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I	
-	IPsec-VPN	IPsec- VPN_R1v1.*_C	IPsec- VPN_R1v1.*_I	
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I	
-	IPsec-SHA-512- VPN	IPsec-SHA-512- VPN_R1v1.*_C	IPsec-SHA-512- VPN_R1v1.*_I	
-	SSHV2	Self-Test	Self-Test	
-	TLS	Self-Test	Self-Test	

USGv6 Profile Supplier's Declaration of Conformity (SDoC) R1.1

-	TLS-1.3	Self-Test	Self-Test	
-	Tunneling-IP	Self-Test	Self-Test	
-	Tunneling-UDP	Self-Test	Self-Test	
-	GRE	Self-Test	Self-Test	
-	DS-Lite	Self-Test	Self-Test	
-	LW4over6	Self-Test	Self-Test	
-	MAP-E	Self-Test	Self-Test	
-	MAP-T	Self-Test	Self-Test	
-	XLAT	Self-Test	Self-Test	
-	NAT64	Self-Test	Self-Test	
-	DNS64	Self-Test	Self-Test	
-	6PE	Self-Test	Self-Test	
-	LISP	Self-Test	Self-Test	
-	SNMP	Self-Test	Self-Test	
-	Tunneling	Self-Test	Self-Test	
-	DiffServ	Self-Test	Self-Test	
-	NETCONF	Self-Test	Self-Test	
-	SSM	Self-Test	Self-Test	

NIST.SP.500-281Ar1s

-	PIM-SM	Self-Test	Self-Test	
-	PIM-SM-IPsec	Self-Test	Self-Test	
-	PIM-SM-BiDir	Self-Test	Self-Test	
-	Multicast	Multicast_R1v1. *_C	Multicast_R1v1. *_I	
-	ECN	Self-Test	Self-Test	

# **Application Capabilities**

[10] PRODUC	T ID/ STACK ID			CAPABILITY SUMMARY		
[11] SUPPORTED CAPABILITY	UPPORTED TEST RESULT ID TEST		ITY/FUNCTIONAL NOTES RESULT ID			
-	IPv6-ONLY		IPv6- ONLY_R1v1.*_F			
-	App-Serv=		APP- ONLY_R1v1.*_F			
-	Link =		Self-Test			

### USGv6 Profile Supplier's Declaration of Conformity (SDoC) R1.1

# NPP Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFOR	RMANCE	INTEROPERABILI	TY/FUNCTIONAL	NOTES	
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	FW	FW_R1v1.*_C					
-	APFW	Self-Test					
-	IDS	FW_R1v1.*_C					
-	IPS	FW_R1v1.*_C					
-	Link =	Self-Test					

### **Switch Capabilities**

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY		
	CAPABILITY							
[11] SUPPORTED CAPABILITY	CAFABILITY	CONFOR TEST SELECTION	MANCE RESULT ID	INTEROPERABILIT TEST SELECTION	RESULT ID	NOTES		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F				
-	DHCPv6-Guard	Self-Test		Self-Test				
-	RA-Guard	Self-Test		Self-Test				
-	MLD-Snooping	Self-Test		Self-Test				
-	Link =	Self-Test		Self-Test				

1	CONTACT INFORMATION	Supplier name, email and signature (digital recommended). Include printed name and date if wet ink signed.  Accredited laboratory name, email and signature (digital recommended). Include printed name and date if wet ink signed.
2	PRODUCT VERSION TESTED	Firmware/ software version of product declared
3	PRODUCT ID	Suppliers concise name for product declared
4	PRODUCT FAMILY	Applicable hardware or software with an unmodified IPv6 stack from "PRODUCT VERSION TESTED"
5	UNITARY OR COMPOSITE	Indicate if this is a unitary or composite SDoC. If composite is checked, composite SDoC must be linked in section 6.
6	REF	Reference number to profile(s) reference in this SDoC
	SUPPLIER	Supplier name
	PRODUCT ID/STACK ID	Product ID must match field 3. As there may be more than one unique IPv6 stack, stack ID identifies particular stack described in CAPABILITY SUMMARY. Each unique stack requires a CAPABILITY SUMMARY.
	CAPABILITY SUMMARY	The strong notation as described in NIST-SP-500-267Ar1 that describes the product capabilities of the given stack.
	COMPOSITE SDOC LINK	URL link to composite SDoC referenced.
7	USGV6-CAPABLE REQUIREMENTS	Refer to section 5 in NIST-SP-500-267Br1 for CSS strings referenced in this section. Check the appropriate box if the product meets the requirements.
8	PROFILE(S) REFERENCED	Profile(s) referenced in the SDoC.
9	SUPPLEMENTARY ATTESTATIONS	Attestations made by the supplier. Check all that apply.
10	PRODUCT ID/STACK ID	PRODUCT ID/STACK ID for stack documented on given page.
	CAPABILITY SUMMARY	CAPABILITY SUMMARY for stack documented on given page.
11	SUPPORTED CAPABILITY	"PASS" – All requirements of the capability have been met
		"NOTES" – See notes for details regarding the level of support for this capability
		"X" – Capability not supported
		BLANK – No declaration for this capability
	CAPABILITY	IPv6 Capability as described in NIST-SP-500-267Ar1.
	TEST SELECTION	Test Selection Tables version of capabilities with existing test programs. Capabilities without an existing test program are indicated with "Self-Test"
	RESULT ID	Abbreviation of accredited laboratory and unique identifier of test result. Capabilities with "Self-Test" can be self-declared writing "Self Declaration" in the cell.
	NOTES	The cell must be filled out if "NOTE" is indicated for SUPPORTED CAPABILITY. Suppliers may use notes to clarify unsupported features or non-passing results.

# SUPPLIER GENERAL NOTES