Supplie	ers Declaration of Conformity f	or USGv6 Products		USGv6-v1 SDOC-v1.10 Page 1							
1	The Document Requiring Con	formity:		USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)							
2	Product Identifier:	HPE Primer	a 600 Sto	orage & HPE Alletra 9000 Storage							
	Supplier's Name, Address and	SDOC Contact Details									
	Hewlett Packard Enterprise Company										
	ckrimmon Blvd S, Colorado Sprir	igs									
	Colorado 80919 United States										
Deepesh Nanjangud Seetharama deeps@hpe.com											
4	4 Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.										
HPE Primera Operating System (OS) 4.3.1											
5	5 Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.										
HPE Primera A630, HPE Primera A650, HPE Primera A670, HPE Primera C630, HPE Primera C650, HPE Primera C670, HPE Alletra 9060, HPE Alletra 9080											
SW: HPE Primera OS version 4.3.1, 4.3.2, 4.3.3 and 4.3.4											
SW: HPE Alletra 9000 OS version 9.3.1, 9.3.2, 9.3.3 and 9.3.4											
with HPE SSMC version 3.8.1											
6	,	· · · · · · · · · · · · · · · · · · ·			SGv6 capabilities below and include a detailed test result						
	summary). e.g. example-prod-id	d/stack-1: USGv6-v1-Host: IPv6-Base+Addr-Arc									
		USGv6-v1-Host: IPv6-Base+Addr-	-Arch+SLA	AC+Link =	Ethernet						
7	Self Contained or Composite SDOC? (Must indicate one).										
YES	All of the declared USGv6 capabilities of				rovided by the use and/or integration of umodified components that have						
	are addressed by orginal test results reported in this their own unique USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product SDOC.										
	SDOC. 2 will indicate which capabilities are provided by specific referenced components (product-id/stack-id).										
8	Additional Declarations / Attac	hments: (List supplier & product-id/stack-id for	r referenced	referenced and attached test results in the case of composite products).							
	Component Supplier	Product ID:	Stack ID:		Notes:						
[1]											
[2]											
[3]											
[4]											
9	Supplementary Attestations (Answer all).										
	X This product is fully function	onal in dual stack environments.That is, no claimed	Х	This product	is fully functional in IPv6 only environments. That is, no claimed capabilities						
		l ifthis product is operated in a dual stack (6 and 4)network	^	are invalidated if this product is deployed in a network environment that does not support lpv4.							
	χ This SDOC contains a cap	pabilities test report for each unique IPv6 stack in the	X	All of the products listed in the product family in section 5 are implemented such that their							
	· ·	ports not covered are documented, and how their lpv6		USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilities are identical and unmodified for all the products cited							
	capabilities differ from thos	se reported are explained.									
				above.							
10	Signature	Sdeekem	Date		9/21/2021						
	Print Name / Title Deepesh	Nanjangud Seetharama, Program Manager									
See instri	uctions for fields 1-12 on Page 4.										

		iers Declaration of Conformity for USGv6			Τ'			T *		Gv6-v1 SDOC-v1.10 Pag		
oduct lo	d:	HPE Primera 600 Storage & HPE Alle	tra 9000 Stora	age	Stack I	d:		HPE Prime	era Operating Syster	n (OS) 4.3.1		
			Context /	Suppo	rted Capa	abilities		USGv6 Testing Program Results				
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #		
eference	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperability	Component Ref		
500-267	6.1	IPv6 Basic Requirements	· · · · · · · · · · · · · · · · · · ·						'			
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	Р			Basic_v1.*_C	UNH-IOL/34124	Basic_V1.*_I	UNH-IOL/34125		
		support of PMTU Discovery Protocol requirements	PMTU	Р			Basic_v1.*_C	UNH-IOL/34124	Basic_V1.*_I	UNH-IOL/34125		
		support of stateless address auto-configuration	SLAAC	Р			SLAAC-V1.*_C	UNH-IOL/34124	SLAAC-V1.*_I	UNH-IOL/34125		
		support of Creation of Global Addresses	SLAAC - c(M)	P			SLAAC-V1.* C	UNH-IOL/34124	SLAAC-V1.*_I	UNH-IOL/34125		
		support of SLAAC privacy extensions.	PrivAddr	<del>                                     </del>			Self Test		Self Test			
		support of stateful (DHCP) address auto-	DHCP-Client				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I			
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test			
		support of neighbor discovery security extensions	SEND				Self Test		Self Test	<del> </del>		
500-267	6.6	Addressing Requirements	CEND				2011 7 000		30,, 700,			
300-201	0.0	support of addressing architecture regts	Addr-Arch	Р			Addr_Arch_v1.*_C	UNH-IOL/34126	Addr_Arch_v1.*_I	UNH-IOL/34127		
		support of addressing architecture requisions support of cryptographically generated addresses	CGA	-			Self Test	01111-101/04120	Self Test	01111-102/94121		
500-267	6.7	IP Security Requirements	OOA				Sell Test		Sell Test			
300-201	0.7	support of the IP security architecture	IPsecv3				IDeacy3 v4 * C		IPsecv3_v1.*_I			
	<del> </del>	support of the IP security architecture support for automated key management	IKEv2				IPsecv3_v1.*_C IKEv2_v1.*_C	+	IKEv2_v2.*_I	+		
	<del>                                     </del>		ESP									
500 007	6.44	support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I			
2500-267	6.11	Application Requirements	DNC Olicat				Calf Tast		Colf Took			
	1	support of DNS client/resolver functions	DNS-Client	+			Self Test	<del> </del>	Self Test	<del> </del>		
	1	support of Socket application program interfaces	SOCK	+			Self Test	<del> </del>	Self Test	<del> </del>		
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test			
		support of a DNS server application	DNS-Server				Self Test	1	Self Test			
500 007		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I			
500-267	6.2	Routing Protocol Requirements	1014									
		support of the intra-domain (interior) routing	IGW				Self Test		OSPFv3_v1.*_I			
		support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP_v1.*_I			
500-267	6.4	Transition Mechanism Requirements	.= .									
		support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test			
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test			
2500-267	6.8	Network Management Requirements							Self Test			
		support of network management services	SNMP				Self Test		Self Test			
500-267	6.9	Multicast Requirements										
		support of basic multicast	Mcast				Self Test					
		full support of multicast communications	SSM				Self Test		Self Test			
500-267	6.10	Mobility Requirements										
		support of mobile IP capability.	MIP				Self Test		Self Test			
		support of mobile network capabilities	NEMO				Self Test		Self Test			
2500-267	6.3	Quality of Service Requirements										
		support of Differentiated Services capabilities	DS				Self Test		Self Test			
500-267	6.12	Network Protection Device Requirements										
		support of common NPD reqts	NPD				N1 N2 N3 N4_v1.3					
		support of basic firewall capabilities	FW				N1_FW_v1.3					
		support of application firewall capabilities	APFW				Self Test					
		support of intrusion detection capabilities	IDS				N3_IDS_v1.3					
		support of intrusion protection capabilities	IPS				N4_IPS_v1.3					
500-267	6.5	Link Specific Technologies										
		support of robust packet compression services	ROHC				Self Test		Self Test			
	1	support of link technology [O:1]		Р			Self Test	Self Declaration	Self Test	Self Declaration		
	1								1	1		
		(repeat as needed) support of link technology	Link=						1	<u> </u>		
12		< Check HERE if this stack's DOC include		nforma	tion abo	ut test	ed capabilities and o	ptions on an attached page	3 of notes.	•		
							1 12 4	(1100 0 4 0	1.60 1.6			
							Indication of USGv6-v1 Recommended Level of Support for device type / stack role.  Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.  Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.					
Blank - SDOC makes no declaration for this capability.  P Passed required tests of USGv6-V1 requirements for these capabilities.												
N See notes page for details on the level of support of USGv6-v1 reequirements for this capability.							Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.					
		capability not supported in product.					, , ,					
								** ** **		1.00		
t Suite -	Specific	USGv6 Test suite used for test. See: http://www.anto			ications.h	tml	Note # - reference to a detailed note about this capability or result on attached pa Component Ref - Supplier / Product / Stack ID of distinctly tested component that provides this capability.					

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary  USGv6-v1 SDOC-v1.10										-v1 SDOC-v1.10 Page 3	
Field Product Id:						Stack I	d:				
13				Context /	Supported Capabilities				Notes about USG	v6-v1 Capabilities.	
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interoperability	Test Lab / Result ID, Note
NOTE #	Keierence	Section	030V0-V1 F10IIIe Requirements	Орион	11031	Kouter	NFD	Comormance/NFD	rest Lab / Nesult ID, Note	interoperability	rest Lab / Nesult ID, Note
1											
Discussion:											
Diocussio											
2											
Discussion:											
3											
Discussion:											
4											
7					l						
Discussion	1:				I	1 1					
5											
Discussion	1:										
6											
Discussion	1:										
7											
Discussion	n:										
	<u></u>										
8											
Discussion	n:										
9											
Discussion	n:										
10											
					<u>I</u>	<u> </u>					
Discussion: Vendor's Congral Notes / Discussion about this Product / Stack's canabilities:											
Vendor's General Notes / Discussion about this Product / Stack's capabilities:											

**General**: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field

Field Description and Instructions

- 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completable field.
- 2 Product Identifier: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- **USGv6 Capability Summary**: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- **Signature Block**: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

**Description and Instructions** 

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

**Product Id/Stack Id**: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

**Host, Router and Network Protection (NPD)** columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

**Test Suite Conformance and Interoperability** columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

**Additional Options Tested**: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.

Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.

Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.