Suppl	iers Declaration of	Conformity for U	SGv6 Products		USGv6-v1 SDOC-v1.1 Page 1					
1	The Document Re	quiring Conform	ity:		USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)					
2	Product Identifier:			Cisco 5940						
3	Supplier's Name,	Supplier's Name, Address and SDOC Contact Details								
	Systems, Inc.									
	170 West Tasman Dr.									
LISA	Jose, CA 95134									
4	Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.									
	IOS 15.2(1)GC1									
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.									
			Cisco ESR 59	940 Serie	;					
	1									
6		· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	•		of its USGv6 capabilities below and include a				
	detailed test result	Summary). e.g. e.	rampie-prou-iu/stack-1. USGV0-V	1-11081. IF	70-base+Auur-	Arch+IPsec-v3+IKEv2+SLAC+Link=Ethernet.				
				0 0						
		USGV	i-v1-Router:IPv6-Base+Addr-Arch	+SLAAC	·IGW+EGW+Lii	nk=Ethernet				
7	Self Contained or	Composite SDO	C? (Must indicate one).							
YES	All of the declared USG			•	•	provided by the use and/or integration of umodified				
	product are addressed by reported in this SDOC.	y orginal test results			r own unique USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section luct's page 2 will indicate which capabilities are provided by specific referenced components					
	-		(product_id/stack_id)							
8	Additional Declarations / Attachmer		nts: (List supplier & product-id/st	ack-id for	reterenced and	attached test results in the case of composite				
	Component Supp	ier	Product ID:	Stack II	: Not	es:				
[1]										
[2]										
[3]										
[4]										
9	Supplementary Attestations (Answer all).									
YES		s product is fully functional in YES This SDOC contains a capabilities only environments. That is, no test report for each unique IPv6 sta		YES		s listed in the product family in section 5 are implemented such capabilities are identical in form and function across the entire				
	claimed capabilities are		in the product. If not, please		product family. The specific conformance and interoperability test results for the					
	this product is deployed in a network		document which stacks/ports are not		USGv6 capabilities of an identified member of this product family are provided					
	nvironment that does not support covered, and how their IPv6					e SDOC attests to the fact that these tested USGv6				
10	Signature	IPv4.   capabilities differ from those reported Signature   Darryll Gadson				lentical and unmodified for all the products cited above.				
				Date	<u> </u>					
	Print Name / Title	Darryll Gadson, L	ead USGv6 Cisco Systems							

		iers Declaration of Conformity for USGv6 Products: Declared Capabilities and Test F						esuits Summary		USGv6-v1 SDOC-v1.1 Pag			
roduct	ld:	Cisco 5940		Stack	ld:			IOS 15.2(1)GC1					
			Context /	Suppo	rted Cap	abilities	i e	USGv6 Testing I	Program Results				
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID	), Note		
eference	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interopoperability	or Component	Ref		
500-267	6.1	IPv6 Basic Requirements						·					
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base		Р		Basic_v1.*_C	UNH/IOL-10842	Basic_V1.*_I	UNH/IOL-10845			
		support of stateless address auto-	SLAAC		Р		SLAAC-V1.*_C	UNH/IOL-10844	SLAAC-V1.0_I	UNH/IOL-10849			
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test				
		support of stateful (DHCP) address auto-	DHCP-Client				Self Test		DHCP_Client_v1.*_I				
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test				
		support of neighbor discovery security	SEND				Self Test		Self Test				
500-267	6.6	Addressing Requirements											
		support of addressing architecture reqts	Addr-Arch		Р		Addr_Arch_v1.*_C	UNH/IOL-10843	Addr Arch v1.* I	UNH/IOL-10846			
		support of cryptographically generated	CGA				Self Test		Self Test				
500-267	6.7	IP Security Requirements											
000 20.		support of the IP security architecture	IPsecv3				IPsecv3 v1.* C		IPsecv3 v1.* I				
		support for automated key management	IKEv2				IKEv2 v1.* C		IKEv2v1.0 I				
		support for encapsulating security payloads in	ESP				ESPv3 v1.* C		ESP v1.* I				
500-267	6.11	Application Requirements											
200 201	0.11	support of DNS client/resolver functions	DNS-Client				Self Test		Self Test				
	<del>                                     </del>	support of Socket application program	SOCK	<del>                                     </del>			Self Test		Self Test				
	1	support of 30cket application program support of IPv6 uniform resource identifiers	URI	1		1	Self Test		Self Test				
		support of a DNS server application	DNS-Server				Self Test		Self Test				
	1	support of a DHCP server application	DHCP-Server				Self Test		DHCP Serv v1.* I				
500-267	6.2	Routing Protocol Requirements	Diloi ocivei				OCH TOST		DITOT_OCTV_VTI				
300-207	0.2	support of the intra-domain (interior) routing	IGW		N		Self Test		OSPFv3 v1.* I	UNH/IOL-10848, See	a Note		
		support for inter-domain (interior) routing	EGW		P		Self Test		BGP_v1.*_I	UNH/IOL-10847	e Note		
500-267	6.4	Transition Mechanism Requirements	LGW				Sell Test		BGF_V11	UNI 1/10L-10047			
300-201	0.4	support of interoperation with IPv4-only	IPv4				Self Test		Self Test				
		support of fine-logeration with the v4-only support of tunneling IPv6 over IPv4 MPLS	6PE				Self Test		Self Test				
500-267	6.8	Network Management Requirements	01 L				Jeli Test		Self Test				
300-207	0.0	support of network management services	SNMP				Self Test		Self Test				
500-267	6.9	Multicast Requirements	SINIVIE				Sell Test		Sell Test				
BF 300-201	0.9	support of basic multicast	Mcast				Self Test						
		full support of multicast communications	SSM				Self Test		Self Test				
2500-267	6 10	Mobility Requirements	OOW				Jeli Test		Oeli Test				
P300-20 <i>1</i>	0.10	support of mobile IP capability.	MIP				Self Test		Self Test				
	1	support of mobile network capabilities	NEMO				Self Test		Self Test				
2500-267	6.3	Quality of Service Requirements	IVEIVIO				OCH TOST		OCH TOSE				
300-207	0.3	support of Differentiated Services capabilities	DS				Self Test		Self Test				
		PHB Id	D3				Self Test		Sell Test				
2500 267	7 6 1 2	Network Protection Device Requirements					Jeli Test						
300-207	0.12		NDD				MAINIOINIOINIA						
	<u> </u>	support of common NPD regts	NPD				N1 N2 N3 N4						
	<u> </u>	support of basic firewall capabilities	FW				N1_FW						
	1	support of application firewall capabilities	APFW			-	N2_App_FW						
	1	support of intrusion detection capabilities	IDS IPS			-	N3_IDS N4 IPS	<del> </del>					
		support of intrusion protection capabilities	IPS				N4_IPS						
2500-267	6.5	Link Specific Technologies					2.42						
		support of robust packet compression	ROHC				Self Test	0 (10 )	Self Test	0.150.1.11			
12		support of link technology [O:1]	Link=Ethernet		Р		Self Test	Self Declaration	Self Test	Self Declaration			
		(repeat as needed) support of link	Link=	<u> </u>									
	Χ	< Check HERE if this stack's DOC in	nformat	tion ab	out tested capal	pilities and options on an	attached page 3	of notes.	l				
			1 1114			<u> </u>	Indication of IICO C at Decommonded I and of Common for decide to the						
Level		of support for USGv6-v1 Requirements for c		Color	Indication of USGv6-v1 Recommended Level of Support for device type / stack role.  Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.								
		SDOC makes no declaration for this capability											
Р		I required tests of USGv6-V1 requirements for t			Indicates cabability	that is unusal for a given device t	ype / stack role. Do i	not select without care	eful ar				
N	See no	iee notes page for details on the level of support of USGv6-v1 reequirements for this					Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.						
Х	USGv6	capability not supported in product.						· · · · · · · · · · · · · · · · · · ·					
	- Speci	fic USGv6 Test suite used for test. See: http://w	ww.antd nist go	v/usav6	/test-spec	cification	1	Note # - reference to a detailed	note about this canal	oility or result on attack	hed n		
st Suite			90	.,	-50. opol		1		about tino oupui	, or roomit on allao			
		ID - Abbreviation of accredited laboratory and it	s local identifier	for this t	est result	ŀ	Component Ref - S	upplier / Product / Stack ID of dis	tinctly tested compon	ent that provides this	canal		

Supplie	ers Decla	ration	of Conformity for USGv6 Products: I	Notes Page a	nd Det	ailed T	est Re	sults Summary		USGv6-v	1 SDOC-v1.1 Page 3	
	Product	Product Id: Cisco 594				Stack	ld:		IOS 15.2(1)GC1			
				Context / Supported Capabilities					Notes about USGv6-v1 Capabilities.			
	Spec /			Configuration				Test Suite		Test Suite		
Note #	Reference	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Test Lab / Result ID, Note	Interopoperability	Test Lab / Result ID, Note	
1	RFC2740		OSPF for IPv6	IGW		c(M)				OSPFv3_v1.*_I	NH/IOL-10848; Test Case 4	
			supports an older implementation of this RFC a			critical fa		iny means. Our produ	icts will function fine when im			
Discussi	ion:	we will	take steps to modify our implementation to cor	rect this behavior	r in a fut	ure relea	ise.	1	Τ	1	1	
2	RFC2740		OSPF for IPv6	IGW		c(M)				OSPFv3_v1.*_I	UNH/IOL-10848; Test Case 3.2	
			implementation is in accordance with the RFC		. The tes		eds to b	e written and execute	I ed differently to get the desire			
Discussi	ion:	provide	ed by UNH-IOL for additional details		1		ı	1			T	
	_											
3												
4												
Discussi	ion:											
5												
Discussi	ion:											
Discussi												
6												
D:												
Discussi	ion:							1		1		
7												
Discussi	ion:											
8												
Discussi	ion:											
9												
Discussi	ion:											
10												
10	<u> </u>											
Discussi												
General	Notes / Dis	cussior	about this Product / Stack's capabilities:									

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-

## Field Description and Instructions

- 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completeable field.
- 2 Product Identifier: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and ameil
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product
- 6 USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- 10 Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

## Field Description and Instructions

11 Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

**Product Id/Stack Id**: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

**Test Suite Conformance and Interoperability** columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major

The supplier completes the adjacent **Test Lab and Result Id** column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab,

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

12 Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

**Options for Test Lab and Result Id**: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.