			INFORMATION				
	SUPF		SUPPLIER SIGNATURE	ns			
SUPPL	SUPPLIER NAME Trellix Public Sector L		Signed by: Alexander Chapin	_ DS			
SUPPL	TrellixPSLegal@trellix.com		Mexander (LapitVP, Public Sector Sales Suzanne				
	ACCREDITED I	_ABORATORY	ACCREDITED LABORATORY SIGN	IATURE			
LABO	RATORY NAME	UNH InterOperability Laboratory	Signed by: Michayla Newcombe				
LABO	RATORY CONTACT EMAIL	usgv6-sdoc@iol.unh.edu	Michayla Newcombienior Manager				
	[2] PRODUCT VE	RSION TESTED	[3] PRODUCT ID				
eP	O On-prem 5.10.0 Servi	ce Pack 1 Update 5 (2.0.0)	Trellix Endpoint Security	Suite			
		[4] PRODL	JCT FAMILY				
	APPLICABLE SEF	RIES HARDWARE	APPLICABLE SERIES SOFTWA	ARE			
			ePO On-prem 5.10.0 Service Pack 1 Update 5 (2.0.0): DXL Broker Management 6.1.1 TIE Management 4.7.0 DXL Client 6.0.3 Agent 5.4 Endpoint Security 10.7.11 (Mac) Endpoint Security 10.7.18 (Windows) TACC 8.4.4.125 (Windows) TACC 8.4.4.125 (Windows) TACC 8.4.2 (Windows) EDR 4.2.1 (Linux) Policy Auditor 6.5.10 (Windows) Policy Auditor 6.5.10 (Mac) Policy Auditor 6.5.10 (Linux) IVX Cloud				
			COMPOSITE SDOC				
	iitary : All of the declared cassed by original test results	apabilities of this product are reported in this SDoC.	Composite: Some or all of the capabilities of this product are provided by the use and/or integration of unmodified components that have their own unique SDoCs. All of the relevant referenced SDoCs are identified in section 6 and linked.				
[6] REF	SUPPLIER	PRODUCT ID/STACK ID	CAPABILITY SUMMARY	COMPOSITE SDOC LINK			
i.	Trellix Public Sector LLC	Frellix Endpoint Security Suite/ePO On-prem 5.10.0 Service Pack 1 Update 5 (2.0.0)	JSGv6-r1:App-Serv				
		[7] USGV6-CAPAB	LE REQUIREMENTS				
Πu	SGv6-r1-Capable-Host	USGv6-r1-Capable-Router		pable-NPP			
	_	[8] PROFILE(S) REFERENCED				
i.	NIST SP 500-267Br1, U	JSGv6 Profile					
ii.		IOI OLIDDI EMENTA	ADV ATTENTATIONS				
		* *	ARY ATTESTATIONS				
That is operated	s, no claimed capabilities a ted in a dual stack (IPv6 ar	al in dual stack environments. re invalidated if this product is ad IPv4) network environment.	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4.				
unique covere		If not, the stacks/ports not ow their IPv6 capabilities differ	All of the products listed in the product family in section 4 are implemented such that their capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the capabilities of an identified member of this product family are provided in this SDoC. The SDoC attests that these tested capabilities are identical and unmodified for all the products cited above.				

Host Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY			
[11]	CAPABILITY	CONFOR	RMANCE	INTEROPERABILI	TY/FUNCTIONAL	NOTES		
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID			
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F				
-	Core	Core_R1v1.*_C		Core_R1v1.*_I				
-	Extended-ICMP	Self-Test		Self-Test				
-	PLPMTUD	Self-Test		Self-Test				
-	ND-Ext	Self-Test		Self-Test				
-	ND-WL	Self-Test		Self-Test				
-	SEND	Self-Test		Self-Test				
-	SLAAC	SLAAC_R1v1.*_C		SLAAC_R1v1.*_I				
-	PriAddr	Self-Test		Self-Test				
-	DHCP- Stateless	DHCP- Stateless_R1v1 .*_C		DHCP- Stateless_R1v1 .*_I				
-	DHCP-Client	DHCP- Client_R1v1.*_C		DHCP- Client_R1v1.*_I				
-	DHCP-Client- Ext	Self-Test		Self-Test				
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I				
-	DHCP-Prefix- Ext	Self-Test		Self-Test				
-	6Lo	Self-Test		Self-Test				

Host Capabilities

		Self-Test	Self-Test		
-	Happy-Eyeballs	Sell-Test	3en-1est		
-	Addr-Arch	Addr- Arch_R1v1.*_C	Addr- Arch_R1v1.*_I		
-	CGA	Self-Test	Self-Test		
-	DNS-Client	Self-Test	Self-Test		
-	URI	Self-Test	Self-Test		
-	NTP-Client	Self-Test	Self-Test		
-	NTP-Server	Self-Test	Self-Test		
-	DNS-Server	Self-Test	Self-Test		
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_I		
-	DHCP-Server- Ext	Self-Test	Self-Test		
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_I		
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I		
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I		
-	SSHV2	Self-Test	Self-Test		
-	TLS	Self-Test	Self-Test		
-	TLS-1.3	Self-Test	Self-Test		
-	Tunneling-IP	Self-Test	Self-Test		

Host Capabilities

-	Tunneling-UDP	Self-Test	Self	f-Test		
-	XLAT	Self-Test	Self	f-Test		
-	NAT64	Self-Test	Self	-Test		
-	DNS64	Self-Test	Self	-Test		
-	SNMP	Self-Test	Self	-Test		
-	Tunneling	Self-Test	Self	-Test		
-	DiffServ	Self-Test	Self	-Test		
-	NETCONF	Self-Test	Self	-Test		
-	SSM	Self-Test	Self	-Test		
-	Multicast	Multicast_R1v1 .*_C	Multica	est_R1v1 *_I		
-	ECN	Self-Test	Self	-Test		
-	Link =	Self-Test	Self	-Test		

Router Capabilities

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY
[11] SUPPORTED		CONFOR TEST	MANCE RESULT ID	INTEROPERABIL TEST	TY/FUNCTIONAL RESULT ID	NOTES
CAPABILITY	CAPABILITY	SELECTION		SELECTION		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F		
-	Core	Core_R1v1.*_C		Core_R1v1.*_I		
-	Extended-ICMP	Self-Test		Self-Test		
-	PLPMTUD	Self-Test		Self-Test		
-	ND-Ext	Self-Test		Self-Test		
-	ND-WL	Self-Test		Self-Test		
-	SEND	Self-Test		Self-Test		
-	SLAAC	SLAAC_R1v1.*_C		SLAAC_R1v1.*_I		
-	PrivAddr	Self-Test		Self-Test		
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I		
-	DHCP-Prefix- Ext	Self-Test		Self-Test		
-	6Lo	Self-Test		Self-Test		
-	Addr-Arch	Addr- Arch_R1v1.*_C		Addr- Arch_R1v1.*_I		
-	CGA	Self-Test		Self-Test		

USGv6 Profile Supplier's Declaration of Conformity (SDoC) R1.1

Router Capabilities

DNS-Client	Self-Test	Self-Test	
URI	Self-Test	Self-Test	
NTP-Client	Self-Test	Self-Test	
NTP-Server	Self-Test	Self-Test	
DNS-Server	Self-Test	Self-Test	
DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_I	
DHCP-Server- Ext	Self-Test	Self-Test	
DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_I	
OSPF	Self-Test		
OSPF-IPsec	Self-Test		
OSPF-Auth	Self-Test	OSPF- Auth_R1v1.*_I	
OSPF-Ext	Self-Test	Self-Test	
OSPF-Trans	Self-Test	Self-Test	
OSPF-Graceful		Self-Test	
ISIS	Self-Test	Self-Test	
IS-IS-Auth	Self-Test	Self-Test	
IS-IS-Ext	Self-Test	Self-Test	
IS-IS-MT	Self-Test	Self-Test	
	URI NTP-Client NTP-Server DNS-Server DHCP-Server-Ext DHCP-Relay OSPF OSPF-IPsec OSPF-Auth OSPF-Trans OSPF-Graceful ISIS IS-IS-Auth IS-IS-Ext	URI NTP-Client Self-Test NTP-Server DNS-Server DHCP-Server DHCP-Server-Ext DHCP-Relay DHCP-Relay DHCP-Relay Cospf Self-Test Self-Test	DNS-Client URI Self-Test Self-Test Self-Test NTP-Client NTP-Server Self-Test DNS-Server DHCP- DHCP-Server Self-Test DHCP-Server-R1v1.*_C DHCP-Server-R1v1.*_C DHCP-Relay DHCP-Relay CSPF DHCP-Relay Self-Test OSPF OSPF-Auth Self-Test OSPF-Auth Self-Test OSPF-Trans OSPF-Trans OSPF-Graceful Self-Test Self-Test

R1.1 Router Capabilities

		Self-Test	BGP_R1v1.*_I	
-	BGP			
-	BGP-Reflect	Self-Test	Self-Test	
-	BGP-Graceful	Self-Test	Self-Test	
-	BGP-FlowSpec	Self-Test	Self-Test	
-	BGP-OV	Self-Test	Self-Test	
-	BGP-VPLS	Self-Test	Self-Test	
-	BGP-EVPN	Self-Test	Self-Test	
-	BGP-6VPE	Self-Test	Self-Test	
-	BGP-MVPN	Self-Test	Self-Test	
-	MPLS	Self-Test	Self-Test	
-	CE-Router	CE_Router_R1v 1.*_C	CE_Router_R1v 1.*_I	
-	VRRP	Self-Test	Self-Test	
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I	
-	IPsec-VPN	IPsec- VPN_R1v1.*_C	IPsec- VPN_R1v1.*_I	
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I	
-	IPsec-SHA-512- VPN	IPsec-SHA-512- VPN_R1v1.*_C	IPsec-SHA-512- VPN_R1v1.*_I	
-	SSHV2	Self-Test	Self-Test	
-	TLS	Self-Test	Self-Test	

-	TLS-1.3	Self-Test	Self-Test	
-	Tunneling-IP	Self-Test	Self-Test	
-	Tunneling-UDP	Self-Test	Self-Test	
-	GRE	Self-Test	Self-Test	
-	DS-Lite	Self-Test	Self-Test	
-	LW4over6	Self-Test	Self-Test	
-	MAP-E	Self-Test	Self-Test	
-	MAP-T	Self-Test	Self-Test	
-	XLAT	Self-Test	Self-Test	
-	NAT64	Self-Test	Self-Test	
-	DNS64	Self-Test	Self-Test	
-	6PE	Self-Test	Self-Test	
-	LISP	Self-Test	Self-Test	
-	SNMP	Self-Test	Self-Test	
-	Tunneling	Self-Test	Self-Test	
-	DiffServ	Self-Test	Self-Test	
-	NETCONF	Self-Test	Self-Test	
-	SSM	Self-Test	Self-Test	

Router Capabilities

NIST.SP.500-281Ar1s

-	PIM-SM	Self-Test	Self-Test	
-	PIM-SM-IPsec	Self-Test	Self-Test	
-	PIM-SM-BiDir	Self-Test	Self-Test	
-	Multicast	Multicast_R1v1. *_C	Multicast_R1v1. *_I	
-	ECN	Self-Test	Self-Test	
-	Link =	Self-Test	Self-Test	

Application Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
Trellix Endpoint	t Security Suite/eF	O On-prem 5.10.0) Service Pack 1 L	Jpdate 5 (2.0.0)	USGv6-r1:App-Serv		
[11]	CAPABILITY	CAPABILITY CONFORMANCE INTEROPERABIL		LITY/FUNCTIONAL	NOTES		
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID		
NOTES	IPv6-ONLY			IPv6- ONLY_R1v1.*_F	UNH-IOL/40568	The product did not shorten multiple consecutive 16-bit groups of zeros to "::" when displaying IPv6 addresses in its local logs.	
-	App-Serv=			APP- ONLY_R1v1.*_F			
-	Link =			Self-Test			

NPP Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY			
[11]	CAPABILITY	CONFOR		INTEROPERABILI		NOTES		
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID			
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F				
-	FW	FW_R1v1.*_C						
-	APFW	Self-Test						
-	IDS	FW_R1v1.*_C						
-	IPS	FW_R1v1.*_C						
-	Link =	Self-Test						

Switch Capabilities

[10] PRODUCT ID/ STACK ID						CAPABILITY SUMMARY	
[11]	CAPABILITY	CONFORMANCE		INTEROPERABILITY/FUNCTIONAL			
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	NOTES	
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	DHCPv6-Guard	Self-Test		Self-Test			
-	RA-Guard	Self-Test		Self-Test			
-	MLD-Snooping	Self-Test		Self-Test			
-	Link =	Self-Test		Self-Test			

1	CONTACT INFORMATION	Supplier name, email and signature (digital recommended). Include printed name and date if wet ink signed. Accredited laboratory name, email and signature (digital recommended). Include printed name and date if wet ink signed			
2	PRODUCT VERSION TESTED	Firmware/ software version of product declared			
3	PRODUCT ID	Suppliers concise name for product declared			
4	PRODUCT FAMILY	Applicable hardware or software with an unmodified IPv6 stack from "PRODUCT VERSION TESTED"			
5	UNITARY OR COMPOSITE	Indicate if this is a unitary or composite SDoC. If composite is checked, composite SDoC must be linked in section 6.			
6	REF	Reference number to profile(s) reference in this SDoC			
	SUPPLIER	Supplier name			
	PRODUCT ID/STACK ID	Product ID must match field 3. As there may be more than one unique IPv6 stack, stack ID identifies particular stack described in CAPABILITY SUMMARY. Each unique stack requires a CAPABILTY SUMMARY.			
	CAPABILITY SUMMARY	The strong notation as described in NIST-SP-500-267Ar1 that describes the product capabilities of the given stack.			
	COMPOSITE SDOC LINK	URL link to composite SDoC referenced.			
7	USGV6-CAPABLE REQUIREMENTS	Refer to section 5 in NIST-SP-500-267Br1 for CSS strings referenced in this section. Check the appropriate box if the product meets the requirements.			
8	PROFILE(S) REFERENCED	Profile(s) referenced in the SDoC.			
9	SUPPLEMENTARY ATTESTATIONS	Attestations made by the supplier. Check all that apply.			
10	PRODUCT ID/STACK ID	PRODUCT ID/STACK ID for stack documented on given page.			
	CAPABILITY SUMMARY	CAPABILITY SUMMARY for stack documented on given page.			
11	SUPPORTED CAPABILITY	"PASS" – All requirements of the capability have been met			
		"NOTES" – See notes for details regarding the level of support for this capability			
		"X" – Capability not supported			
		BLANK – No declaration for this capability			
	CAPABILITY	IPv6 Capability as described in NIST-SP-500-267Ar1.			
	TEST SELECTION	Test Selection Tables version of capabilities with existing test programs. Capabilities without an existing test program are			
	DECLUTION	indicated with "Self-Test"			
	RESULT ID	Abbreviation of accredited laboratory and unique identifier of test result. Capabilities with "Self-Test" can be self-declared			
	NOTES	writing "Self Declaration" in the cell.			
	NOTES	The cell must be filled out if "NOTE" is indicated for SUPPORTED CAPABILITY. Suppliers may use notes to clarify			
		unsupported features or non-passing results.			

SUPPLIER GENERAL NOTES