Supplie	ers Declaration of Confe	ormity for USGv6 Pro	oducts			USGv6-v1 SDOC-v1.1 Page 1						
1	The Document Requir					USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)						
2	Product Identifier: CISCO ASA-SM blade											
3	Supplier's Name, Add	ress and SDOC Con	tact Details									
	ystems, Inc.											
	st Tasman Dr.											
	se, CA 95134											
USA	Due de et es Telete d'De	alamada Duada at Ida at		-££:	4: 441							
4	Product as Tested/De	ciarea: Product identi	fier, version/revision information, details	or configura	uon testea.							
			9.0.(0)	16								
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.											
	ASA SM blade for 6500 series, 7600 series Routers											
6	<b>USGv6 Capability summary.</b> (For each distinct IPv6 stack in the product provide a summary of its USGv6 capabilities below and include a detailed test result summary). e.g. example-prod-id/stack-1: USGv6-v1-Host: IPv6-Base+Addr-Arch+IPsec-v3+IKEv2+SLAC+Link=Ethernet.											
			USGv6-v1-NPD: FV	/+Link=Ether	rnet							
7	Self Contained or Con	nposite SDOC? (Mus	t indicate one).									
YES	All of the declared USGv6 cap addressed by orginal test rest	•	Some or all of the USGv6 capabilities of this product are provided by the use and/or integration of umodified components that have their own unique USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indicate which capabilities are provided by specific referenced components (product-id/stack-id).									
8	Additional Declarations / Attachments: (List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).											
	Component Supplier		Product ID:	Stack ID:		Notes:						
[1]												
[2]												
[3]												
[4]												
9	Supplementary Attest	ations (Answer all).										
YES	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4.		This SDOC contains a capabilities test report for each unique IPv6 stack in the product. If not, please document which stacks/ports are not covered, and how their IPv6 capabilities differ from those reported in this SDOC.	YES	USGv6 capab specific confo member of thi	lucts listed in the product family in section 5 are implemented such that their bilities are identical in form and function across the entire product family. The rmance and interoperability test results for the USGv6 capabilities of an identified is product family are provided in this SDOC. The SDOC attests to the fact that USGv6 capabilities are identical and unmodified for all the products cited above.						
10	Signature	Darryll Gadson		Date								
	Print Name / Title	Darryll Gadson Lead	USGv6 Cisco Systems	1								

	-	01 404 014					Results Summary		0.0(0)46				
roduct ld	:	Cisco ASA-SM Stack							9.0(0)16				
			Context /	Suppo	rted Capa	bilities			Program Results				
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #, o			
Reference			Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interopoperability	Component Ref			
P500-267	6.1	IPv6 Basic Requirements											
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base				Basic_v1.*_C		Basic_V1.*_I				
		support of stateless address auto-configuration	SLAAC				SLAAC-V1.*_C		SLAAC-V1.0_I				
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test				
		support of stateful (DHCP) address auto-configuration	DHCP-Client				Self Test		DHCP_Client_v1.*_I				
		support of automated router prefix delegation support of neighbor discovery security extensions	DHCP-Prefix SEND				Self Test		Self Test				
DE00 007	0.0		SEND				Self Test		Self Test				
P500-267	6.6	Addressing Requirements											
		support of addressing architecture reqts	Addr-Arch				Addr_Arch_v1.*_C		Addr_Arch_v1.*_I				
DE00.007		support of cryptographically generated addresses	CGA				Self Test		Self Test				
P500-267	6.7	IP Security Requirements	ID 0				ID 0 1 1 0		15 0 1 1				
		support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I				
		support for automated key management	IKEv2 ESP				IKEv2_v1.*_C		IKEv2v1.0_I				
DE00 007	0.44	support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I				
P500-267	6.11	Application Requirements support of DNS client/resolver functions	DNS-Client				Call Tank		Call Tank				
		support of DNS client/resolver functions support of Socket application program interfaces	SOCK				Self Test Self Test		Self Test Self Test				
		support of Socket application program interfaces support of IPv6 uniform resource identifiers	URI				Self Test		Self Test				
		support of 1PV6 difficility resource identifiers support of a DNS server application	DNS-Server				Self Test		Self Test				
		support of a DNS server application	DHCP-Server				Self Test		DHCP Serv v1.* I				
P500-267	6.2	Routing Protocol Requirements	DI ICF-Server				Sell Test		DHCF_Selv_VII				
P500-267	0.2	support of the intra-domain (interior) routing protocols	IGW				Self Test		OSPFv3 v1.* I				
			EGW				Self Test		BGP v1.* I				
2500-267	6.4	support for inter-domain (exterior) routing protocols  Transition Mechanism Requirements	EGW				Sell Test		BGP_V1."_I				
-300-207	0.4	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test				
		support of funding IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test				
2500-267	6.8	Network Management Requirements	OFE				Sell Test		Self Test				
P300-207	0.0	support of network management services	SNMP				Self Test		Self Test				
P500-267	6.9	Multicast Requirements	SINIVIP				Sell Test		Sell Test				
1 300-201	0.3	support of basic multicast	Mcast				Self Test						
		full support of multicast communications	SSM				Self Test		Self Test				
P500-267	6.10	Mobility Requirements	OOW				Gen Test		Gen Test				
1 000 201	0.10	support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO				Self Test		Self Test				
P500-267	6.3	Quality of Service Requirements											
. 000 20.	0.0	support of Differentiated Services capabilities	DS				Self Test		Self Test				
		PHB Id					Self Test		00 7000				
P500-267	6.12	Network Protection Device Requirements											
000 201		support of common NPD regts	NPD			Р	N1 N2 N3 N4						
		support of basic firewall capabilities	FW			P	N1 FW	UNH/IOL-12424					
		support of application firewall capabilities	APFW				N2 App FW	01417102 12121					
		support of intrusion detection capabilities	IDS				N3 IDS						
		support of intrusion protection capabilities	IPS				N4 IPS						
P500-267	6.5	Link Specific Technologies											
		support of robust packet compression services	ROHC				Self Test		Self Test				
		support of link technology [O:1]	Link=Ethernet			Р	Self Test	Self Declaration	Self Test	Self Declaration			
		55, [5.7]											
		(repeat as needed) support of link technology	Link=										
12				motic-	about to	otod so	abilition and anti-	on on ottoched name 2 of me	too				
12		< Check HERE if this stack's DOC includes a	additional infor	mation	about te	sted cap	Dabilities and option	is on an attached page 3 of no	tes.				
Level Level of support for USGv6-v1 Requirements for capability.						Color	Color Indication of USGv6-v1 Recommended Level of Support for device type / stack role.						
FEAGI		- SDOC makes no declaration for this capability.						is recommendend as mandatory (unco					
Р		required tests of USGv6-V1 requirements for these capabilities.					Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.						
N		notes page for details on the level of support of USGv6-v1 reequirements for this capability.					Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.						
Χ	USGv6	capability not supported in product.											
t Suite - 9	Specific U	ecific USGv6 Test suite used for test. See: http://www.antd.nist.gov/usgv6/test-specifications.html  ult ID - Abbreviation of accredited laboratory and its local identifier for this test result.					Note # - reference to a detailed note about this capability or result on attached particles.  Component Ref - Supplier / Product / Stack ID of distinctly tested component that provides this capability.						

1	C-v1.1 Page	
Note #   Spec   Reference   Section   USGv6-v1 Profile Requirements   Configuration   Option   Host   Router   NPD   Conformance(NPD   Test Lab / Result ID, Note   Interopoperability   Test Lab		
Note # Reference   Section   USGVS-VI Profile Requirements   Coston   Host   Router   NPD   ConformanceNPD   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / 1   Test Lab / Result ID, Note   Interopoperability   Test Lab / 1   Test Lab / Result ID, Note   Te		
1	/ Result ID, Note	
Discussion:	Ttoodit 1D, Ttoto	
2		
Discussion:		
3   Discussion:  4   Discussion:  5   Discussion:  6   Discussion:  7   Discussion:  8   Discussion:  9   Discussion:  10   Discussion:		
Discussion:		
A		
Discussion:  5  Discussion:  6  Discussion:  7  Discussion:  8  Discussion:  9  Discussion:  10  Discussion:		
S		
Discussion:  6		
Discussion:		
Discussion:  7  Discussion:  8  Discussion:  9  Discussion:  10  Discussion:		
7 Discussion:  8 Discussion:  9 10 10 Discussion:		
Discussion:		
8   Discussion:		
Discussion:  9  10  Discussion:  10  Discussion:		
9 Discussion: Disc		
Discussion:  10  Discussion:		
10 Discussion:		
Discussion:		
Discussion:  General Notes / Discussion about this Product / Stack's capabilities:		
General Notes / Discussion about this Product / Stack's capabilities:		

**General**: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usqv6/testing.html. Contact: usqv6-project@antd.nist.gov.

Field

## Field Description and Instructions

- 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completeable field.
- **2 Product Identifier**: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- 6 USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

## Description and Instructions

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

**Product Id/Stack Id**: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

**Test Suite Conformance and Interoperability** columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent **Test Lab and Result Id** column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

12 Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

**Options for Test Lab and Result Id**: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.