Suppli			ducts			USGv6-v1 SDOC-v1.1 Page 1					
1	The Document Requir	ring Conformity:				USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)					
2	Product Identifier:				Cisco 45	00X					
3	Supplier's Name, Add	ress and SDOC Conta	ct Details								
	•										
	se, CA 95134										
<u> </u>	Product as Tested/De	clared: Product Identifi	er version/revision information details	of configura	ation tested						
	Troduct do roctourbo	olar oa: 1 Todaot Taomini	or, verdierin evidieri innermation, detaile	or cornigan	ation toolog.						
			108 03.03.	.00.SG							
	The Document Requiring Conformity: Product Identifier: Supplier's Name, Address and SDOC Contact Details Supplier's Name, Address and SDOC Contact Details Froduct as Tested/Declared: Product Identifier, version/revision information, details of configuration tested. IOS 03.03.00.SG Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below. Cisco 4500X Series Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below. Cisco 4500X Series IOS 03.03.00.SG										
5	Product Family (other	products using same IF	Pv6 stack(s) to which these results are	declared to	apply). Che	eck Product Family attestation below.					
			0								
			Cisco 4500)	X Series							
											
6											
	Te.g. example-prod-id/si	ack-1. USGV0-V1-HUSL	IPVO-Base+Addi-Arch+iPsec-v3+IKE	VZ+SLAC+L	.irik=Etrierrie	ti.					
		US	GV6-v1-Router:IPv6-Base+Addr-Arch	+SLAAC+IC	GW+EGW+L	ink=Ethernet					
7	Salf Cantained or Composite SDOC2 (Must indicate one)										
			· · · · · · · · · · · · · · · · · · ·	hilities of this n	roduct are prov	ided by the use and/or integration of umodified components that have their own					
TES											
	3200										
0	Additional Declaration	no / Attachmento: // ici	augustian e product id/atack id for rafa	ranged and	attached too	t regults in the coop of composite products)					
0		ns / Attachments: (List			allached les						
	Component Supplier		Product ID:	Stack ID:		Notes:					
[1]											
[2]											
[4]											
9	Supplementary Attest	ations (Answer all).									
YES				YES	All of the products listed in the product family in section 5 are implemented such that their USGve						
	capabilities are invalidated if this product is deployed in a network environment that does				capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests to the fact that these tested						
			1 ''								
			differ from those reported in this SDOC.		USGv6 capab	pilities are identical and unmodified for all the products cited above.					
10	Signature	Darryll Gadson		Date							
	Print Name / Title	Darryll Gadson, Lead l	ISGv6 Cisco Systems	ļ	1						
		12 arry ii Caasori, Load (2000 Oyulullu								

		ers Declaration of Conformity for USGv6 Pro			Negulia Guillilary	1		GGv6-v1 SDOC-v1.1 Pag					
oduct Id	:	Cisco 4500X	Stack Id			IOS 03.03.00.SG							
			Context / Supported Capabilitie			bilities			Program Results				
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #,			
	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interopoperability	Component Ref			
P500-267	6.1	IPv6 Basic Requirements	ID 0 D				5 1 1 2	10000	5 1 1/4 1	11111101 10000			
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base		Р		Basic_v1.*_C	UNH/IOL-12926	Basic_V1.*_I	UNH/IOL-12929			
		support of stateless address auto-configuration	SLAAC		Р		SLAAC-V1.*_C	UNH/IOL-12928	SLAAC-V1.0_I	UNH/IOL-12933			
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test				
		support of stateful (DHCP) address auto-configuration	DHCP-Client				Self Test		DHCP_Client_v1.*_I				
		support of automated router prefix delegation	DHCP-Prefix SEND				Self Test		Self Test				
2500-267	6.6	support of neighbor discovery security extensions Addressing Requirements	SEND				Self Test		Self Test				
-300-207	0.0	support of addressing architecture regts	Addr-Arch		Р		Addr_Arch_v1.*_C	LINH/IOL-12027	Addr Arch v1.* I	UNH/IOL-12930			
		support of addressing architecture requisions support of cryptographically generated addresses	CGA				Self Test	UN1/10L-12927	Self Test	ONH/IOL-12930			
2500-267	6.7	IP Security Requirements	CGA				Jeli Test		Sen rest				
300-201	0.7	support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I				
		support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2v1.0 I				
		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I				
500-267	6.11	Application Requirements											
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test				
		support of Socket application program interfaces	SOCK	1			Self Test		Self Test				
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test				
		support of a DNS server application	DNS-Server				Self Test		Self Test				
		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I				
P500-267	6.2	Routing Protocol Requirements											
		support of the intra-domain (interior) routing protocols	IGW		N		Self Test		OSPFv3_v1.*_I	UNH/IOL - 12932 , See Note 1,2			
		support for inter-domain (exterior) routing protocols	EGW		Р		Self Test		BGP_v1.*_I	UNH/IOL-12931			
500-267	6.4	Transition Mechanism Requirements											
		support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test				
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test				
2500-267	6.8	Network Management Requirements							Self Test				
		support of network management services	SNMP				Self Test		Self Test				
2500-267	6.9	Multicast Requirements											
		support of basic multicast	Mcast				Self Test						
		full support of multicast communications	SSM				Self Test		Self Test				
2500-267	6.10	Mobility Requirements											
		support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO				Self Test		Self Test				
2500-267	6.3	Quality of Service Requirements					0 15 7 1		2 " 7 1				
		support of Differentiated Services capabilities	DS				Self Test		Self Test				
2500 007	0.40	PHB Id					Self Test						
2500-267	6.12	Network Protection Device Requirements	NDD				NAINIOINIOINIA						
		support of common NPD regts	NPD				N1 N2 N3 N4						
	-	support of basic firewall capabilities	FW APFW				N1_FW N2_App_FW						
	-	support of application firewall capabilities support of intrusion detection capabilities	IDS				N2_App_FW N3_IDS						
	-	support of intrusion detection capabilities support of intrusion protection capabilities	IPS				N4_IPS						
P500-267	6.5	Link Specific Technologies	IFO				N4_IF3						
300-201	0.5	support of robust packet compression services	ROHC				Self Test		Self Test				
		support of robust packet compression services support of link technology [O:1]			Р		Self Test	Self Declaration	Self Test	Self Declaration			
		Support of milk technology [O.1]	L LUIDINOL				Con root	Son Douglation	Con root	Co Doorardion			
		(repeat as needed) support of link technology	l ink=										
40	\ <u></u>	, , , , , , , , , , , , , , , , , , , ,					a a la liliti a a construction		4				
12	X	< Check HERE if this stack's DOC includes a	idditional infor	mation	about te	sted cap	pabilities and option	ns on an attached page 3 of no	tes.				
Lavial		support for USGv6.v1 Requirements for canability					Indication of ISCOVC at Decommanded I and of Commant for decide time Latest and						
Level	Level of support for USGv6-v1 Requirements for capability. Blank - SDOC makes no declaration for this capability. Passed required tests of USGv6-V1 requirements for these capabilities.					Color							
						Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile. Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.							
Р													
N	See note	See notes page for details on the level of support of USGv6-v1 reequirements for this capability.					Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.						
Χ	USGv6	Gv6 capability not supported in product.							· · · · · · · · · · · · · · · · · · ·				
		SGv6 Test suite used for test. See: http://www.antd.nist.c						Note # - reference to					

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary											USGv6-v1 SDOC-v1.1 Page 3	
	Product Id:		Cisco 4500X	Stack Id:					IOS 03.03.00.SG			
	2/			Context /	Supported Capabilities			Notes about USG	v6-v1 Capabilities.			
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interopoperability	Test Lab / Result ID, Note	
	RFC											
1	2328,2740	The Roi	OSPFv3_IOT_4_3	IGW	m across r	c(M)	eas Wher	r faced with equal cost it	ne router did not choose the route v	OSPFv3_v1.*_I	UNH/IOL - 12932	
Discussion	The Router does not make the correct routing decision within an Autonomous System across multiple areas. When faced with equal cost, the router did not choose the route with the largest area ID. Discussion:											
2	RFC 4552		Authentication/Confidentialify for OSPFv3	IGW	th Cisco al	c(M)	rogress on	implementation of this fe	atura	OSPFv3_v1.*_I	UNH/IOL - 12932	
This feature is currently not supported on this specific device. Please check back with Cisco about the progress on implementation of this feature. Discussion:												
3	=											
Discussion:												
4	ı	1	!	1	1 '	1						
Discussion	1:											
5	i											
Discussion	1:											
6		<u> </u>										
Discussion	1:		Т						I			
7		<u> </u>		ļ	<u> </u>	<u> </u>						
Discussion	ı:	<u> </u>				-						
8		<u> </u>			<u> </u>	<u> </u>						
Discussion	1:	<u> </u>	'		<u> </u>							
9		<u> </u>		<u> </u>	<u> </u>	<u> </u>						
Discussion	1:	<u> </u>			ļ'							
10		<u> </u>		ļ	<u> </u>	<u> </u>						
Discussion:												
General Notes / Discussion about this Product / Stack's capabilities:												

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field Description and Instructions 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completeable field. 2 Product Identifier: Supplier's concise name for the product declared.

3 Suppliers Name, Address and Contact Details: Company name and point of

contact for SDOC questions, street address, phone and email.

- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- **6 USGv6 Capability Summary**: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Field Description and Instructions

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent **Test Lab and Result Id** column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (*e.g.* "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

12 Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.