Supplie	rs Declaration of Conf			lucts		USGv6-v1 SDOC-v1.1 Page						
1	The Document Requir	ring Conforr	nity:			USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)						
2	Product Identifier: Cisco Catalyst 3750X											
3												
	ystems, Inc. st Tasman Dr.											
	e, CA 95134											
USA	A Ó											
4	Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.											
	IOS15.0(2)SE											
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.											
	Cisco Catalyst 3750V2, Cisco Catalyst 3750E, Cisco Catalyst 3750C, Cisco Catalyst 3750X											
6				ct IPv6 stack in the product provide a IPv6-Base+Addr-Arch+IPsec-v3+IKI			capabilities below and include a detailed test result summary).					
				USGv6-v1-Host:IPv6-Base+Ado	Ir-Arch+SLAA	AC+Link=Eth	nernet					
7	Self Contained or Cor	-	•	<u>'</u>								
YES	All of the declared USGv6 capabilities of this product are addressed by original test results reported in this SDOC. Some or all of the USGv6 capabilities of this product are provided by the use and/or integration of umodified components that have their unique USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indica capabilities are provided by specific referenced components (product-id/stack-id).											
8	Additional Declaration	ns / Attachm	nents: (List	supplier & product-id/stack-id for ref		attached tes	at results in the case of composite products).					
	Component Supplier			Product ID:	Stack ID:		Notes:					
[1]												
[2]												
[3]												
[4]												
9	Supplementary Attest	t ations (Ansv	ver all).									
YES	environments. That is, no clai capabilities are invalidated if t	ris product is fully functional in IPv6 only priving in the state of t		This SDOC contains a capabilities test report for each unique IPv6 stack in the product. If not, please document which stacks/ports are not covered, and how their IPv6 capabilities differ from those reported in this SDOC.	1.20	capabilities ar conformance of this produc	All of the products listed in the product family in section 5 are implemented such that their USt capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified memb of this product family are provided in this SDOC. The SDOC attests to the fact that these teste USGv6 capabilities are identical and unmodified for all the products cited above.					
10	Signature				Date							
	Print Name / Title	Anil Bhatt, L	ead USGv6	6 Cisco Systems								

11	Suppli	ers Declaration of Conformity for USGv6 Pro	ducts: Declare	d Capat	pilities and	d Test I	Results Summary		U	SGv6-v1 SDOC-v1.1 Pag			
Product Id:		Cisco Catalyst 3750X			IOS 15.0(2)SE								
			Context /	Suppo	rted Capab	oilities			Program Results				
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #,			
eference		USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interopoperability	Component Ref			
2500-267	6.1	IPv6 Basic Requirements											
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	Р			Basic_v1.*_C	UNH/IOL-12748	Basic_V1.*_I	UNH/IOL-12751			
		support of stateless address auto-configuration	SLAAC	P			SLAAC-V1.*_C	UNH/IOL-12749	SLAAC-V1.0_I	UNH/IOL-12752			
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test				
		support of stateful (DHCP) address auto-configuration	DHCP-Client				Self Test		DHCP_Client_v1.*_I				
	-	support of automated router prefix delegation	DHCP-Prefix		-		Self Test		Self Test				
2500-267	6.6	support of neighbor discovery security extensions Addressing Requirements	SEND				Self Test		Self Test				
200-207	0.0	Addressing Requirements						UNH/IOL-12747. See Addr Notes.		UNH/IOL-12750, See Addr Note			
		support of addressing architecture regts	Addr-Arch	N			Addr Arch v1.* C	Number 2	Addr Arch v1.* I	Number 1			
		support of addressing architecture regis	CGA	IN			Self Test	Number 2	Self Test	Number			
500-267	6.7	IP Security Requirements	CGA				Sell Test		Sell Test				
300-201	0.7	support of the IP security architecture	IPsecv3				IPsecv3 v1.* C		IPsecv3 v1.* I				
		support for automated key management	IKEv2				IKEv2 v1.* C		IKEv2v1.0 I	1			
		support for encapsulating security payloads in IP	ESP				ESPv3 v1.* C		ESP v1.* I	+			
500-267	6 11	Application Requirements	LOI						LOF_VII	<u> </u>			
200 201	V. 11	support of DNS client/resolver functions	DNS-Client				Self Test		Self Test	+			
		support of Socket application program interfaces	SOCK	1			Self Test	1	Self Test	†			
		support of Gooker application program interfaces	URI				Self Test		Self Test	•			
		support of a DNS server application	DNS-Server				Self Test		Self Test				
		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I	+			
500-267	6.2	Routing Protocol Requirements	DITOT OCIVE				OCH TOST		Brief _GCIV_VI1				
000 201		support of the intra-domain (interior) routing protocols	IGW				Self Test		OSPFv3 v1.* I				
		support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP v1.* I	1			
500-267	6.4	Transition Mechanism Requirements											
000 201		support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test				
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test				
500-267	6.8	Network Management Requirements							Self Test				
		support of network management services	SNMP				Self Test		Self Test				
500-267	6.9	Multicast Requirements											
		support of basic multicast	Mcast				Self Test						
		full support of multicast communications	SSM				Self Test		Self Test				
500-267	6.10	Mobility Requirements											
		support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO				Self Test		Self Test				
500-267	6.3	Quality of Service Requirements											
		support of Differentiated Services capabilities	DS				Self Test		Self Test				
		PHB Id					Self Test						
500-267	6.12	Network Protection Device Requirements											
		support of common NPD reqts	NPD				N1 N2 N3 N4						
		support of basic firewall capabilities	FW				N1_FW						
		support of application firewall capabilities	APFW				N2_App_FW						
		support of intrusion detection capabilities	IDS				N3_IDS						
		support of intrusion protection capabilities	IPS				N4_IPS						
500-267	6.5	Link Specific Technologies											
		support of robust packet compression services	ROHC				Self Test		Self Test				
		support of link technology [O:1]	Link=Ethernet	Р			Self Test	Self Declaration	Self Test	Self Declaration			
		(repeat as needed) support of link technology	Link=										
12	Х	< Check HERE if this stack's DOC includes a	dditional infor	mation	about tes	ted car	pabilities and option	ns on an attached page 3 of no	tes.				
	^`							To an an annual page of the					
	_						1						
.evel		support for USGv6-v1 Requirements for capability.		Color	Indication of USGv6-v1 Recommended Level of Support for device type / stack role.								
		SDOC makes no declaration for this capability.			Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.								
Р	Passed required tests of USGv6-V1 requirements for these capabilities.						Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.						
N		ee notes page for details on the level of support of USGv6-v1 reequirements for this capability.						Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.					
X		capability not supported in product.			1		, , , , , , , , , , , , , , , , , , , ,	,					
	,												

Suppliers	ers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary									USG	v6-v1 SDOC-v1.1 Page	
	Product Id:		Cisco Catalyst 3750X		Stack I	d:		IOS 15.0(2)SE				
				Context /	Suppo	orted Cap	abilities		Notes about USG	3v6-v1 Capabilities.		
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interopoperability	Test Lab / Result ID, Note	
											, , , , , , , , , , , , , , , , , , , ,	
1	RFC3484	5	Address Architecture for IPv6	Addr_Arch	М					Addr_Arch_v1.*_I	UNH/IOL-12750; Test Case 1.:	
		Cisco's o	surrent implementation of this does not account for longe oes not use longest matching prefix if it is deprecated. C	st matching prefix.	This was	good to pa	ass these to	ests based on a test spec	cification we have tested with until r	now. However the current	est specification tests that the	
Discussion	:	device di	bes not use longest matering prenx in it is deprecated.	lisco wiii take steps	I	I	Inemation	Correct this behavior in	luture releases	I		
2	RFC3484		Address Architecture for IPv6	Addr_Arch	М				UNH/IOL-12747; Test Case 1.2B			
		Cisco's current implementation of this does not account for longest matching prefix. This was good to pass these tests based on a test specification we have tested with until now. However the current test specification tests the device does not use longest matching prefix if it is deprecated. Cisco will take steps to modify our implementation to correct this behavior in future releases										
Discussion	:				1	T		I				
3	-											
Discussion	:											
4												
Discussion					•	•	•					
5	•											
Discussion												
6												
Discussion	:				1			ı	I	ı		
7												
Discussion	:											
8												
Discussion	:											
9												
Discussion												
10												
Discussion General No	tes / Discuss	ion abou	t this Product / Stack's capabilities:	l	1	1			l .	1		

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field Description and Instructions

- 1 The Document Requiring Conformity. Identifies the profile version implemented. Not a user completeable field.
- 2 Product Identifier: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families
- 6 USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Field Description and Instructions

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent **Test Lab and Result Id** column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

12 Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.

Further Description: http://www.antd.nist.gov/usgv6/testing.html, and NIST SP 500-267 USGv6 Testing Program Users Guide available at the website.