


Suppliers Declaration of Conformity for USGv6 Products

USGv6-v1 SDOC-v1.4 Page 1

1	The Document Requiring Conformity:			USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)		
2	Product Identifier:	MS Windows 7				
3	Supplier's Name, Address and SDOC Contact Details Microsoft - One Microsoft Way, Redmond WA - 98052 Christopher Palmer - IPv6 PM for Windows ipv6pm@microsoft.com					
4	Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.					
Windows 7 6.1.7600						
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.					
Windows 7 and Windows Server 2008 R2						
6	USGv6 Capability summary. (For each distinct IPv6 stack in the product provide a summary of its USGv6 capabilities below and include a detailed test result summary). e.g. example-prod-id/stack-1: USGv6-v1-Host: IPv6-Base+Addr-Arch+IPsec-v3+IKEv2+SLAC+Link=Ethernet.					
USGv6-v1-Host: IPv6-Base+Addr-Arch+SLAAC+Link = Ethernet						
7	Self Contained or Composite SDOC? (Must indicate one).					
YES	All of the declared USGv6 capabilities of this product are addressed by original test results reported in this SDOC.		Some or all of the USGv6 capabilities of this product are provided by the use and/or integration of unmodified components that have their own unique USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indicate which capabilities are provided by specific referenced components (product-id/stack-id).			
8	Additional Declarations / Attachments: (List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).					
	Component Supplier	Product ID:	Stack ID:	Notes:		
[1]						
[2]						
[3]						
[4]						
9	Supplementary Attestations (Answer all).					
YES	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4.	YES	This SDOC contains a capabilities test report for each unique IPv6 stack in the product. If not, please document which stacks/ports are not covered, and how their IPv6 capabilities differ from those reported in this SDOC.	YES	All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests to the fact that these tested USGv6 capabilities are identical and unmodified for all the products cited above	
10	Signature	Daniel Havey 		Date	July 5, 2016	
	Print Name / Title	Daniel Havey - Program Manager Windows TCP/IP				

7/5/2016

Product Id:		MS Windows 7			Stack Id:		Windows 7			
Spec / Reference	Section	USGv6-v1 Profile Requirements		Context / Configuration Option	Supported Capabilities		USGv6 Testing Program Results			
		Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID Note # or Component Ref	Test Suite Interoperability	Test Lab / Result ID Note # or Component Ref		
SP500-267	6.1	IPv6 Basic Requirements			IPv6-Base	P	Basic_v1.*_C	UNH/IOL - 4856	Basic_V1.*_I	UNH/IOL - 4857
		support of IPv6 base (IPv6 ICMPv6 PMTU ND)			SLAAC	P	SLAAC_V1.*_C	UNH/IOL - 5339	SLAAC_V1.0_I	UNH/IOL - 5341
		support of stateless address auto-configuration			PrivAddr		Self Test		Self Test	
		support of SLAAC privacy extensions			DHCP-Client		Self Test		DHCP_Client_v1.*_I	UNH/IOL - 5432
		support of stateful (DHCP) address auto-			DHCP-Prefix		Self Test		Self Test	
		support of automated router prefix delegation			SEND		Self Test		Self Test	
		support of neighbor discovery security extensions								
SP500-267	6.6	Addressing Requirements			Addr-Arch	P	Addr_Arch_v1.*_C	UNH/IOL - 5462	Addr_Arch_v1.*_I	UNH/IOL - 5463
		support of addressing architecture reqts			CGA		Self Test		Self Test	
		support of cryptographically generated addresses								
SP500-267	6.7	IP Security Requirements			IPsecv3		IPsecv3_v1.*_C		IPsecv3_v1.*_I	
		support of the IP security architecture			IKEv2		IKEv2_v1.*_C		IKEv2v1.0_I	
		support for automated key management			ESP		ESPv3_v1.*_C		ESP_v1.*_I	
SP500-267	6.11	Application Requirements			DNS-Client		Self Test		Self Test	
		support of DNS client/resolver functions			SOCK		Self Test		Self Test	
		support of Socket application program interfaces			URI		Self Test		Self Test	
		support of IPv6 uniform resource identifiers			DNS-Server		Self Test		Self Test	
		support of a DNS server application			DHCP-Server		Self Test		DHCP_Serv_v1.*_I	
SP500-267	6.2	Routing Protocol Requirements			IGW		Self Test		OSPFv3_v1.*_I	
		support of the intra-domain (interior) routing			EGW		Self Test		BGP_v1.*_I	
SP500-267	6.4	Transition Mechanism Requirements			IPv4		Self Test		Self Test	
		support of interoperation with IPv4-only systems			6PE		Self Test		Self Test	
SP500-267	6.8	Network Management Requirements			SNMP		Self Test		Self Test	
SP500-267	6.9	Multicast Requirements			Mcast		Self Test		Self Test	
		support of basic multicast			SSM		Self Test		Self Test	
SP500-267	6.10	Mobility Requirements			MIP		Self Test		Self Test	
		support of mobile IP capability			NEMO		Self Test		Self Test	
SP500-267	6.3	Quality of Service Requirements			DS		Self Test		Self Test	
SP500-267	6.12	Network Protection Device Requirements			NPD		N1 N2 N3 N4			
		support of common NPD reqts			FW		N1_FW			
		support of basic firewall capabilities			APFW		N2_App_FW			
		support of application firewall capabilities			IDS		N3_IDS			
		support of intrusion detection capabilities			IPS		N4_IPS			
SP500-267	6.5	Link Specific Technologies			ROHC		Self Test		Self Test	
		support of robust packet compression services		Link=Ethernet	P		Self Test		Self Test	
		support of link technology (O/I)								
		(repeat as needed) support of link technology	Link=							
12	< Check HERE if this stack's DOC includes additional information about tested capabilities and options on an attached page 3 of notes.									

Level	Level of support for USGv6-v1 Requirements for capability.	Color	Indication of USGv6-v1 Recommended Level of Support for device type / stack role.
Blank - SDOC makes no declaration for this capability			Indicates capability that is recommended as mandatory (unconditional MUST) in the USGv6-v1 Profile
P	Passed required tests of USGv6-V1 requirements for these capabilities		Indicates capability that is unusual for a given device type / stack role. Do not select without careful analysis
N	See notes page for details on the level of support of USGv6-v1 requirements for this capability		Indicates capability that is left optional / conditional by the recommendations of the USGv6-v1 Profile
X	USGv6 capability not supported in product		

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1.

Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: <http://www.antd.nist.gov/usgv6/testing.html>. Contact: usgv6-project@antd.nist.gov

Field	Description and Instructions	Field	Description and Instructions
1	The Document Requiring Conformity Identifies the profile version implemented. Not a user completable field.	11	Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.
2	Product Identifier: Supplier's concise name for the product declared.		Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.
3	Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.		Host, Router and Network Protection (NPD) columns: identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.
4	Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports ongoing test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g. hardware configuration, operating system, etc.).		Test Suite Conformance and Interoperability columns: identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.
5	Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.		The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3 (e.g. "See Note N"). See the USGv6 testing website to identify the test lab, and find contact details.
6	USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).		Cells marked Self Test have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.
7	Self Contained or Composite SDOC: If this SDOC relies on the test results of other distinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.	12	Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary
8	Additional Declarations / Attachments: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC		Headings and Special Notations: as described
9	Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities, multiple stacks present, product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply		Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory. (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability. (3) See attachment or note 'N', where the supplier explains variations in greater detail.
10	Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below		