Supplie	ers Declaration of Confo	ormity for U	SGv6 Prod	ucts				USGv6-v1 SDOC	-v1.1 Page				
1	The Document Requir							USGv6 Profile Version 1.0, July 2008. (NI					
2	Product Identifier:						Cisco 3	560					
3	Supplier's Name, Addı	ress and SD	OC Contac	t Details									
	ystems, Inc.												
	st Tasman Dr.												
	se, CA 95134												
USA	Product as Tested/Dec	clared: Prod	uct Identifie	r version/re	evision information, details	of configura	tion tested						
-	i roduct us resteurbee	Jidi Cd. 1 100	act racritine	1, 10131011110	violon imormation, actails	or cornigare	tion testeu.						
					IOS 12.2(5	3)SE1							
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.												
	С	isco 3560-E	series, Ciso	co 3560-X s	eries, Cisco 3560-G series	s, catalyst bl	ade series -	- CBS-3012, CBS-3020, CBS-3032					
6	6 USGv6 Capability summary. (For each distinct IPv6 stack in the product provide a summary of its USGv6 capabilities below and include a detailed test result summary). e.g. example-prod-id/stack-1: USGv6-v1-Host: IPv6-Base+Addr-Arch+IPsec-v3+IKEv2+SLAC+Link=Ethernet.												
7 YES	Self Contained or Composite SDOC? (Must indicate one). All of the declared USGv6 capabilities of this product are addressed by orginal test results reported in this SDOC. Self Contained or Composite SDOC? (Must indicate one). Some or all of the USGv6 capabilities of this product are provided by the use and/or integration of umodified components that have the addressed by orginal test results reported in this SDOC. USGv6-v1-Router:IPv6-Base+Addr-Arch+IGW+SLAAC+Link=Ethernet Self Contained or Composite SDOC? (Must indicate one).												
					capabilities are provided by spe	ecific referenced components (product-id/stack-id).							
8	Additional Declarations / Attachments: (List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).												
	Component Supplier			Product ID):	Stack ID:		Notes:					
[1]													
[2]													
[3]													
[4]													
9	Supplementary Attesta	ations (Answ	ver all).										
YES	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4.			for each unique not, please do not covered, a	ontains a capabilities test report ue IPv6 stack in the product. If ocument which stacks/ports are and how their IPv6 capabilities se reported in this SDOC.	YES	All of the products listed in the product family in section 5 are implemented such that their USG capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified membe of this product family are provided in this SDOC. The SDOC attests to the fact that these tested USGv6 capabilities are identical and unmodified for all the products cited above.						
10	Signature	Darryll Gads	son			Date							
	Print Name / Title	Darryll Gads	on, Lead U	SGv6 Cisco	Systems								

		ers Declaration of Conformity for USGv6 Pro	uucis. Decialei	u Capab			Nesults Sullillary	ı		GV6-v1 SDOC-v1.1 Pag		
Product Id:		Cisco 3560	Stack Id				IOS12.2(53)SE1					
			Context / Supported Capabilities			bilities	s		Program Results			
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #,		
	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interopoperability	Component Ref		
P500-267	6.1	IPv6 Basic Requirements	ID 0 D				5 1 1 2	1000	5 1 1/4 1	1,1,11,1101, 5,100		
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base		Р		Basic_v1.*_C	UNH/IOL-5492	Basic_V1.*_I	UNH/IOL-5493		
		support of stateless address auto-configuration	SLAAC		Р		SLAAC-V1.*_C	UNH/IOL-5498	SLAAC-V1.0_I	UNH/IOL-5499		
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test			
		support of stateful (DHCP) address auto-configuration	DHCP-Client				Self Test		DHCP_Client_v1.*_I			
		support of automated router prefix delegation	DHCP-Prefix SEND				Self Test		Self Test			
2500-267	6.6	support of neighbor discovery security extensions Addressing Requirements	SEND				Self Test		Self Test			
F300-201	0.0	support of addressing architecture regts	Addr-Arch		Р		Addr Arch v1.* C	LINIH/IOL 5404	Addr Arch v1.* I	UNH/IOL-5495		
		support of addressing architecture requirements support of cryptographically generated addresses	CGA				Self Test	UN11/10L-3494	Self Test	UNIT/IOL-5495		
2500-267	6.7	IP Security Requirements	CGA				Sell Test		Sell Test			
300-201	0.7	support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I			
		support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2v1.0 I			
		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I			
2500-267	6.11	Application Requirements										
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test			
		support of Socket application program interfaces	SOCK				Self Test		Self Test			
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test			
		support of a DNS server application	DNS-Server				Self Test		Self Test			
		support of a DHCP server application	DHCP-Server				Self Test		DHCP Serv v1.* I			
2500-267	6.2	Routing Protocol Requirements										
		support of the intra-domain (interior) routing protocols	IGW		N		Self Test		OSPFv3_v1.*_I	UNH/IOL-5497, Notes 1,2, and		
		support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP_v1.*_I			
2500-267	6.4	Transition Mechanism Requirements										
		support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test			
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test			
2500-267	6.8	Network Management Requirements							Self Test			
		support of network management services	SNMP				Self Test		Self Test			
P500-267	6.9	Multicast Requirements										
		support of basic multicast	Mcast				Self Test					
		full support of multicast communications	SSM				Self Test		Self Test			
P500-267	6.10	Mobility Requirements										
		support of mobile IP capability.	MIP				Self Test		Self Test			
		support of mobile network capabilities	NEMO				Self Test		Self Test			
P500-267	6.3	Quality of Service Requirements							- 11-			
		support of Differentiated Services capabilities	DS				Self Test		Self Test			
2500 007		PHB Id					Self Test					
P500-267	6.12	Network Protection Device Requirements	NDD				NAINIOINIOINIA					
		support of common NPD regts	NPD				N1 N2 N3 N4					
		support of basic firewall capabilities	FW APFW				N1_FW					
		support of application firewall capabilities					N2_App_FW					
	-	support of intrusion detection capabilities support of intrusion protection capabilities	IDS IPS				N3_IDS N4_IPS					
P500-267	6.5	Link Specific Technologies	IFO				N4_IF3					
1 300-207	0.5	support of robust packet compression services	ROHC				Self Test		Self Test			
		support of robust packet compression services support of link technology [O:1]			Р		Self Test	Self Declaration	Self Test	Self Declaration		
		support of milk tearningy [O.1]	LINK LUICING				Och root	Con Beolaranon	Con root	Con Boolardion		
		(repeat as needed) support of link technology	l ink=									
40	\ <u></u>	, , , , , , , , , , , , , , , , , , , ,				.4	a a la liliti a a construction		4			
12	X	< Check HERE if this stack's DOC includes a	idditional infor	mation	about te	sted cap	Dabilities and option	is on an attached page 3 of no	tes.			
Lovel	Lovel of	pport for USGv6-v1 Requirements for capability.					Indication of IISGv6 v4 Pacammandad Laval of Support for davice type / stack rate					
Level		Blank - SDOC makes no declaration for this capability.					Indication of USGv6-v1 Recommended Level of Support for device type / stack role. Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.					
_												
Р		Passed required tests of USGv6-V1 requirements for these capabilities.						is unusal for a given device type / stack		•		
	See note	s page for details on the level of support of USGv6-v1 re-	equirements for thi	s capabilit	y.		Indicates capability that	is left optional / ocnditional by the reco	mmedations of the USGv6	-v1 Profile.		
Х	USGv6	apability not supported in product.										
		SGv6 Test suite used for test. See: http://www.antd.nist.c						Note # - reference to				

Suppliers	uppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary								USGv6-v1 SDOC-v1.1 Pag				
	Product Id:		Cisco 3560		Stack lo	i:		IOS 12.2(53)SE1					
				Context /			abilities		Notes about USGv6-v1 Capabilities.				
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interopoperability	Test Lab / Result ID) Note	
11010 11		00000011	occio vi i iomo noquiiomomo	- Option		- reducer	2	Comormanosi ii	1000 2007 1100010 125, 11010	interopoporability	root East Hoodit IE	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
1	RFC2740		OSPF for IPv6 pports an older implementation of this RFC and we belie	IGW	failura by	c(M)	Our pro	duate will function fine wh	on implemented according to our o	OSPFv3_v1.*_I	UNH/IOL-5497; Test		
Discussion			profits an order implementation of this KPC and we belied	ve it is not a critical	ialiule by	any mean	. Our pro	uucis wiii lunciion iine wii	en implemented according to our g	guidance. However, we will	take steps to modify ou	1	
2	RFC2740		OSPF for IPv6	IGW		c(M)					UNH/IOL-5497; Test Ca 4.5	ase 3.2,	
Discussion:		Cisco's implementation is in accordance with the RFC's for these tests. The testcase needs to be written and executed differently to get the desired result. Please contact Cisco to see the test report provided by UNH-IOL for additional details											
3	RFC4552			1014						0005 0 444	UNH/IOL-5497; Test Ca	ase 5.1,	
3			Authentication/Confidentiality for OSPFv3 IGW c(M) OSPFv3_v1.*_1 5.2 This protocol is supported on this specific device, however, some problems were uncovered during test. Cisco is working actively to address these issues and plans to retest the product once the issues have been resolv.							ease check			
Discussion:		back with Cisco about the progress on this issue.											
4													
Discussion	1:												
5													
Discussion	1:												
6													
Discussion	ı:												
7													
Discussion	1:												
8													
Discussion	ı:												
9													
Discussion	ı:												
10													
Discussion	ı:												
General Notes / Discussion about this Product / Stack's capabilities:													

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field Description and Instructions 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completeable field. 2 Product Identifier: Supplier's concise name for the product declared.

3 Suppliers Name, Address and Contact Details: Company name and point of

contact for SDOC questions, street address, phone and email.

- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- **6 USGv6 Capability Summary**: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Field Description and Instructions

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent **Test Lab and Result Id** column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (*e.g.* "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

12 Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.