Supplie	rs Declaration of Conformity for U		ucts			USGv6-v1 SDOC-v1.10 Page '					
1	The Document Requiring Conform	nity:				USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)					
2	Product Identifier: VMware ESXi 6.0.0										
3	Supplier's Name, Address and SDOC Contact Details										
	are, Inc 3401 Hillview Ave Palo Alto, CA, 94304										
4	Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.										
	ESXi 6.0.0										
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.										
6	USGv6 Capability summary. (For each distinct IPv6 stack in the product provide a summary of its USGv6 capabilities below and include a detailed test result summary). e.g. example-prod-id/stack-1: USGv6-v1-Host: IPv6-Base+Addr-Arch+IPsec-v3+IKEv2+SLAC+Link=Ethernet.										
	USGv6-v1-Host: IPv6-Base+Addr-Arch+SLAAC+ESP+IPsecv3+Link = Ethernet										
7	Self Contained or Composite SDOC? (Must indicate one).										
YES	All of the declared USGv6 capabilities of this addressed by orginal test results reported in t		N/A	unique USGv6 SDOCs. All of t	bilities of this product are provided by the use and/or integration of umodified components that have their own he relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indicate by specific referenced components (product-id/stack-id).						
8	Additional Declarations / Attachm	ents: (List	supplier & pr	roduct-id/stack-id for refer	enced and a	attached test	results in the case of composite products).				
	Component Supplier		Product ID	):	Stack ID:		Notes:				
[1]											
[2]											
[3]											
[4] 9											
9	Supplementary Attestations (Answer all).  YES This product is fully functional in IPv6 only environments. That is, no claimed capabilities are										
	This product is fully functional are invalidated ifthis product is				YES	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support Ipv4.					
	This SDOC contains a capabilities test report for each unique IPv6 stack in the product. It not, the stacks/ports not covered are documented, and how their lpv6 capabilities differ from those reported are explained.					USGv6 capab specific confor member of this USGv6 capab	All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilities are identical and unmodified for all the products cited above.				
10	Signature Orna Berryr Print Name / Title Orna Berryr		or Program	Management Office	Date	17-May-16					
Coo inotes	Print Name / Title Orna Berryman / Director, Program Management Office										

11		ers Declaration of Conformity for USGv6 Prod											
Product Id:		VMware ESXi 6.0.0 Stack Id							ESXi 6.0.0				
			Context /	Suppo	rted Capa	bilities		USGv6 Testing F	Program Results				
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or		Test Lab / Result ID, Note #,			
eference P500-267	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Test Suite Interoperability	Component Ref			
500-267	6.1	IPv6 Basic Requirements support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	D			Basic v1.* C	UNH-IOL/20067	Basic V1.* I	UNH-IOL/20072			
		support of PMTU Discovery Protocol requirements	PMTU	P			Basic v1.* C	UNH-IOL/20067	Basic_V1I	UNH-IOL/20072			
		support of PMTO Discovery Protocol requirements support of stateless address auto-configuration	SLAAC	P			SLAAC-V1.* C	UNH-IOL/20067	SLAAC-V1.* I	UNH-IOL/20072			
		support of Stateless address auto-configuration	SLAAC - c(M)	P			SLAAC-V1. C	UNH-IOL/20068	SLAAC-V1.* I	UNH-IOL/20073			
		support of Cleation of Global Addresses support of SLAAC privacy extensions.	PrivAddr				Self Test	ON 1-10L/20000	Self Test	ONTI-TOE/20073			
		support of stateful (DHCP) address auto-configuration	DHCP-Client				DHCP Client v1.* C		DHCP Client v1.* I				
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test				
		support of neighbor discovery security extensions	SEND				Self Test		Self Test				
500-267	6.6	Addressing Requirements											
		support of addressing architecture regts	Addr-Arch	Р			Addr Arch v1.* C	UNH-IOL/20069	Addr Arch v1.* I	UNH-IOL/20074			
		support of cryptographically generated addresses	CGA				Self Test		Self Test				
500-267	6.7	IP Security Requirements											
		support of the IP security architecture	IPsecv3	Р			IPsecv3 v1.* C	UNH-IOL/20070	IPsecv3 v1.* I	UNH-IOL/20075			
		support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2 v2.* I				
		support for encapsulating security payloads in IP	ESP	Р			ESPv3 v1.* C	UNH-IOL/20071	ESP v1.* I	UNH-IOL/20076			
500-267	6.11	Application Requirements											
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test				
		support of Socket application program interfaces	SOCK				Self Test		Self Test				
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test				
		support of a DNS server application	DNS-Server				Self Test		Self Test				
		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I				
2500-267	6.2	Routing Protocol Requirements											
		support of the intra-domain (interior) routing protocols	IGW				Self Test		OSPFv3 v1.* I				
		support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP v1.* I				
500-267	6.4	Transition Mechanism Requirements											
		support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test				
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test				
500-267	6.8	Network Management Requirements							Self Test				
		support of network management services	SNMP	Р			Self Test	Self Declaration	Self Test	Self Declaration			
2500-267	6.9	Multicast Requirements											
		support of basic multicast	Mcast	Р			Self Test	Self Declaration	Self Test	Self Declaration			
		full support of multicast communications	SSM				Self Test		Self Test				
P500-267	6.10	Mobility Requirements											
		support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO				Self Test		Self Test				
2500-267	6.3	Quality of Service Requirements											
		support of Differentiated Services capabilities	DS				Self Test		Self Test				
2500-267	6.12	Network Protection Device Requirements											
		support of common NPD reqts	NPD				N1 N2 N3 N4_v1.3						
		support of basic firewall capabilities	FW				N1_FW_v1.3						
		support of application firewall capabilities	APFW				Self Test						
		support of intrusion detection capabilities	IDS				N3_IDS_v1.3						
		support of intrusion protection capabilities	IPS				N4_IPS_v1.3						
500-267	6.5	Link Specific Technologies											
		support of robust packet compression services	ROHC				Self Test		Self Test				
		support of link technology [O:1]	Link= Ethernet	Р			Self Test	Self Declaration	Self Test	Self Declaration			
								ļ					
		(repeat as needed) support of link technology	Link=	L	$\Box$					<u> </u>			
12		< Check HERE if this stack's DOC includes a	dditional infor	mation a	about tes	sted cap	pabilities and options	on an attached page 3 of notes	S				
Level	Level of	support for USGv6-v1 Requirements for capability.				Color	Indication of USGv6-v1 Recommended Level of Support for device type / stack role.						
	Blank - S	SDOC makes no declaration for this capability.					Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.						
Р	Passed	required tests of USGv6-V1 requirements for these capabi	lities.				Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.						
N		es page for details on the level of support of USGv6-v1 ree		capability	1.		Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.						
X USG/6 capability not supported in product.													
-													
t Suite - 9	Specific I	JSGv6 Test suite used for test. See: http://www.antd.nist.c	inv/usav6/test-snea	rifications	html			Note # - reference	to a detailed note about this	s capability or result on attached			
		Abbreviation of accredited laboratory and its local identifie			arutii		Component Ref - Supplier / Product / Stack ID of distinctly tested component that provides this capability.						

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary											r6-v1 SDOC-v1.10 Page 3
Field	Product Id:					Stack lo	d:				
13				Context /	Supported Capabilitie				Notes about USG	v6-v1 Capabilities.	
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interoperability	Test Lab / Result ID, Note
Note #	recipione	Occilon	OSCIONAL TOME REQUIEMENTS	Option	11031	Router	IN D	Comorniance/Ni D	rest Lab / Result ID, Note	interoperability	rest Lab / Result ID, Note
1											
Discussion	1:			ı	1		1	T	1		
2											
Discussion:											
3											
Discussion:											
4											
Discussion	1:										
5											
Discussion	1:										
6											
Discussion	1:			•		•					
7											
Discussion	1:		l	l .			ı		1		
8											
Discussion	1:										
9											
Discussion	1:										
10											
Discussion:											
Vendor's General Notes / Discussion about this Product / Stack's capabilities:											
L											