Supplie	ers Declaration of Conf	formity for USGv6 Prod	ducts		USGv6-v1 SDOC-v1.10 Page 1						
1	The Document Requi	ring Conformity:					USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)				
2	Product Identifier:				Cisco CGS 2520						
3	3 Supplier's Name, Address and SDOC Contact Details										
	Cisco Systems, Inc.										
	170 West Tasman Dr.										
	San Jose, CA 95134										
USA											
4	Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.										
	15.2(4)EA1										
5	Product Family (other	products using same IP	v6 stack(s) to	o which these results are	declared to	apply), <b>Che</b> o	ck Product Family attestation below.				
		<u> </u>									
6	USGv6 Capability sur	mmarv. (For each distin	ct IPv6 stack	in the product provide a s	summarv of	its USGv6 c	apabilities below and include a detailed test result summary).				
		- ·		Addr-Arch+IPsec-v3+IKEv	-		•				
			USGv6-v1	I-Host: IPv6-Base+Addr-	Arch+SLA	AC+Link=Et	hernet				
7	Self Contained or Composite SDOC? (Must indicate one).										
	All of the declared USGv6 ca	ided by the use and/or integration of umodified components that have their own									
	addressed by orginal test res	sults reported in this SDOC.					s are identified in section 8 and attached. This product's page 2 will indicate				
	which capabilities are provided by specific referenced components (product-id/stack-id).										
8	Additional Declarations / Attachments: (List supplier & product-id/stack-id for refe				enced and attached test results in the case of composite products).						
	<b>Component Supplier</b>		Product ID:				Notes:				
[1]											
[2]											
[3]											
[4]											
9	Supplementary Attestations (Answer all).										
		is fully functional in dual stack e		· · · ·	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are						
	are invalidate	d ifthis product is operated in a	a dual stack (6 ai	nd 4)network environment.		invalidated if this product is deployed in a network environment that does not support lpv4.					
	This SDOC of	ontains a capabilities test repo	rt for each uniqu	e IPv6 stack in the product. If		All of the prod	ucts listed in the product family in section 5 are implemented such that their				
	This SDOC contains a capabilities test report for each unique IPv6 stack in the product. If not, the stacks/ports not covered are documented, and how their Ipv6 capabilities differ from those reported are explained.					USGv6 capabilities are identical in form and function across the entire product family. The					
						specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilitiesare identical and unmodified for all the products cited above.					
10	Signature	nature Darryll Gadson			Date						
	Print Name / Title	Darryll Gadson, Lead L	JSGv6 Cisco	Systems		<u>.</u>					
See instru	See instructions for fields 1-12 on Page 4.										

uppliers Declaration of Conformity for USGv6 Products: Declared Capabilities and Test Results Summary							USGv6-v1 SDOC-v1.10 Page 2				
Cisco CGS 2520 Stack Id:								15.2(4)EA1			
		Context / Supported Capabili			hilities		USGv6 Testing P				
		Configuration	Guppo			Test Suite	Test Lab / Result ID, Note #, or		Test Lab / Result ID, Note #,		
	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Test Suite Interoperability	Component Ref		
B	Basic Requirements	option									
	support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	Р			Basic_v1.*_C	UNH-IOL/24278	Basic V1.* I	UNH-IOL/24281		
sι	support of PMTU Discovery Protocol requirements	PMTU	Р			Basic v1.* C	UNH-IOL/24278	Basic V1.* I	UNH-IOL/24281		
	support of stateless address auto-configuration	SLAAC	Р			SLAAC-V1.* C	UNH-IOL/24279	SLAAC-V1.* I	UNH-IOL/24282		
	support of Creation of Global Addresses	SLAAC - c(M)	Р			SLAAC-V1.*_C	UNH-IOL/24279	SLAAC-V1.*_I	UNH-IOL/24282		
	support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test			
р	port of stateful (DHCP) address auto-configuration	DHCP-Client				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I			
	support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test			
	support of neighbor discovery security extensions	SEND				Self Test		Self Test			
es	essing Requirements										
	support of addressing architecture reqts	Addr-Arch	Р			Addr_Arch_v1.*_C	UNH-IOL/24277	Addr_Arch_v1.*_I	UNH-IOL/24280		
s	support of cryptographically generated addresses	CGA				Self Test		Self Test			
C	curity Requirements										
	support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I			
	support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2_v2.*_I			
	support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I			
C	cation Requirements										
	support of DNS client/resolver functions	DNS-Client				Self Test		Self Test			
	support of Socket application program interfaces	SOCK				Self Test		Self Test			
	support of IPv6 uniform resource identifiers	URI				Self Test		Self Test			
	support of a DNS server application	DNS-Server				Self Test		Self Test			
	support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I			
	ng Protocol Requirements										
	port of the intra-domain (interior) routing protocols	IGW		_		Self Test		OSPFv3_v1.*_I			
	support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP_v1.*_I			
i	sition Mechanism Requirements	15.4				0 // 7 /		0.47			
	support of interoperation with IPv4-only systems	IPv4		_		Self Test		Self Test			
	support of tunneling IPv6 over IPv4 MPLS services	6PE		_		Self Test		Self Test			
	ork Management Requirements	ONIME				0.16 + 1		Self Test			
-	support of network management services	SNMP				Self Test		Self Test			
Ci	cast Requirements support of basic multicast	Mcast				Self Test					
	full support of multicast communications	SSM				Self Test		Self Test			
if	lity Requirements	33101				Sell Test		Sen rest			
	support of mobile IP capability.	MIP				Self Test		Self Test			
	support of mobile network capabilities	NEMO		-		Self Test		Self Test			
ŧ١	ty of Service Requirements	NEMIO				0011031		Sen rest			
5	support of Differentiated Services capabilities	DS				Self Test		Self Test			
~	ork Protection Device Requirements	00				00111031		Sell Test			
	support of common NPD regts	NPD				N1 N2 N3 N4_v1.3					
	support of basic firewall capabilities	FW				N1 FW v1.3					
	support of application firewall capabilities	APFW				Self Test					
	support of intrusion detection capabilities	IDS				N3_IDS_v1.3					
	support of intrusion protection capabilities	IPS				N4_IPS_v1.3			1		
S	Specific Technologies										
~	support of robust packet compression services	ROHC				Self Test		Self Test			
	support of link technology [O:1]		Р			Self Test	Self Declaration	Self Test	Self Declaration		
	(repeat as needed) support of link technology	Link=									
e	eck HERE if this stack's DOC includes a		mation	about te	sted ca	pabilities and options of	on an attached page 3 of notes				
~ ~	ort for USGV6-v1 Paguirements for constilling				Color	مالمرا	tion of USGV6-v1 Pasammanded La	al of Support for dovice t	une / stack role		
						Indication of USGv6-v1 Recommended Level of Support for device type / stack role. dicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.					
					Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.						
See notes page for details on the level of support of USGv6-v1 reequirements for this capability. Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.							rofile.				
it	lity not supported in product.										
Т	Test suite used for test. See: http://www.antd.nist.	gov/usgv6/test-spec	cifications	.html		Note # - reference to a detailed note about this capability or result on attached pag					
						Component R					
	viation of accredited laboratory and its local identified					Component R	ef - Supplier / Product / Stack ID of dist				

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary USGv6-v1 SDOC-v1.10 Page 3											
Field	Product Id:										
13				Context /	Stack Id: Supported Capabilities				Notes about USG	6v6-v1 Capabilities.	
	Spec / Reference	Castian		Configuration				Test Suite	Taski alı / Dasulki D. Nata	Test Suite	Teet Leb ( Beeuki D. Nete
Note #	Reference	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Test Lab / Result ID, Note	Interoperability	Test Lab / Result ID, Note
1											
Discussio	1:		1	1		1	T	1			
2											
Discussion:											
3											
Discussio	1:										
4											
Discussio	1:										
5											
Discussio	1:										
6											
Discussion	1:		1		n		1		1		
7											
Discussio	1:		1	1	1	I	I	ſ			
8											
Discussio	1:				r				ſ		
9											
Discussio	1:		1	Γ	[	1	1		I		
10											
Discussion:											
Vendor's General Notes / Discussion about this Product / Stack's capabilities:											

## Suppliers Declaration of Conformity for USGv6 Description and Instructions

USGv6-v1 SDOC-v1.10 Page 4

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field	Description and Instructions	Field	Description and Instructions
1	The Document Requiring Conformity: Identifies the profile version implemented. Not a user completable field.	11	<b>Summary of Results</b> : The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.
2	Product Identifier: Supplier's concise name for the product declared.		<b>Product Id/Stack Id</b> : The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.
3	Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.		Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.
4	<b>Product as Tested/Declared</b> : Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).		<b>Test Suite Conformance and Interoperability</b> columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.
5	<b>Product Family</b> : A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.		The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.
6	<b>USGv6 Capability Summary</b> : The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).		Cells marked <b>Self Test</b> have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.
7	Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.	12	<b>Additional Options Tested</b> : Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary. <b>Headings and Special Notations</b> : as described.
8	Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.		<b>Options for Test Lab and Result Id:</b> Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.
9	<b>Supplementary Attestations</b> : Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.	13	<b>Stack-1 Notes Instructions</b> : The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.
10	<b>Signature Block</b> : Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.		Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the

buyer.