Suppli	ers Declaration of Confo	rmity for USGv6 P	roducts		USGv6-v1 SDOC-v1.10 Page 1						
1	The Document Requirin	g Conformity:			USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)						
2	Product Identifier: RedHawk™ Linux® real-time operating system										
3											
	oncurrent Real-Time										
	th: Vince Hauber										
	81 Gateway Drive										
	ompano Beach, FL 33069										
(954) 9	54) 973-5095										
4	4 Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.										
	64-bit RedHawk 7.2 on Supermicro X10DRi with 2.1a BIOS										
5	Product Family (other pr	oducts using same	IPv6 stack(s) to which these	results are decl	ared to app	oly). Check Product Family attestation below.					
	Concurrent iHawk Series HQ000-x and HQ0G1-x										
6	USGv6 Capability summ	hary . (For each dis	tinct IPv6 stack in the produc	ct provide a sum	mary of its I	USGv6 capabilities below and include a detailed test result					
	summary). e.g. example-		Gv6-v1-Host: IPv6-Base+Ac								
	USGv6-v1-Host: IPv6-Base+Addr-Arch+SLAAC+DHCP-Client+ Link= Ethernet										
7	Self Contained or Comp										
YES	All of the declared USGv6 capabilities of this product are addressed by orginal test results reported in this SDOC. SDOC.										
8	Additional Declarations	/ Attachments: (Li	st supplier & product-id/stacl	k-id for reference	d and attac	ched test results in the case of composite products).					
	Component Supplier		Product ID:	Stack ID:		Notes:					
[1]											
[2]											
[3]											
[4]											
9	Supplementary Attestat										
	YES Capabilities are inv 4)network environ	validated ifthis product is	k environments.That is, no claimed coperated in a dual stack (6 and	YES	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support Ipv4.						
	YES This SDOC contains a capabilities test report for each unique IPv6 stack in the product. If not, the stacks/ports not covered are documented, and how their Ipv6 capabilities differ from those reported are explained.				All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilitiesare identical and unmodified for all the prodµcts cited above.						
10	Signature				<i>i1/1</i>	6/2017					
	Print Name / Title	VP, PRODUCT	MANAGEMENT								
See instr	uctions for fields 1-12 on Page 4.	-									

		ers Declaration of Conformity for USGv6 Pro								SGv6-v1 SDOC-v1.10 Pag			
Product Id:		RedHawk™ Linux® real-time operating system Stack Id:						7.2					
			Context /	Suppo	rted Capa	bilities			Program Results				
Spec / teference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note #, or Component Ref	Test Suite Interoperability	Test Lab / Result ID, Note #, Component Ref			
P500-267		IPv6 Basic Requirements											
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	Р			Basic_v1.*_C	UNH-IOL/27599	Basic_V1.*_I	UNH-IOL/27601			
		support of PMTU Discovery Protocol requirements	PMTU	Р			Basic_v1.*_C	UNH-IOL/27599	Basic_V1.*_I	UNH-IOL/27601			
		support of stateless address auto-configuration	SLAAC	Р			SLAAC-V1.* C	UNH-IOL/27600	SLAAC-V1.* I	UNH-IOL/27602			
		support of Creation of Global Addresses	SLAAC - c(M)	Р			SLAAC-V1.* C	UNH-IOL/27600	SLAAC-V1.* I	UNH-IOL/27602			
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test				
		support of stateful (DHCP) address auto-configuration	DHCP-Client	Р			DHCP_Client_v1.*_C	UNH-IOL/26722	DHCP_Client_v1.*_I	UNH-IOL/26723			
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test				
		support of neighbor discovery security extensions	SEND				Self Test		Self Test				
P500-267	6.6	Addressing Requirements											
		support of addressing architecture regts	Addr-Arch	Р			Addr Arch v1.* C	UNH-IOL/27603	Addr Arch v1.* I	UNH-IOL/27604			
		support of cryptographically generated addresses	CGA				Self Test		Self Test				
2500-267	6.7	IP Security Requirements											
		support of the IP security architecture	IPsecv3				IPsecv3 v1.* C		IPsecv3 v1.* I				
		support for automated key management	IKEv2				IKEv2_v1.*_C	T	IKEv2_v2.*_I	1			
		support for encapsulating security payloads in IP	ESP				ESPv3 v1.* C		ESP v1.* I				
2500-267	6.11	Application Requirements											
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test				
		support of Socket application program interfaces	SOCK	1			Self Test		Self Test				
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test				
		support of a DNS server application	DNS-Server				Self Test		Self Test				
		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I	UNH-IOL/26468			
2500-267	6.2	Routing Protocol Requirements											
000 201	0.2	support of the intra-domain (interior) routing protocols	IGW				Self Test		OSPFv3 v1.* I				
		support of the inter-domain (interior) routing protocols	EGW				Self Test		BGP v1.* I				
2500-267	6.4	Transition Mechanism Requirements	LOW				oen reat						
000 207	0.1	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test				
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test				
SP500-267	6.8	Network Management Requirements	01 2				000 1000		Self Test				
000-201	0.0	support of network management services	SNMP				Self Test		Self Test				
P500-267	6.9	Multicast Requirements	0.1111				000 1000						
000 201	0.0	support of basic multicast	Mcast				Self Test						
		full support of multicast communications	SSM				Self Test		Self Test				
P500-267	6.10	Mobility Requirements											
		support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO				Self Test		Self Test				
P500-267	6.3	Quality of Service Requirements											
		support of Differentiated Services capabilities	DS				Self Test		Self Test				
P500-267	6.12	Network Protection Device Requirements											
000 201	0.12	support of common NPD regts	NPD				N1 N2 N3 N4 v1.3						
		support of basic firewall capabilities	FW				N1 FW v1.3						
		support of application firewall capabilities	APFW				Self Test						
		support of application mewan capabilities	IDS				N3 IDS v1.3						
		support of intrusion protection capabilities	IPS				N4 IPS v1.3						
P500-267	6.5	Link Specific Technologies	10				114_11 0_11.0						
300-207	0.5	support of robust packet compression services	ROHC				Self Test		Self Test				
		support of link technology [0:1]		P			Self Test	Self Declaration	Self Test	Self Declaration			
		support of milk teelhology [0.1]	cons- Euromot					con Boolaration		Son Doblaration			
		(repeat as needed) support of link technology	l ink=						1				
10									•	•			
12		< Check HERE if this stack's DOC includes a	additional infor	mation	about tes	sted cap	pabilities and options	on an attached page 3 of notes	5.				
	Level of	support for USGv6-v1 Requirements for capability.				Color	Indica	tion of USGv6-v1 Recommended Le	vel of Support for device ty	/pe / stack role.			
Level		SDOC makes no declaration for this capability.			Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.								
Level								Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.					
Р							Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.						
P N	See note												
Р	See note	capability not supported in product.											
P N X	See note USGv6 o	capability not supported in product.	av/usav6/tast ass	oifications	html			Noto #_roforonoo	to a detailed note about this	capability or result on attached			
P N X	See note USGv6 o Specific U				html		Component 5	Note # - reference Ref - Supplier / Product / Stack ID of dis	to a detailed note about this				

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary USGv6-v1 SDOC-v1.10 Page 3											
Field Product Id:				Stack Id:							
13				Context /	Supported Capabilities				Notes about USC	Sv6-v1 Capabilities.	
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interoperability	Test Lab / Result ID, Note
Note #	Reference	Section	USGV6-V1 Profile Requirements	Option	HOST	Router	NPD	Conformance/NPD	Test Lad / Result ID, Note	interoperability	Test Lad / Result ID, Note
1											
Discussion:											
Discussion	1.										
2											
Discussion	n:										
2100000101											
3											
Discussion	n:										
4											
Discussion	n:										
_											
5											
Discussion	n:										
6											
0											
Discussion	n:		ſ			r					
7											
Discussion	n:				1	1					
8											
			•								
Discussion	n:				1	-					
9											
Discussion	n:										
10											
Discussio	. .										
Vendor's General Notes / Discussion about this Product / Stack's capabilities:											

Suppliers Declaration of Conformity for USGv6 Description and Instructions

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field	Description and Instructions	Field	Description and Instructions
1	The Document Requiring Conformity: Identifies the profile version implemented. Not a user completable field.	11	Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.
2	Product Identifier: Supplier's concise name for the product declared.		Product Id/Stack Id : The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.
3	Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.		Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.
4	Product as Tested/Declared : Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).		Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.
5	Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.		The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test Iab, and find contact details.
6	USGv6 Capability Summary : The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).		Cells marked Self Test have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.
7	Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.	12	Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary. Headings and Special Notations: as described.
8	Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.		Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.
9	Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.	13	Stack-1 Notes Instructions : The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.
10	Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.		Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.

Further Description: http://www.antd.nist.gov/usgv6/testing.html, and NIST SP 500-267 USGv6 Testing Program Users Guide available at the website.