Supplie	ers Declara	tion of Confo	rmity for US	SGv6 Prod	lucts	USGv6-v1 SDOC-v1.10 Page 1						
1		nent Requirir					USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)					
2	Product Id	lentifier:				Cis	Cisco Stealthwatch					
3	3 Supplier's Name, Address and SDOC Contact Details											
	Systems, Inc											
	170 West Tasman Dr. San Jose, CA 95134 USA											
San Jo												
4	4 Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.											
	7.0											
5												
					Cisco Steal	hwatch						
6	USGv6 Capability summary. (For each distinct IPv6 stack in the product provide a summary of its USGv6 capabilities below and include a detailed test result											
summary). e.g. example-prod-id/stack-1: USGv6-v1-Host: IPv6-Base+Addr-Arch+IPsec-v3+IKEv2+SLAC+Link=Ethemet. USGv6-v1-Host: IPv6-Base+Addr-Arch+SLAAC+Mcast+Link = Ethernet												
				US	GV0-VI-Host. IF VO-base+Addi-Aic	IITSLAACT	WCaStTLIII	ik - Eulefflet				
7	Self Contained or Composite SDOC? (Must indicate one).											
/ES	All of the decla	red USGv6 capabil	lities of this prod	duct are	Some or all of the USGv6 capabi	lities of this pro	duct are provid	ded by the use and/or integration of umodified components that have their own unique				
	addressed by orginal test results reported in this SDOC.				USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indicate which capabilities							
are provided by specific referenced components (product-id/stack-id).								ack-id).				
8	Additional	Declarations	/ Attachm	ents: (List	supplier & product-id/stack-id for ref	erenced and attached test results in the case of composite products).						
		nt Supplier		(=:=:	Product ID:	Stack ID:		Notes:				
[1]	Componer	it Supplier			Floudet ID.	Stack ID.		Notes.				
[2]												
[3]												
[4]												
9	Supplementary Attestations (Answer all).											
							This product	is fully functional in IPv6 only environments. That is, no claimed capabilities are				
	Yes	invalidated ifthis product is operated in a dual stack (6 and 4) network environment.			Yes		this product is deployed in a network environment that does not support Ipv4.					
	Yes						All of the products listed in the product family in section 5 are implemented such that their USGv6					
		stacks/ports not covered are documented, and how their lpv6 capabilities differ from those reported are explained.					capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6					
		торопод аге ехрганед.										
								re identical and unmodified for all the products cited above.				
10	Cianatura	l In	Annul Cada	on		Doto		40/04/40				
10	Signature	ال	arryll Gads	UII		Date		12/21/18				
	Print Name	/ Title	arryll Gads	on, Lead l	JSGv6 Cisco System Inc.	•	•					
			•	•	•							
ee instru	ctions for fields	1-12 on Page 4.										

P500-267 P500-267 P500-267	6.6	USGv6-v1 Profile Requirements IPv6 Basic Requirements support of IPv6 base (IPv6;ICMPv6;PMTU;ND) support of PMTU Discovery Protocol requirements support of Stateless address auto-configuration support of Creation of Global Addresses support of SLAAC privacy extensions. support of stateful (DHCP) address auto-support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of cryptographically generated addresses IP Security Requirements support of the IP security architecture	Context / Configuration Option IPv6-Base PMTU SLAAC SLAAC - c(M) PrivAddr DHCP-Client DHCP-Prefix SEND Addr-Arch CGA	Host P P P	Stack lorted Capa	bilities	Test Suite Conformance/NPD Basic_v1.*_C Basic_v1.*_C SLAAC.V1.*_C SLAAC.V1.*_C	USGv6 Testing F Test Lab / Result ID, Note #, or Component Ref UNH-IOL/29507 UNH-IOL/29507	Test Suite Interoperability Basic_V1.*_I Basic_V1.*_I	Test Lab / Result ID, Note #, c Component Ref UNH-IOL/29509 UNH-IOL/29509			
P500-267 P500-267 P	6.6	IPv6 Basic Requirements support of IPv6 base (IPv6;ICMPv6;PMTU;ND) support of PMTU Discovery Protocol requirements support of stateless address auto-configuration support of Creation of Global Addresses support of SLAAC privacy extensions. support of stateful (DHCP) address auto-support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	Configuration Option IPv6-Base PMTU SLAAC SLAAC - c(M) PrivAddr DHCP-Client DHCP-Prefix SEND Addr-Arch	Host P P			Basic_v1.*_C Basic_v1.*_C SLAAC-V1.*_C	Test Lab / Result ID, Note #, or Component Ref UNH-IOL/29507 UNH-IOL/29507	Test Suite Interoperability Basic_V1.*_I Basic_V1.*_I	Component Ref UNH-IOL/29509			
P500-267 P500-267 P	6.6	IPv6 Basic Requirements support of IPv6 base (IPv6;ICMPv6;PMTU;ND) support of PMTU Discovery Protocol requirements support of stateless address auto-configuration support of Creation of Global Addresses support of SLAAC privacy extensions. support of stateful (DHCP) address auto-support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	Option IPv6-Base PMTU SLAAC SLAAC - c(M) PrivAddr DHCP-Client DHCP-Prefix SEND Addr-Arch	P P P	Router	NPD	Basic_v1.*_C Basic_v1.*_C SLAAC-V1.*_C	Component Ref UNH-IOL/29507 UNH-IOL/29507	Basic_V1.*_I Basic_V1.*_I	Component Ref UNH-IOL/29509			
P500-267 P500-267 P500-267	6.6	IPv6 Basic Requirements support of IPv6 base (IPv6;ICMPv6;PMTU;ND) support of PMTU Discovery Protocol requirements support of stateless address auto-configuration support of Creation of Global Addresses support of SLAAC privacy extensions. support of stateful (DHCP) address auto-support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	IPv6-Base PMTU SLAAC SLAAC - c(M) PrivAddr DHCP-Client DHCP-Prefix SEND Addr-Arch	P P P	Router	NPD	Basic_v1.*_C Basic_v1.*_C SLAAC-V1.*_C	UNH-IOL/29507 UNH-IOL/29507	Basic_V1.*_I Basic_V1.*_I	UNH-IOL/29509			
P500-267 (6.6	support of IPv6 base (IPv6;ICMPv6;PMTU;ND) support of PMTU Discovery Protocol requirements support of stateless address auto-configuration support of Creation of Global Addresses support of St.AAC privacy extensions. support of stateful (DHCP) address auto- support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	PMTU SLAAC SLAAC - c(M) PrivAddr DHCP-Client DHCP-Prefix SEND Addr-Arch	P P			Basic_v1.*_C SLAAC-V1.*_C	UNH-IOL/29507	Basic_V1.*_I				
P500-267	6.7	support of PMTU Discovery Protocol requirements support of stateless address auto-configuration support of Creation of Global Addresses support of SLAAC privacy extensions. support of stateful (DHCP) address auto-support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	PMTU SLAAC SLAAC - c(M) PrivAddr DHCP-Client DHCP-Prefix SEND Addr-Arch	P P			Basic_v1.*_C SLAAC-V1.*_C	UNH-IOL/29507	Basic_V1.*_I				
P500-267	6.7	support of stateless address auto-configuration support of Creation of Global Addresses support of SLAAC privacy extensions. support of stateful (DHCP) address auto- support of automated router prefix delegation support of neighbor discovery security extensions. Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	SLAAC SLAAC - c(M) PrivAddr DHCP-Client DHCP-Prefix SEND Addr-Arch	Р			SLAAC-V1.*_C						
P500-267	6.7	support of Creation of Global Addresses support of SLAAC privacy extensions. support of stateful (DHCP) address auto- support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	SLAAC - c(M) PrivAddr DHCP-Client DHCP-Prefix SEND Addr-Arch					UNH-IOL/29507	SLAAC-V1.* I	UNH-IOL/29509			
P500-267	6.7	support of SLAAC privacy extensions. support of stateful (DHCP) address auto- support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	PrivAddr DHCP-Client DHCP-Prefix SEND Addr-Arch	1				UNH-IOL/29507	SLAAC-V1. I	UNH-IOL/29509			
P500-267	6.7	support of stateful (DHCP) address auto- support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	DHCP-Client DHCP-Prefix SEND Addr-Arch				Self Test	ON 1-10E/29307	Self Test	GIVI 1-10E/29309			
P500-267	6.7	support of automated router prefix delegation support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	DHCP-Prefix SEND Addr-Arch				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I				
P500-267	6.7	support of neighbor discovery security extensions Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	SEND Addr-Arch				Self Test		Self Test				
P500-267	6.7	Addressing Requirements support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements	Addr-Arch				Self Test		Self Test				
P500-267	6.7	support of addressing architecture reqts support of cryptographically generated addresses IP Security Requirements					00% 1000		00111000				
		support of cryptographically generated addresses IP Security Requirements		Р			Adds Assh v4 * C	UNH-IOL/29506	Adds Asob v4 * I	UNH-IOL/29508			
		IP Security Requirements		Р			Addr_Arch_v1.*_C Self Test	UNH-IUL/29506	Addr_Arch_v1.*_I	UNH-IOL/29508			
			CGA				Sell Test		Self Test				
2500-267 6	6.11		ID				IDaaa24 * C		ID24 * I				
2500-267	6.11	support of the IP security architecture support for automated key management	IPsecv3 IKEv2				IPsecv3_v1.*_C IKEv2_v1.*_C		IPsecv3_v1.*_I IKEv2_v2.*_I	+			
2500-267	6.11		ESP				ESPv3 v1.* C			+			
-500-267	0.17	support for encapsulating security payloads in IP	ESP				ESPV3_V1."_C		ESP_v1.*_I				
		Application Requirements	DNC Client				Colf T4		Colf Tags				
		support of DNS client/resolver functions	DNS-Client	 		-	Self Test		Self Test	-			
		support of Socket application program interfaces	SOCK				Self Test		Self Test				
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test				
		support of a DNS server application support of a DHCP server application	DNS-Server DHCP-Server				Self Test		Self Test				
2500 007			DHCP-Server				Self Test		DHCP_Serv_v1.*_I				
P500-267	6.2	Routing Protocol Requirements	IOW				C = # T = = 4		OCDE::2 ::4 * I				
		support of the intra-domain (interior) routing protocols support for inter-domain (exterior) routing protocols	IGW EGW				Self Test		OSPFv3_v1.*_I				
2500 207	C 4	Transition Mechanism Requirements	EGW				Self Test		BGP_v1.*_I				
P500-267	6.4		IPv4				Call Tast		Call Tast				
		support of interoperation with IPv4-only systems	6PE				Self Test		Self Test				
0500.007		support of tunneling IPv6 over IPv4 MPLS services	OPE				Self Test		Self Test				
P500-267	6.8	Network Management Requirements	ONIMO				0.15.7		Self Test	4			
P500-267 (support of network management services Multicast Requirements	SNMP				Self Test		Self Test				
2500-267	6.9	support of basic multicast	Mcast				Self Test	Self Declaration		Self Declaration			
		full support of multicast communications	SSM				Self Test	Seir Deciaration	Self Test	Seir Deciaration			
P500-267 6	6.10	Mobility Requirements	SSIVI				Sell Test		Sell Test				
300-207	0.10	support of mobile IP capability.	MIP				Self Test		Self Test	+			
		support of mobile network capabilities	NEMO				Self Test		Self Test	+			
P500-267	6.3	Quality of Service Requirements	INLINIO				Sell Test		Sell Test				
-300-207	0.3	support of Differentiated Services capabilities	DS				Self Test		Self Test	+			
P500-267 6	6.12	Network Protection Device Requirements	DO				Sell Test		Sell Test				
2500-267	0.12	,											
		support of common NPD reqts	NPD				N1 N2 N3 N4_v1.3						
		support of basic firewall capabilities	FW				N1_FW_v1.3			+			
		support of application firewall capabilities	APFW				Self Test			+			
		support of intrusion detection capabilities	IDS				N3_IDS_v1.3			+			
		support of intrusion protection capabilities	IPS				N4_IPS_v1.3						
P500-267	6.5	Link Specific Technologies	D0:::2				0 15 =		0 1/ =				
		support of robust packet compression services	ROHC				Self Test	O. K. D d C.	Self Test	Out Death with			
		support of link technology [O:1]	Link=Ethernet	Р			Self Test	Self Declaration	Self Test	Self Declaration			
\longrightarrow		(12.1				1		1	<u> </u>			
		(repeat as needed) support of link technology	Link=							<u> </u>			
12		< Check HERE if this stack's DOC includes a	dditional inforn	nation a	bout tes	sted cap	pabilities and options or	n an attached page 3 of notes.					
							i e						
		f support for USGv6-v1 Requirements for capability.				Color							
Bla	lank - S	SDOC makes no declaration for this capability.					Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.						
		required tests of USGv6-V1 requirements for these cap				Indicates cabability that is	unusal for a given device type / stack	role. Do not select withou	ut careful analysis.				
		es page for details on the level of support of USGv6-v1		this cana	hility		Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.						
		capability not supported in product.	rooquiromento IUI	ино сара	willy.	l	majorios capability trial is	ion optional / oonaliional by the fecon	minodations of the USGV0-V	1 1 TOTAL .			
× 103	.5000	capasing not supported in product.											
.10 :1 6		100.0 Test - "					1	N. 6 "					
		JSGv6 Test suite used for test. See: http://www.antd.ni			ions.html		 			apability or result on attached pa			
st Lab / Result ID - Abbreviation of accredited laboratory and its local identifier for this test result.							Component Ref - Supplier / Product / Stack ID of distinctly tested component that provides this capability.						

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary USGv6-v1 SDOC-v1.10 Page 3											
Field Product Id:											
13				Context /	Supported Capabilities				Notes about USG	Gv6-v1 Capabilities.	
	Spec /			Configuration		4 /		Test Suite	/	Test Suite	
Note #	Reference	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Test Lab / Result ID, Note	Interoperability	Test Lab / Result ID, Note
1	<u>.</u>	<u> </u>				'	'				
Discussion	n:										
2	 										
Discussion	n:										
3											
Discussion	n:				-						
4	 										
Discussion	n:										
5	 										
Discussion	n:										
6	 										
Discussion	n:										
7	 										
Discussion	n:										
8											
Discussion	n:		·							·	
9	<u> </u>										
Discussion	n:		,				_	,		, 	
10	<u> </u>										
Discussion: Vendor's General Notes / Discussion about this Product / Stack's capabilities:											
Vendor's General Notes / Discussion about this Product / Stack's capabilities:											

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field	Description and Instructions	Field	Description and Instructions
1	The Document Requiring Conformity : Identifies the profile version implemented. Not a user completable field.	11	Summary of Results : The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.
2	Product Identifier: Supplier's concise name for the product declared.		Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.
3	Suppliers Name, Address and Contact Details : Company name and point of contact for SDOC questions, street address, phone and email.		Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.
4	Product as Tested/Declared : Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).		Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.
5	Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.		The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.
6	USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).		Cells marked Self Test have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.
7	Self Contained or Composite SDOC : If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.	12	Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary. Headings and Special Notations: as described.
8	Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.		Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.
9	Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.	13	Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.
10	Signature Block : Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.		Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.