Suppli	ers Declar	ation of Co	nformity for USGv6 F	Products	USGv6-v1 SDOC-v1.10 Page 1							
1	The Document Requiring Conformity:					USGv6 Profile Version 1.0, July 2008. (NIST SP500-267						
2	Product le	dentifier:				Avamar						
3 Dell EN	3 Supplier's Name, Address and SDOC Contact Details ell EMC											
	outh St. ton MA. 01											
	mail: Roger.Zee@dell.com											
4	Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.											
	7.5.1											
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.											
	Gen4T M600, M1200, M2400, Utility, Accelerator, S2400											
6	USGv6 Capability summary. (For each distinct IPv6 stack in the product provide a summary of its USGv6 capabilities below and include a detailed test result summary). e.g. example-prod-id/stack-1: USGv6-v1-Host: IPv6-Base+Addr-Arch+IPsec-v3+IKEv2+SLAC+Link=Ethemet.											
7 YES	USGv6-v1-Host: IPv6-Base+Addr-Arch+SLAAC+Link = Ethernet Self Contained or Composite SDOC? (Must indicate one). All of the declared USGv6 capabilities of this product are provided by the use and/or integration of umodified components that have are addressed by original test results reported in this SDOC. Some or all of the USGv6 capabilities of this product are provided by the use and/or integration of umodified components that have their own unique USGv6 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indicate which capabilities are provided by specific referenced components (product-id/stack-id).											
8	Additiona	l Declaration	ons / Attachments: (L	 list supplier & product-id/stack-id fo	for referenced and attached test results in the case of composite products).							
	Compone	nt Supplie		Product ID:	Stack ID:	ĮN	otes:					
[1]												
[2]					-							
[4]		-	<u> </u>		 							
9	Supplementary Attestations (Answer all).											
	YES			ck environments.That is, no claimed is operated in a dual stack (6 and 4)network	YES	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support Ipv4.						
	YES This SDOC contains a capabilities test report for each unique IPv6 stack in the product. If not, the stacks/ports not covered are documented, and how their Ipv6 capabilities differ from those reported are explained.					All of the products listed in the product family in section 5 are implemented such that USGv6 capabilities are identical in form and function across the entire product family specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attest that these tested USGv6 capabilities are identical and unmodified for all the products above.						
10	Signature Print Name	1694 41/				1/16/2019						
See insta	uctions for field			E / SOFTWARE PRINC	TYPL EN	AINEE						

Spec / Reference SP500-267	d:	Avamar			Stack I	d:			7.5.1				
Reference SP500-267		J							7.5.1				
Reference SP500-267	-		Context /	Suppor	rted Cape	abilities			ng Program Results				
SP500-267	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note #, or Component Ref	Test Suite Interoperability	Test Lab / Result ID, Note #, or Component Ref			
SP500-267		IPv6 Basic Requirements	22 SONIO 1-1										
SP500-267		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	P			Basic_v1.*_C	UNH-IOL/28729	Basic_V1.*_I	UNH-IOL/28731			
SP500-267		support of PMTU Discovery Protocol requirements	PMTU	P.			Basic_v1.*_C	UNH-IOL/28729	Basic_V1.*_1	UNH-IOL/28731			
SP500-267		support of stateless address auto-configuration	SLAAC	Р			SLAAC-V1.*_C	UNH-IOL/28729	SLAAC-V1.*_I	UNH-IOL/28731			
SP500-267		support of Creation of Global Addresses		P			SLAAC-V1.*_C	UNH-IOL/28729	SLAAC-V1.*_I	UNH-IOL/28731			
SP500-267		support of SLAAC privacy extensions.	PrivAddr				Sell Test		Self Test	<u> </u>			
SP500-267		support of stateful (DHCP) address auto-	DHCP-Client				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I				
SP500-267		support of automated router prefix delegation	DHCP-Prelix				Self Test		Self Test				
SP500-267		support of neighbor discovery security extensions	SEND				Self Test -		Self Test				
	6.6	Addressing Requirements		1	-								
		support of addressing architecture reqts	Addr-Arch	P			Addr_Arch_v1.*_C	UNH-IOL/28730	Addr_Arch_v1.*_l	UNH-IOL/28732			
		support of cryptographically generated addresses	CGA				Self Test		Self Test				
SP500-267	6.7	IP Security Requirements											
		support of the IP security architecture	IPsecv3		CONTROL OF		IPsecv3_v1.*_C		IPsecv3_v1.*_I				
		support for automated key management	IKEv2	100			IKEv2_v1.*_C		IKEv2_v2.*_I				
		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I				
SP500-267	6.11	Application Requirements		0.000	Section 2.								
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test				
		support of Socket application program interfaces	SOCK		0		Self Test		Self Test				
		support of IPv6 uniform resource identifiers	UAI				Self Test		Self Test				
		support of a DNS server application	DNS-Server				Self Test		Self Test				
		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I				
SP500-267	6.2	Routing Protocol Requirements	No. of the last of	0		5 7 12		United the second state of the second					
		support of the intra-domain (interior) routing	IGW				Self Test		OSPFv3_v1.*_I				
		support for inter-domain (exterior) routing protocols	EGW	S			Self Test		BGP_v1.*_I				
SP500-267	6.4	Transition Mechanism Requirements		-3	7-2								
		support of interoperation with IPv4-only systems	iPv4				Self Test		Self Test				
-		support of tunneling IPv6 over IPv4 MPLS services	6PE	1) 4-010-0			Self Test		Self Test	1			
SP500-267	6.8	Network Management Requirements		2		1000000			Self Test				
		support of network management services	SNMP				Self Test		Self Test				
SP500-267	5.9	Multicast Requirements			0.00								
		support of basic multicast	Mcast		Description of the last		Self Test						
		full support of multicast communications	SSM				Self Test		Self Test				
SP500-267	6.10	Mobility Requirements			6	100	Chicago Company	National Control of the Control of t					
		support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO	1			Self Test		Self Test	1			
SP500-267	6.3	Quality of Service Requirements								Sign Styles			
		support of Differentiated Services capabilities	DS				Self Test		Self Test	ļ			
SP500-267	6.12	Network Protection Device Requirements			9 1 2	200							
		support of common NPD regts	NPD				N1 N2 N3 N4_v1.3						
		support of basic firewall capabilities	FW	- 638			N1_FW_v1.3						
		support of application firewall capabilities	APFW	(a	10		Self Test						
	1	support of intrusion detection capabilities	IDS	2	B		N3_ID\$_v1.3						
		support of intrusion protection capabilities	IPS		1		N4_IPS_v1.3						
SP500-267	6.5	Link Specific Technologies											
		support of robust packet compression services	ROHC				Self Test		Self Test	10.40			
		support of link technology [O:1]	Link=Ethemet	P	E CONTRACTOR OF		Self Test	Self Declaration	Self Test	Self Declaration			
				15 3						<u> </u>			
		(repeat as needed) support of link technology											
12		< Check HERE if this stack's DOC include	es additional i	nforma	tion abo	out test	ed capabilities and options on an attached page 3 of notes.						
V =													
Level	Level o	f support for USGv6-v1 Requirements for capabili	ty.			Color	Indication of USGv6-v1 Recommended Level of Support for device type / stack role.						
	Blank -	SDOC makes no declaration for this capability.			Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.								
Р							Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.						
N	See notes page for details on the level of support of USGv6-v1 reequirements for this capability. Indicates capability that is							left optional / ocnditional by the reco					
	X USGv6 capability not supported in product.												
^	JUGGVO	capazing not supported in product.											
Total Cultur	Con -it	HCO.C Test suits upper for test. Cons http://www.anti-	niet nochannen	et-enositi	cations hi	mi		Note # - reference to a c	letailed note about this o	anability or result on attached page			
Took Lab / C	est Suite - Specific USGv6 Test suite used for test. See: http://www.antd.nist.gov/usgv6/test-specifications.html est Lab / Result ID - Abbreviation of accredited laboratory and its local identifier for this test result.							Note # - reference to a detailed note about this capability or result on attached page. Component Ref - Supplier / Product / Stack ID of distinctly tested component that provides this capability.					
1881 LBD / H	(LBD / nesult ib - Abdreviation of accredited laboratory and its local identificer for this test result.							everiportent (18) - Outpute / / Toutou / Output is of additional toutou composition that provides this capability.					

.....

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary									USGv6-v1 SDOC-v1.10 Page 3			
	Product ld:											
13	The same of			Context /	Supported Capabilities				Notes about USG	iv6-v1 Capabilities.	v1 Capabilities.	
	Spec /			Configuration	Because			Test Suite		Test Suite		
Note #	Reference	Section	USGv6-v1 Profile Requirements	Option	Host	Houter	NPD	Conformance/NPD	Test Lab / Result ID, Note	Interoperability	Test Lab / Result ID, Note	
1												
•												
Discussio	Π:		<u>. </u>		,							
_												
2							<u> </u>			1		
Discussion:												
_												
3							<u> </u>					
Discussion:												
Discussio						Ī		ľ				
4			<u> </u>		<u> </u>		<u> </u>					
		1										
Discussio	η:				1	Т		ì				
5												
			-					·				
Discussio	n:				1	_		т		T	1	
6												
Ť				_ '						•		
Discussio	n:											
7						1						
							<u> </u>	l .		<u> </u>	<u> </u>	
Discussio	n:											
						1						
- 8					<u>l</u>	<u> </u>	l					
Discussio	n:											
9			<u> </u>			<u> </u>	<u> </u>	<u> </u>				
Discussio	n:											
						<u> </u>						
10						<u> </u>						
Discussio	o.											
Vendor's	General Notes	/ Discussio	on about this Product / Stack's capabilities:									
					3.0		7.5					
											ı	