Suppli	ers Declaration of Confor	mity for USGv6	Products				USGv6-v1 S	DOC-v1.10 Page			
1	The Document Requiring	Conformity:				USGv6 Profile V	ersion 1.0, July 2008.	(NIST SP500-267			
2	Product Identifier:										
3	Supplier's Name, Addres	s and SDOC Co	ntact Details								
	chnologies				15 -10						
	ll Way										
	Rock, TX 78682										
ontac											
eorge	Dilger george.dilger@dell.	com Pablo Arias	pablo_arias@dell.com								
4	Bradust so Tostad/Dooley	end. Product Ider	ntifier, version/revision inform	matian dataila a	fassfisses	tion to start					
4	Product as resteu/Decial	ed. Froduct ider		3.30.30.30	i configura	tion testea.					
5	Product Family (other pro	ducts using same	Pv6 stack(s) to which thes	se results are de	eclared to a	apply). Check Produ	ct Family attestation	below.			
			PowerE	dge 14G iDRAC	09	74.	The latest				
6	USGv6 Capability summa	ry. (For each dis	stinct IPv6 stack in the produ	uct provide a su	mmary of it	ts USGv6 capabilities	s below and include a	detailed test result			
	summary). e.g. example-p	rod-id/stack-1: U	SGv6-v1-Host: IPv6-Base+A	Addr-Arch+IPse	c-v3+IKEv2	2+SLAC+Link=Etheri	net				
7	Self Contained or Compo	site SDOC? (Mu	st indicate one).								
S	All of the declared USGv6 capabi	lities of this product	Some or all of the U	SGv6 capabilities of	f this product	are provided by the use a	nd/or integration of umodified	components that have			
	are addressed by orginal test resu	ılts reported in this	their own unique US	GV6 SDOCs. All of	the relevant i	referenced SDOCs are ide	entified in section 8 and attack	hed. This product's			
	SDOC.		page 2 will indicate v	which capabilities ar	e provided by	specific referenced comp	onents (product-id/stack-id).				
8	Additional Declarations / Attachments: (List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).										
	Component Supplier		Product ID:	Stack II		Notes:					
1]											
2]						and the second second		12 17 17 17			
3]	22,000					1000		- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1			
4]								Trans.			
9	Supplementary Attestation	ns (Answer all).									
	Yes This product is fully	functional in dual stat	ck environments.That is, no claimed	d Yes	This produ	ıct is fully functional in IPv	6 only environments. That is,	no claimed			
	capabilities are inva		s operated in a dual stack (6 and		capabilitie	s are invalidated if this pro	duct is deployed in a networ	k environment that			
	4) network environm					support Ipv4.					
			port for each unique IPv6 stack in t ed are documented, and how their i		All of the p	products listed in the produ	oct family in section 5 are imp	elemented such that			
		m those reported are		ipvo	family. The	vo capabilities are identica e specific conformance an	I in form and function across d interoperability test results	the entire product			
			1		capabilities	s of an identified member	of this product family are pro-	vided in this SDOC.			
		11	1/1		The SDOC	C attests that these tested ducts cited above.	USGv6 capabilitiesare identi	ical and unmodified for			
10	Signature /	/		Date	all trie proc	Jugs cheu apove.					
		(mm) mo		P	15/1					
	Print Name / Title	THAMAG	GARVENS	MICE	DAKE	INFAIT 5	NGINBERIN	16			
	uctions for fields 1-12 on Page 4.	11011111	9171211011	e visit 1	1-100	10001 12	V WIN WESTERIN				
ısır											

ALCOHOLD BASE		iers Declaration of Conformity for USGv6	Froducts: De	clared	State of the last		u rest Results Sumi	nary T		Gv6-v1 SDOC-v1.10 Pa		
duct l	ld:	PowerEdge iDRAC			Stack I				3.30.30.30			
			Context /	Suppo	rted Capa	abilities		USGv6 Testing P	rogram Results			
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note		
	Section		Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperability	Component Ref		
500-267	6.1	IPv6 Basic Requirements										
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	Р	Shape 118		Basic_v1.*_C	UNH-IOL/29444	Basic_V1.*_I	UNH-IOL/29447		
		support of PMTU Discovery Protocol requirements	PMTU	Р			Basic_v1.*_C	UNH-IOL/29444	Basic_V1.*_I	UNH-IOL/29447		
		support of stateless address auto-configuration	SLAAC	P			SLAAC-V1.*_C	UNH-IOL/29444	SLAAC-V1.*_I	UNH-IOL/29447		
	-	support of Creation of Global Addresses	SLAAC - c(M)	Р			SLAAC-V1.*_C	UNH-IOL/29444	SLAAC-V1.*_I	UNH-IOL/29447		
	-	support of SLAAC privacy extensions.	PrivAddr	P			Self Test	1511101101100110	Self Test			
	-	support of stateful (DHCP) address auto- support of automated router prefix delegation	DHCP-Client DHCP-Prefix	P				UNH-IOL/29446		UNH-IOL/29449		
	-	support of automated router prefix delegation support of neighbor discovery security extensions	SEND				Self Test		Self Test			
500-267	6.6	Addressing Requirements	SEND		Intersection		Self Test		Self Test			
000-207	0.0		Addr Arab	Р			Adda Anab u4 t C	LINIU IOI IOO 445				
	-	support of addressing architecture reqts support of cryptographically generated addresses	Addr-Arch CGA	atte Post			Addr_Arch_v1.*_C	UNH-IOL/29445	Addr_Arch_v1.*_I	UNH-IOL/29448		
500-267	6.7	IP Security Requirements	CGA	CHARLES AND SEAL		STATISTICS.	Self Test		Self Test			
300-207	0.7	support of the IP security architecture	IPsecv3				IPsecv3 v1.* C		'D 0 1 1 1			
	_	support of the IP security architecture support for automated key management	IKEv2				IKEv2_v1.*_C		IPsecv3_v1.*_I			
	+	support for automated key management support for encapsulating security payloads in IP	ESP	X Hebri			ESPv3_v1.*_C		IKEv2_v2.*_I			
500-267	6.11	Application Requirements	LUI	PSYCHOLOGIC	San Carrier		LOTVO_VIC		ESP_v1.*_I			
300-207	0.11	support of DNS client/resolver functions	DNS-Client			an supplied to	Self Test		Self Test			
	+	support of Socket application program interfaces	SOCK				Self Test		Self Test			
-		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test			
		support of a DNS server application	DNS-Server				Self Test		Self Test	-		
		support of a DHCP server application	DHCP-Server				Self Test		DHCP Serv v1.* I			
500-267	6.2	Routing Protocol Requirements	SEED SEARCH SEARCH	SHEET SHEET			2011 108t		DHCF_Selv_VII			
000 201	0.2	support of the intra-domain (interior) routing	IGW		allianimino (cine) del	MANUFACTURE.	Self Test		OSPFv3 v1.* I			
		support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP v1.* I			
500-267	6.4	Transition Mechanism Requirements		AUGUNEA			Haraca and Albanda		DOF_VII			
		support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test			
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test			
500-267	6.8	Network Management Requirements							Self Test			
		support of network management services	SNMP		247		Self Test		Self Test			
500-267	6.9	Multicast Requirements				1000			CON TOOL	National Action Control of the Contr		
		support of basic multicast	Mcast		A PARTY OF THE PAR		Self Test					
		full support of multicast communications	SSM				Self Test		Self Test			
500-267	6.10	Mobility Requirements										
		support of mobile IP capability.	MIP				Self Test		Self Test			
		support of mobile network capabilities	NEMO	+ + 1			Self Test		Self Test			
500-267	6.3	Quality of Service Requirements										
		support of Differentiated Services capabilities	DS				Self Test		Self Test			
500-267	6.12	Network Protection Device Requirements										
		support of common NPD regts	NPD				N1 N2 N3 N4_v1.3					
		support of basic firewall capabilities	FW				N1_FW_v1.3					
		support of application firewall capabilities	APFW				Self Test					
		support of intrusion detection capabilities	IDS				N3_IDS_v1.3					
		support of intrusion protection capabilities	IPS				N4_IPS_v1.3					
00-267	6.5	Link Specific Technologies	POLIC									
		support of robust packet compression services	ROHC	_			Self Test		Self Test			
		support of link technology [O:1] [I	_ink=Ethernet	Р			Self Test	Self Declaration	Self Test	Self Declaration		
		(to to a									
		(repeat as needed) support of link technology										
12		< Check HERE if this stack's DOC include	es additional in	nforma	tion abo	ut test	ed capabilities and o	ptions on an attached page 3	of notes.			
evel	Level of	support for USGv6-v1 Requirements for capabili	T	Color	Indication of USGv6-v1 Recommended Level of Support for device type / stack role.							
		SDOC makes no declaration for this capability.			Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.							
		required tests of USGv6-V1 requirements for these ca	apabilities.			100,000	Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.					
		ee notes page for details on the level of support of USGv6-v1 reequirements for this capability.					Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.					
		capability not supported in product.	ooquiioilioilio	JI 4113 V6	.pabinty.		marcates capability triat is	ion optional / ochultional by the recor	inneuations of the USGV	o-v i Prollie.		
Suite -	Specific USGv6 Test suite used for test. See: http://www.antd.nist.gov/usgv6/test-specifications.html						Note # - reference to a detailed note about this capability or result on attached					
		- Abbreviation of accredited laboratory and its local in					Component Ref -	Supplier / Product / Stack ID of distin	actly tested component th	at provides this capability		

			formity for USGv6 Products: Notes Page	e and Detailed	Test Re	esults S	ummar	y		USGv6	-v1 SDOC-v1.10 Page 3	
	Product Id:					Stack	ld:					
13	Spec /			Context /	Supported Capabilities				Notes about USGv6-v1 Capabilities.			
Note #	Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interoperability	Test Lab / Result ID, Note	
1									reet ass intoducing, note	meroperusinty	rest Lab / Nesult ID, Note	
Discussio	n:							-				
2										_		
Discussio	n:				<u></u>							
3												
Discussio	n:										2	
4												
Discussio	n:											
5			E F							8		
Discussio	n:											
6		LI T										
Discussion	1:											
7												
Discussion	1:							11,,, 1				
8												
Discussion	1:		-1				*					
9												
Discussion	1:											
10												
Discussion	:									•		
Vendor's G	ieneral Notes	/ Discussion	on about this Product / Stack's capabilities:	1								
											4	
											1 11- =	

Gen laims support of USGv6 capabilities. General product and supplier identification is given on Page 1.0 network protection are given on Page 2. Detailed instructions for completing and interpreting each num .gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field	Description and Instructions
1	The Document Requiring Conformity: Identifies the profile version implemented. Not a user completable field.
2	Product Identifier: Supplier's concise name for the product declared.
3	Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
4	Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually teste (e.g., hardware configuration, operating system, etc).
5	Product Family : A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
	recognized product families.
6	USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A.

- nary For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Field **Description and Instructions**

11 Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked Self Test have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric ld of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.

Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.

Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.