uppii	ore Dealers	tion of Confe	armity for HECKE	Products				HEAVE US SDOC US SO Dame S
1			ormity for USGv6 P	roducts				USGv6-v1 SDOC-v1.10 Page 1 USGv6 Profile Version 1.0, July 2008. (NIST SP500-267
2	Product Identifier: OptiPlex							·
3	Supplier's	s Name, Addr	ess and SDOC Con	ntact Details			<u> </u>	
ell		•						
	Samok,							
	ell Way Rock, TX 7	8682						
	34-D136	0002						
	+1 512-65							
		ok@Federal.D		('f' ' '	(	1-1-7	· C'	and all
4	Product a	is Tested/Dec	lared: Product Ident	tifier, version/	revision information, d	etalis of col	ntiguration te	ested.
					Window	vs 10		
5	Product F	amily (other p	roducts using same	IPv6 stack(s)	) to which these result:	s are declar	ed to apply)	. Check Product Family attestation below.
					OptiPlex All-In-			
ptiPle	ex 3050 All-	In-One, OptiPl	lex 5260 All-In-One,	OptiPlex 527	0 All-In-One, OptiPlex All-In-0		-One, OptiP	lex 7470 All-In-One, OptiPlex 7760 All-In-One, OptiPlex 7770
		OptiF	Plex XE2 Mini- Towe	r, OptiPlex XE	<b>OptiPlex Rug</b> E2 Slim Form Factor, 0			er, OptiPlex XE3 Slim Form Factor
					OptiPlex Tov	vor Carias		
ptiPl	ex 3060 Mic	ro Form Facto	or, OptiPlex 3060 Mir	ni Tower, Opti	•		tiPlex 3070	Micro Form Factor, OptiPlex 3070 Mini Tower, OptiPlex 3070
								Form Factor, OptiPlex 5070 Mini Tower, OptiPlex 5070 Slim
orm	Factor, Opt	iPlex 7060 Mic	cro Form Factor, Opt	iPlex 7060 Mi			,	OptiPlex 7070 Micro Form Factor, OptiPlex 7070 Mini Tower,
					OptiPlex 7070 Sm	ali Form Fa	Ctor	
					Dell Precision Fixe	d Form Fa	ctors	
Dell	Precision 3	3420 Tower, Do	ell Precision 3430 Sr	Tauna Ta	otor Dell Presision 24			
				maii Form Fac	Clor, Dell Precision 34	31 Small Fo	rm Factor, [	Dell Precision 3620 Tower, Dell Precision 3630 Tower, Dell
								Dell Precision 3620 Tower, Dell Precision 3630 Tower, Dell Dell Precision 7920 Tower
6			Precision 3930 Ra	ack, Dell Preci	ision 5820 Tower, Dell	Precision 7	7820 Tower,	Dell Precision 7920 Tower  GGv6 capabilities below and include a detailed test result
6			Precision 3930 Ra	ack, Dell Preci	ision 5820 Tower, Dell	Precision 7	7820 Tower,	Dell Precision 7920 Tower  GGv6 capabilities below and include a detailed test result
6			Precision 3930 Ra	ack, Dell Preci	ision 5820 Tower, Dell	Precision 7	7820 Tower,	Dell Precision 7920 Tower  GGv6 capabilities below and include a detailed test result
6			Precision 3930 Ramary. (For each dis	ack, Dell Preci stinct IPv6 sta SGv6-v1-Hos	ision 5820 Tower, Dell	Precision 7 ide a summ ch+IPsec-v	7820 Tower, ary of its US 3+IKEv2+Si	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.
6			Precision 3930 Ramary. (For each dis	ack, Dell Preci stinct IPv6 sta SGv6-v1-Hos	ision 5820 Tower, Dell ack in the product prov tt: IPv6-Base+Addr-An	Precision 7 ide a summ ch+IPsec-v	7820 Tower, ary of its US 3+IKEv2+Si	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.
6	summary).	e.g. example	Precision 3930 Ra  mary. (For each dis a-prod-id/stack-1: US  U  posite SDOC? (Mu	stinct IPv6 states SGv6-v1-Hos  JSGv6-v1-Hos  ust indicate on	ision 5820 Tower, Dellack in the product proving the IPv6-Base+Addr-Annost: IPv6-Base+Addr-IPv6-Base+IPv6-Base+IPv6-IPv6-Base+IPv6-IPv6-IPv6-IPv6-IPv6-IPv6-IPv6-IPv6-	Precision 7 ide a summ ch+IPsec-v. +Arch+SLA	7820 Tower, ary of its US 3+IKEv2+Si AC+Link =	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet
7	Self Conta	ained or Com	Precision 3930 Ra  mary. (For each dis a-prod-id/stack-1: US  uposite SDOC? (Mu abilities of this product	stinct IPv6 states SGv6-v1-Hos  USGv6-v1-Hos  ust indicate on	ision 5820 Tower, Dellack in the product provid: IPv6-Base+Addr-Anast: IPv6-Base+Addr-An	Precision 7 ide a summ ch+IPsec-v. +Arch+SLA pabilities of this	ary of its US 3+IKEv2+Si AC+Link =	Dell Precision 7920 Tower  GGv6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet  rovided by the use and/or integration of umodified components that have their
7	Self Conta	ained or Com	Precision 3930 Ra  mary. (For each dis a-prod-id/stack-1: US  U  posite SDOC? (Mu	stinct IPv6 states SGv6-v1-Hos  JSGv6-v1-Hos  st indicate on	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Article).  Some or all of the USGv6 callow unique USGv6 SDOCs.	Precision 7 ide a summ ch+IPsec-v.  +Arch+SLA  pabilities of this All of the relev	ary of its US 3+IKEv2+Si AC+Link =	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet
7 :S	Self Cont.  All of the decare addresse SDOC.	ained or Com	Precision 3930 Ra  mary. (For each dis prod-id/stack-1: US  U  posite SDOC? (Mu  abilities of this product  esults reported in this	stinct IPv6 states SGv6-v1-Hos  JSGv6-v1-Hos  ist indicate on	ision 5820 Tower, Dellack in the product proving the IPv6-Base+Addr-Andrews: I	ide a summ ch+lPsec-v.  Arch+SLA  cabilities of this All of the releve	ary of its US 3+IKEv2+Si AC+Link = s product are p vant reference specific referen	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).
7 ES	Self Cont.  All of the decare addresse SDOC.	ained or Com	Precision 3930 Ra  mary. (For each dis prod-id/stack-1: US  U  posite SDOC? (Mu  abilities of this product  esults reported in this	stinct IPv6 states SGv6-v1-Hos  JSGv6-v1-Hos  ist indicate on	ision 5820 Tower, Dellack in the product proving the IPv6-Base+Addr-Andrews: I	ide a summ ch+lPsec-v.  Arch+SLA  cabilities of this All of the releve	ary of its US 3+IKEv2+Si AC+Link = s product are p vant reference specific referen	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result LAC+Link=Ethernet.  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will
7 ES	Self Conta All of the dec are addresse SDOC.  Additiona	ained or Com	Precision 3930 Ra  mary. (For each dis prod-id/stack-1: US  U  posite SDOC? (Mu  abilities of this product  esults reported in this	stinct IPv6 states SGv6-v1-Hos  JSGv6-v1-Hos  ist indicate on	ack in the product proving the IPv6-Base+Addr-Andrews:	ide a summ ch+lPsec-v.  Arch+SLA  cabilities of this All of the releve	ary of its US 3+IKEv2+Si AC+Link = s product are p vant reference specific referen	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).
7 S 8	Self Conta All of the dec are addresse SDOC.  Additiona	ained or Com	mary. (For each disa-prod-id/stack-1: US  Upposite SDOC? (Muabilities of this product esults reported in this	stinct IPv6 states GGv6-v1-Hos  SGv6-v1-Hos  st indicate on  ist supplier &	ack in the product proving the IPv6-Base+Addr-Andrews:	Precision 7 ide a summ ch+IPsec-v. +Arch+SLA  pabilities of this All of the releve	ary of its US 3+IKEv2+Si AC+Link = s product are p vant reference specific referen	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result LAC+Link=Ethernet.  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).
7 ES 8	Self Conta All of the dec are addresse SDOC.  Additiona	ained or Com	mary. (For each disa-prod-id/stack-1: US  Upposite SDOC? (Muabilities of this product esults reported in this	stinct IPv6 states GGv6-v1-Hos  SGv6-v1-Hos  st indicate on  ist supplier &	ack in the product proving the IPv6-Base+Addr-Andrews:	Precision 7 ide a summ ch+IPsec-v. +Arch+SLA  pabilities of this All of the releve	ary of its US 3+IKEv2+Si AC+Link = s product are p vant reference specific referen	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result LAC+Link=Ethernet.  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).
7 ES 8 [1] [2] [3]	Self Conta All of the dec are addresse SDOC.  Additiona	ained or Com	mary. (For each disa-prod-id/stack-1: US  Upposite SDOC? (Muabilities of this product esults reported in this	stinct IPv6 states GGv6-v1-Hos  SGv6-v1-Hos  st indicate on  ist supplier &	ack in the product proving the IPv6-Base+Addr-Andrews:	Precision 7 ide a summ ch+IPsec-v. +Arch+SLA  pabilities of this All of the releve	ary of its US 3+IKEv2+Si AC+Link = s product are p vant reference specific referen	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result LAC+Link=Ethernet.  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).
7 ESS 8 [1] [2] [3] [4]	Self Cont. All of the decare addresse SDOC. Additiona Compone	ained or Com lared USGv6 cape d by orginal test re	Precision 3930 Ra  mary. (For each dis a-prod-id/stack-1: US  U  pposite SDOC? (Mu  abilities of this product esults reported in this	stinct IPv6 states GGv6-v1-Hos  SGv6-v1-Hos  st indicate on  ist supplier &	ack in the product proving the IPv6-Base+Addr-Andrews:	Precision 7 ide a summ ch+IPsec-v. +Arch+SLA  pabilities of this All of the releve	ary of its US 3+IKEv2+Si AC+Link = s product are p vant reference specific referen	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result LAC+Link=Ethernet.  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).
7 ES 8 [1] [2] [3]	Self Cont. All of the decare addresse SDOC. Additiona Compone	ained or Com lared USGv6 cape d by orginal test re in Declarations ent Supplier	Precision 3930 Ra  mary. (For each dis  p-prod-id/stack-1: US  U  pposite SDOC? (Mu  abilities of this product  esults reported in this  s / Attachments: (L	stinct IPv6 states GGv6-v1-Hos  JSGv6-v1-Hos  ist indicate on  ist supplier &  Product ID:	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Andrews: IPv6-	Precision 7 ide a summ ch+IPsec-v. +Arch+SLA  pabilities of this All of the releve	ary of its US 3+IKEv2+Si AC+Link = s product are p yant referenced specific referen	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).  ed test results in the case of composite products).  Notes:
7 ES 8 [1] [2] [3] [4]	Self Cont. All of the decare addresse SDOC. Additiona Compone	ained or Com lared USGv6 cape of by orginal test re il Declarations ent Supplier entary Attesta  This product is fit	mary. (For each disp-prod-id/stack-1: US  posite SDOC? (Mu abilities of this product escuts reported in this  s / Attachments: (L  attions (Answer all).	stinct IPv6 states SGv6-v1-Hos  JSGv6-v1-Hos  st indicate on  ist supplier &  Product ID:	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Andrews: IPv6-	Precision 7 ide a summ ch+IPsec-v. +Arch+SLA  pabilities of this All of the releve	ary of its US 3+IKEv2+Si AC+Link = s product are p ant reference appearing reference and attach This product	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result LAC+Link=Ethernet.  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).
7 ES 8 [1] [2] [3] [4]	Self Cont. All of the decare addresse SDOC. Additiona Compone	ained or Com lared USGv6 cape d by orginal test re la Declarations ent Supplier  antary Attesta This product is fu environment. This SDOC conte	Precision 3930 Ra  mary. (For each dis  p-prod-id/stack-1: US  U  pposite SDOC? (Mu  abilities of this product  esults reported in this  s / Attachments: (L  attions (Answer all).  ally functional in dual stack  nvalidated ifthis product is  ains a capabilities test rep	stinct IPv6 states GGv6-v1-Hos  JSGv6-v1-Hos  Ist indicate on ir  ist supplier & Product ID:	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Andrew IPv6-Base+Addr-An	Precision 7 ide a summ ch+IPsec-v.  Arch+SLA  pabilities of this All of the releve provided by s r referenced  Stack ID:	ary of its US 3+IKEv2+Si AC+Link = s product are p yant referenced specific referen d and attach This product are invalidate lpv4. All of the prod	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet  Ethernet  Trovided by the use and/or integration of umodified components that have their SDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).  The product is product in the case of composite products).  Notes:  Stully functional in IPv6 only environments. That is, no claimed capabilities if this product is deployed in an envork environment that does not support ducts listed in the product family in section 5 are implemented such that their
7 ES 8 [1] [2] [3]	Self Cont. All of the decare addresse SDOC. Additiona Compone	ained or Com lared USGv6 cape of by orginal test re il Declarations ent Supplier  This product is fic capabilities are in environment.  This SDOC conta	mary. (For each disp-prod-id/stack-1: US  posite SDOC? (Mu abilities of this product soults reported in this  s / Attachments: (L  attions (Answer all).  ally functional in dual stach invalidated ifthis product is  ains a capabilities test repe e stacks/ports not covered.	stinct IPv6 states SGv6-v1-Hos  SGv6-v1-Hos  Ist indicate on  ist supplier &  Product ID:  k environments. To soperated in a due operated	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Andrew IPv6-Base+Addr-An	Precision 7 ide a summ ch+IPsec-v.  Arch+SLA  pabilities of this All of the releve provided by s r referenced  Stack ID:	ary of its US 3+IKEv2+Si 3+IKEv2+Si AC+Link = s product are product are product are product are product are invalidate lpv4.  All of the product are invalidate lpv4.  All of the product are invalidate lpv4.	Dell Precision 7920 Tower  SGV6 capabilities below and include a detailed test result LAC+Link=Ethernet.  Ethernet  Tovided by the use and/or integration of umodified components that have their SDOCs are identified in section 8 and attached. This product's page 2 will ceed components (product-id/stack-id).  The case of composite products).  Notes:  Is fully functional in IPv6 only environments. That is, no claimed capabilities of if this product is deployed in a network environment that does not support that is listed in the product family in section 5 are implemented such that their bilities are identical in form and function across the entire product family. The
7 ES 8 [1] [2] [3] [4]	Self Cont. All of the decare addresse SDOC. Additiona Compone	ained or Com lared USGv6 cape of by orginal test re il Declarations ent Supplier  This product is fic capabilities are in environment.  This SDOC conta	Precision 3930 Ra  mary. (For each dis  p-prod-id/stack-1: US  U  pposite SDOC? (Mu  abilities of this product  esults reported in this  s / Attachments: (L  attions (Answer all).  ally functional in dual stack  nvalidated ifthis product is  ains a capabilities test rep	stinct IPv6 states SGv6-v1-Hos  SGv6-v1-Hos  Ist indicate on  ist supplier &  Product ID:  k environments. To soperated in a due operated	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Andrew IPv6-Base+Addr-An	Precision 7 ide a summ ch+IPsec-v.  Arch+SLA  pabilities of this All of the releve provided by s r referenced  Stack ID:	ary of its US 3+IKEv2+Si AC+Link = s product are p yant referenced specific referen d and attach  This product are invalidate lpv4.  All of the product specific capals specific of identified mei	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet  Ethernet  Ethernet  Frovided by the use and/or integration of umodified components that have the SDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).  Eed test results in the case of composite products).  Notes:  Stully functional in IPv6 only environments. That is, no claimed capabilities if this product is deployed in a network environment that does not support ducts listed in the product family in section 5 are implemented such that their bilities are identical in form and function across the entire product family. The side of the USGV6 capabilities of an orbor of this product family are provided in this SDOC. The SDOC attests the
7 ES 8 [1] [2] [3]	Self Contact All of the decare addresse SDOC.  Additional Componer  Supplement	ained or Com lared USGv6 cape of by orginal test re il Declarations ent Supplier  This product is fic capabilities are in environment.  This SDOC conta	mary. (For each disp-prod-id/stack-1: US  posite SDOC? (Mu abilities of this product soults reported in this  s / Attachments: (L  attions (Answer all).  ally functional in dual stach invalidated ifthis product is  ains a capabilities test repe e stacks/ports not covered.	stinct IPv6 states SGv6-v1-Hos  SGv6-v1-Hos  Ist indicate on  ist supplier &  Product ID:  k environments. To soperated in a due operated	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Andrew IPv6-Base+Addr-An	Precision 7 ide a summ ch+IPsec-v.  Arch+SLA  cabilities of thi. All of the relete provided by s  referenced Stack ID:  YES	ary of its US 3+IKEv2+Si 3+IKEv2+Si AC+Link = s product are print reference specific referent diand attach  This product are invalidate four. All of the capai specific conferince intensitied mei these tested in the set set of the s	Dell Precision 7920 Tower  Gov6 capabilities below and include a detailed test result LAC+Link=Ethernet.  Ethernet  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).  The case of composite products).  Notes:  Is fully functional in IPv6 only environments. That is, no claimed capabilities if this product is deployed in a network environment that does not support that Island in the product family in section 5 are implemented such that their transce and interoperability test results for the USGv6 capabilities of an
7 ES 8 [1] [2] [3] [4] 9	Self Cont: All of the dec are addresse SDOC.  Additiona Compone  Supplement YES	ained or Com lared USGv6 cape d by orginal test re il Declaration: ent Supplier  Entary Attesta  This product is fic capabilities are in environment.  This SDOC cont product. If not, th capabilities differ	mary. (For each disp-prod-id/stack-1: US  upposite SDOC? (Mu abilities of this product esults reported in this  s / Attachments: (L  utions (Answer all).  dily functional in dual stack a movement of the product is a stack product is a capabilities test representations of the product is a capabilities test representation.	stinct IPv6 states SGv6-v1-Hos  JSGv6-v1-Hos  st indicate on  ist supplier &  Product ID:  k environments. To soperated in a dual poort for each unique dexplained.	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Andrew IPv6-Base+Addr-An	Precision 7 ide a summ ch+IPsec-v. Arch+SLA  pabilities of this All of the reference of the stack ID:  YES  YES	ary of its US 3+IKEv2+Si AC+Link = s product are product are product are product are product are invalidate lipv4.  All of the product are invalidate lipv4.  All of the product are invalidate lipv4.  All of the product are invalidate lipv4.	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet  Ethernet  Ethernet  Frovided by the use and/or integration of umodified components that have their SDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).  Rotes:  Notes:  Sit fully functional in IPv6 only environments. That is, no claimed capabilities diffusion that product is deployed in an intervork environment that does not support ducts listed in the product family in section 5 are implemented such that their bilities are identical in form and function across the entire product family. The other of this product family are provided in this SDOC. The SDOC attests that other of this product family are provided in this SDOC. The SDOC attests that
7 ES 8 [1] [2] [3] [4] 9	Self Contact All of the decare addresse SDOC.  Additional Componer  Supplement	ained or Com lared USGv6 cape d by orginal test re il Declaration: ent Supplier  Entary Attesta  This product is fic capabilities are in environment.  This SDOC cont product. If not, th capabilities differ	mary. (For each disp-prod-id/stack-1: US  posite SDOC? (Mu abilities of this product soults reported in this  s / Attachments: (L  attions (Answer all).  ally functional in dual stach invalidated ifthis product is  ains a capabilities test repe e stacks/ports not covered.	stinct IPv6 states SGv6-v1-Hos  JSGv6-v1-Hos  st indicate on  ist supplier &  Product ID:  k environments. To soperated in a dual poort for each unique dexplained.	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Andrew IPv6-Base+Addr-An	Precision 7 ide a summ ch+IPsec-v.  Arch+SLA  cabilities of thi. All of the relete provided by s  referenced Stack ID:  YES	ary of its US 3+IKEv2+Si 3+IKEv2+Si AC+Link = s product are print reference specific referent diand attach  This product are invalidate four. All of the capai specific conferince intensitied mei these tested in the set set of the s	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).  The product is product in the case of composite products).  Notes:  Is fully functional in IPv6 only environments. That is, no claimed capabilities of if this product is deployed in an entwork environment that does not support stucts listed in the product family in section 5 are implemented such that their bilities are identical in form and function across the entire product family. The other of this product family are provided in this SDOC. The SDOC attests that other of this product family are provided in this SDOC. The SDOC attests that
7 ESS 8 [1] [2] [3] [4]	Self Cont: All of the dec are addresse SDOC.  Additiona Compone  Supplement YES	ained or Com lared USGv6 cape d by orginal test re la Declaration: ent Supplier  This product is fic capabilities are in environment.  This SDOC contempoduct. If not, the capabilities difference.	mary. (For each disp-prod-id/stack-1: US  posite SDOC? (Mushilities of this product essults reported in this  s / Attachments: (L  attions (Answer all).  ally functional in dual stack invalidated ifthis product is  ains a capabilities test repe e stacks/ports not coverer from those reported are e	stinct IPv6 states GGv6-v1-Hos  JSGv6-v1-Hos  st indicate on  ist supplier &  Product ID:  k environments. To operated in a dual or of or each unique dare documente explained.	ision 5820 Tower, Dellack in the product provide IPv6-Base+Addr-Andrew IPv6-Base+Addr-An	Precision 7 ide a summ ch+IPsec-v. Arch+SLA  pabilities of this All of the relete provided by s referenced Stack ID:  YES  YES  Date	ary of its US 3+IKEv2+Si AC+Link = s product are product are product are product are product are invalidate lipv4.  All of the product are invalidate lipv4.  All of the product are invalidate lipv4.  All of the product are invalidate lipv4.	Dell Precision 7920 Tower  GGV6 capabilities below and include a detailed test result  LAC+Link=Ethernet.  Ethernet  Ethernet  Trovided by the use and/or integration of umodified components that have their ISDOCs are identified in section 8 and attached. This product's page 2 will ced components (product-id/stack-id).  The product is product in the case of composite products).  Notes:  Is fully functional in IPv6 only environments. That is, no claimed capabilities of if this product is deployed in an entwork environment that does not support stucts listed in the product family in section 5 are implemented such that their bilities are identical in form and function across the entire product family. The other of this product family are provided in this SDOC. The SDOC attests that other of this product family are provided in this SDOC. The SDOC attests that

11	Suppli	pliers Declaration of Conformity for USGv6 Products: Declared Capabilities and			ies and	Test Results Summa	ary	USGv6-v1 SDOC-v1.10 Page 2		
Product Id:		OptiPlex Stack Id						Windows 10		
		Context / Supported C		ted Capa	Canabilities		USGv6 Testing P	rogram Results		
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or		Test Lab / Result ID, Note #, or
	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Test Suite Interoperability	Component Ref
SP500-267		IPv6 Basic Requirements	· · · · · · · · · · · · · · · · · · ·					·		·
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	Р			Basic_v1.*_C	UNH-IOL/29557	Basic_V1.*_I	UNH-IOL/29560
		support of PMTU Discovery Protocol requirements	PMTU	Р			Basic_v1.*_C	UNH-IOL/29557	Basic_V1.*_I	UNH-IOL/29560
		support of stateless address auto-configuration	SLAAC	Р			SLAAC-V1.*_C	UNH-IOL/29557	SLAAC-V1.*_I	UNH-IOL/29560
		support of Creation of Global Addresses	SLAAC - c(M)	Р			SLAAC-V1.*_C	UNH-IOL/29557	SLAAC-V1.*_I	UNH-IOL/29560
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test	
		support of stateful (DHCP) address auto-	DHCP-Client				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I	
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test	
		support of neighbor discovery security extensions	SEND				Self Test		Self Test	
SP500-267	6.6	Addressing Requirements								
		support of addressing architecture reqts	Addr-Arch	Р			Addr_Arch_v1.*_C	UNH-IOL/29558	Addr_Arch_v1.*_I	UNH-IOL/29561
		support of cryptographically generated addresses	CGA				Self Test		Self Test	
SP500-267	6.7	IP Security Requirements	15. 0						ID 0 1 t 1	
		support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I	
		support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2_v2.*_I	
2000		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I	
SP500-267	6.11	Application Requirements	DNIC Client				0-15 T		Colf Tool	
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test	
		support of Socket application program interfaces	SOCK				Self Test		Self Test	
		support of IPv6 uniform resource identifiers support of a DNS server application	DNS-Server				Self Test		Self Test Self Test	
			DHCP-Server				Self Test		DHCP Serv v1.* I	
ODE00 007		support of a DHCP server application  Routing Protocol Requirements	DHCP-Server				Self Test		DHCF_Serv_VII	
SP500-267	6.2	support of the intra-domain (interior) routing protocols	IGW				Co# Too!		OSPFv3_v1.*_I	
			EGW				Self Test Self Test		BGP_v1.*_I	
SP500-267	6.4	support for inter-domain (exterior) routing protocols  Transition Mechanism Requirements	EGW				Sell Test		BGF_V11	
3P300-207	0.4	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test	
-		support of interoperation with 1P44-only systems support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test	
SP500-267	6.8	Network Management Requirements	01 L				Sell Test		Self Test	
3P300-207	0.0	support of network management services	SNMP				Self Test		Self Test	
SP500-267	6.9	Multicast Requirements	OIVIVII				Sell Test		Och Test	
31 300-207	0.9	support of basic multicast	Mcast				Self Test			
		full support of multicast communications	SSM				Self Test		Self Test	
SP500-267	6.10	Mobility Requirements					Con 1 cot		00# 7000	
0. 000 20.	0	support of mobile IP capability.	MIP				Self Test		Self Test	
		support of mobile network capabilities	NEMO				Self Test		Self Test	
SP500-267	6.3	Quality of Service Requirements								
		support of Differentiated Services capabilities	DS				Self Test		Self Test	
SP500-267	6.12	Network Protection Device Requirements								
		support of common NPD regts	NPD				N1 N2 N3 N4 v1.3			
		support of basic firewall capabilities	FW				N1_FW_v1.3			
		support of application firewall capabilities	APFW				Self Test			
		support of intrusion detection capabilities	IDS				N3_IDS_v1.3			
		support of intrusion protection capabilities	IPS				N4_IPS_v1.3			
SP500-267	6.5	Link Specific Technologies								
		support of robust packet compression services	ROHC				Self Test		Self Test	
		support of link technology [O:1]	III Ed	Р			Self Test	Self Declaration	Self Test	Self Declaration
		3,1 :								
		(repeat as needed) support of link technology	Link=							
12		< Check HERE if this stack's DOC include	es additional in	nformati	ion abo	ut teste	d capabilities and op	tions on an attached page 3	of notes.	
Level	I evel of	support for USGv6-v1 Requirements for canability	tv			Color	Indication	n of USGv6-v1 Recommended Lev	vel of Support for device	tyne / stack role
	Blank - SDOC makes no declaration for this capability.			20.01	Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.					
		required tests of USGv6-V1 requirements for these cap					Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.			
		es page for details on the level of support of USGv6-v1	reequirements for	this capab	ılıty.		Indicates capability that is I	eft optional / ocnditional by the recom	medations of the USGv6-v	1 Protile.
X	USGv6	capability not supported in product.								
^										
	Specific	USGv6 Test suite used for test. See: http://www.antd.i	nist.gov/usgv6/test	-specificat	ions.html			Note # - reference to	a detailed note about this	capability or result on attached page
est Suite - S		USGv6 Test suite used for test. See: http://www.antd.i			ions.html		Component Re	Note # - reference to f - Supplier / Product / Stack ID of dis		capability or result on attached pag

2 Discussion: 3	Page 3
Spec / Note # Reference Section USGv6-v1 Profile Requirements Option Host Router NPD Conformance/NPD Test Lab / Result ID, Note Interoperability Test Lab	
Note # Reference Section USGv6-v1 Profile Requirements Option Host Router NPD Conformance/NPD Test Lab / Result ID, Note Interoperability Test Lab / Result ID and Interoperability Test Lab / Result	
1 Discussion:  2 Discussion:  3 Discussion:	ilt ID, Note
Discussion:  2  Discussion:  3  Discussion:	
2 Discussion:  3 Discussion:	
Discussion:  3  Discussion:	
3 Discussion:	
Discussion:	
4	
Discussion:	
5	
Discussion:	
6	
Discussion:	
7	
Discussion:	
8	
Discussion:	
9	
Discussion:	-
10	
Discussion:	
Vendor's General Notes / Discussion about this Product / Stack's capabilities:	

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1.

Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field	Description and Instructions	Field	Description and Instructions
1	<b>The Document Requiring Conformity</b> : Identifies the profile version implemented. Not a user completable field.	11	<b>Summary of Results</b> : The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.
2	Product Identifier: Supplier's concise name for the product declared.		Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.
3	<b>Suppliers Name, Address and Contact Details</b> : Company name and point of contact for SDOC questions, street address, phone and email.		Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.
4	<b>Product as Tested/Declared:</b> Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).		<b>Test Suite Conformance and Interoperability</b> columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.
5	<b>Product Family</b> : A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.		The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.
6	<b>USGv6 Capability Summary</b> : The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).		Cells marked <b>Self Test</b> have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.
7	<b>Self Contained or Composite SDOC</b> : If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.	12	Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.  Headings and Special Notations: as described.
8	Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.		Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.
9	Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.	13	Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.
10	<b>Signature Block</b> : Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.		Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.