Suppli	ers Declaration of Cor		Products		Z	USGv6-v1 SDOC-v1.10 Page 1					
1	The Document Requ	iring Conformity:			USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)						
2	Product Identifier: InfiniStreamNG										
3	Supplier's Name, Ad	dress and SDOC Co	ntact Details								
	COUT Systems 310 Litt	leton Road, Westford	MA 01886 - Contact Karl Schaub (								
4	Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.  6.1										
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.  All ISNG Platforms, All nGenius Collector Platforms										
6 7 Yes	summary). e.g. example-prod-id/stack-1: USGv6-v1-Host: IPv6-Base+Addr-Arch+IPsec-v3+IKEv2+SLAC+Link=Ethernet.  USGv6-v1-Host: SLAAC+Addr-Arch+Link = Ethernet  Self Contained or Composite SDOC? (Must indicate one).										
0	are addressed by orginal to SDOC.		page 2 will indicate which o	capabil <mark>i</mark> ties are	OCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's spabilities are provided by specific referenced components (product-id/stack-id).  Treferenced and attached test results in the case of composite products).						
8			CONTRACTOR	Stack ID:		Notes:					
F43	Component Supplier		Product ID:	Stack ID.		Notes.					
[1]				+							
[2]				+							
[3]											
9	9 Supplementary Attestations (Answer all).										
	Yes  This product is fully functional in dual stack environments. That is, no claimed capabilities are invalidated ifthis product is operated in a dual stack (6 and 4) network environment.				This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment the does not support Ipv4.						
	product. If no	contains a capabilities test in the stacks/ports not cover lifter from those reported and	report for each unique IPv6 stack in the ered are documented, and how their Ipv6 re explained.	Yes	All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilities are identical and unmodified for all the products cited above.						
10	Signature	Mal Some	//	Date		12/2/2021					
	Print Name / Title	Mark Gosselin, Direc	tor, Engineering								
	ructions for fields 1-12 on Pa	000 1									

roduct Id	i:	InfiniCtroamNG										
Spec /		InfiniStreamNG Stack le					6.1					
Spec /		2-7-	Context /	Suppo	rted Capa	bilities		USGv6 Testing I				
Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note #, or Component Ref	Test Suite Interoperability	Test Lab / Result ID, Note # Component Ref		
P500-267	6.1	IPv6 Basic Requirements										
-		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	N			Basic_v1.*_C	UNH-IOL/30025, Note 1, 2, 4	Basic_V1.*_I	UNH-IOL/30026, Note 2		
		support of PMTU Discovery Protocol requirements	PMTU	N			Basic_v1.*_C	UNH-IOL/30025, Note 3	Basic_V1.*_I	UNH-IOL/30026, Note 3		
		support of stateless address auto-configuration	SLAAC	Р			SLAAC-V1.*_C	UNH-IOL/30025	SLAAC-V1.*_I	UNH-IOL/30026		
		support of Creation of Global Addresses	SLAAC - c(M)	Р			SLAAC-V1.*_C	UNH-IOL/30025	SLAAC-V1.*_I	UNH-IOL/30026		
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test			
		support of stateful (DHCP) address auto-	DHCP-Client				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I			
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test			
		support of neighbor discovery security extensions	SEND				Self Test		Self Test			
P500-267	6.6	Addressing Requirements						1,201,00007	Adda Arab ud t I	UNH-IOL/30028		
		support of addressing architecture reqts	Addr-Arch	Р			Addr_Arch_v1.*_C	UNH-IOL/30027	Addr_Arch_v1.*_I  Self Test	UNH-10L/30026		
		support of cryptographically generated addresses	CGA				Self Test		Sell Test			
P500-267	6.7	IP Security Requirements					15 0 11 0		IPsecv3 v1.* I			
		support of the IP security architecture	IPsecv3	100000			IPsecv3_v1.*_C		IKEv2_v2.*_I			
		support for automated key management	IKEv2	-2200			IKEv2_v1.*_C		ESP v1.* I			
		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESF_VII			
P500-267	6.11	Application Requirements	5110 0"				Call Tast		Self Test			
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test	-		
		support of Socket application program interfaces	SOCK				Self Test		Self Test			
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test			
		support of a DNS server application	DNS-Server				Self Test Self Test		DHCP Serv v1.* I			
		support of a DHCP server application	DHCP-Server				Sell Test		Brior_Serv_V1: _1			
P500-267	6.2	Routing Protocol Requirements	1014/				Self Test		OSPFv3_v1.*_I			
		support of the intra-domain (interior) routing	IGW EGW	-			Self Test		BGP v1.* I			
		support for inter-domain (exterior) routing protocols	EGW		-		Sell Test		50.7.1.1.			
P500-267	6.4	Transition Mechanism Requirements	IPv4		_		Self Test		Self Test			
		support of interoperation with IPv4-only systems	6PE	_			Self Test		Self Test			
		support of tunneling IPv6 over IPv4 MPLS services	OFE	-			Jen rest		Self Test			
P500-267	6.8	Network Management Requirements	SNMP		Marine Control		Self Test		Self Test			
0500.007		support of network management services  Multicast Requirements	SINIVII		SCSCHEROUSENCH		00111001					
P500-267	6.9	support of basic multicast	Mcast	service de la companya del companya del companya de la companya de	Street and the second		Self Test					
		full support of multicast communications	SSM	199402.5500.0000	Nanagara ( nanagara )		Self Test		Self Test			
DE00 007	6.10	Mobility Requirements	OOW									
P500-267	6.10	support of mobile IP capability.	MIP				Self Test		Self Test			
		support of mobile network capabilities	NEMO	V 1 - 200			Self Test		Self Test			
P500-267	6.3	Quality of Service Requirements	1120	1		7.00						
F300-207	0.5	support of Differentiated Services capabilities	DS		20075555		Self Test		Self Test			
P500-267	6.12	Network Protection Device Requirements										
F300-207	0.12	support of common NPD regts	NPD			and the	N1 N2 N3 N4_v1.3					
		support of basic firewall capabilities	FW				N1_FW_v1.3					
		support of application firewall capabilities	APFW	1			Self Test					
		support of application newall capabilities	IDS	responding.			N3_IDS_v1.3					
		support of intrusion protection capabilities	IPS	50000			N4_IPS_v1.3					
P500-267	6.5	Link Specific Technologies		23-23								
1 000-207	0.0	support of robust packet compression services	ROHC				Self Test		Self Test			
		support of link technology [O:1]		Р		1	Self Test	Self Declaration	Self Test	Self Declaration		
		5		0.000	MEG YOU							
		(repeat as needed) support of link technology	Link=									
12	х	< Check HERE if this stack's DOC includ	es additional	informa	tion abo	out test	ted capabilities and	options on an attached page	3 of notes.			
		of support for USGv6-v1 Requirements for capability.					Indication of USGv6-v1 Recommended Level of Support for device type / stack role.					
Level			ity.			Color	Indicates canability that is	s recommendend as mandatory (uno	conditional MUST) in the L	JSGv6-v1 Profile.		
		SDOC makes no declaration for this capability.	1.1951			- MARKAGE AND	Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.  Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.					
Р	Passed	ssed required tests of USGv6-V1 requirements for these capabilities.					Indicates cabability that is unusal for a given device type / stack fole. Do not select without careful analysis.  Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.					
N		e notes page for details on the level of support of USGv6-v1 reequirements for this capability.					indicates capability that is left optional / ocholional by the recommedations of the OSOVO-V11 rollie.					
X	USGv6	Gv6 capability not supported in product.										
c.Rep			41	- American	11.1				alasailas alasas alasas siria -	anability or recult an attached		
est Suite -	Specific	USGv6 Test suite used for test. See: http://www.anter- - Abbreviation of accredited laboratory and its local in	d.nist.gov/usgv6/t	est-specif	fications.h	tml	Note # - reference to a detailed note about this capability or result on attached page  Component Ref - Supplier / Product / Stack ID of distinctly tested component that provides this capability.					

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed					est Re	sults Su	mmary			USGv6-v1 SDOC-v1.10 Page 3		
Field Product Id:			InfiniStreamNG		Stack Id:					6.1		
13				Context /	Supported Capabilities			Notes about USG	Gv6-v1 Capabilities.			
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interoperability	Test Lab / Result ID, Note	
Note #	Helefelloc	Section	034V0-V1 F10IIIe Requirements	Option	HOSE	nouter	NPD	Comonnance/NFD	rest Lab / nesult ib, Note	interoperability	rest Lab / Result ID, Note	
1	RFC2460	4	IPv6 Specification	IPv6-Base	М			Basic_v1.*_C	UNH-IOL/30025			
Discussio	n:	The device	under test does not process IPv6 packets with Hop-	by-Hop Options. T	he device	e under tes	st does no	t process IPv6 packets	with Destination Options.			
2	RFC4861	8	Neighbor Discovery for IPv6	IPv6-Base	М			Basic_v1.*_C	UNH-IOL/30025	Basic_V1.*_I	UNH-IOL/30026	
Discussio	n:	The device	under test does not process ICMPv6 Redirect mess	ages.								
3	RFC1981		Path MTU Discovery for IPv6	IPv6-Base	М			Basic_v1.*_C	UNH-IOL/30025	Basic_V1.*_I	UNH-IOL/30026	
Discussio	n:	The device	The device under test doesn't reduce the Path MTU after receiving a Packet Too Big message.									
4	RFC4443		ICMPv6	IPv6-Base	м			Basic_v1.* C	UNH-IOL/30025			
Discussio	n:	The device	under test does not generate a Parameter Problem	messages in respo	nse to a	n unrecoar	nized nex	t header.				
5												
Discussio						<u> </u>						
6	1.											
Discussio												
7												
Discussio	2.											
8												
Discussion							l					
9												
						le le						
Discussion 10	1.											
									l			
Discussion Vendor's (	111	Discussion	on about this Product / Stack's capabilities:									