Suppliers Declaration of Conformity for USGv6 Products USGv6-v1 SDOC-v1.1 Page 1											
Supplie	The Document Requir		ducts			USGv6-v1 SDOC-v1.1 Page 1 USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)					
<u> </u>				<u> </u>		· • • · · ·					
2	Product Identifier: Cisco 4507R-E with SUP7E										
3	Supplier's Name, Add	ress and SDOC Conta	ct Details								
	ystems, Inc. st Tasman Dr.										
-	se, CA 95134										
USA											
4	Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.										
	IOS 15.0(2) SG										
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.										
	1. Totale 1. alimy (sailer producte doing sailer in to stabilly to this in those results and decided to apply). One of the date of alimy attention below.										
	Cisco 4503-E,Cisco 4506-E with SUP7E, Cisco 4507-E with SUP7E, Cisco 4507R+E with SUP7E, Cisco 4510R-E with SUP7E, Cisco 4510R-E with SUP7E										
6	USGv6 Capability summary. (For each distinct IPv6 stack in the product provide a summary of its USGv6 capabilities below and include a detailed test result summary).										
			IPv6-Base+Addr-Arch+IPsec-v3+IKE								
		US	GGv6-v1-Router:IPv6-Base+Addr-Arch	+IGW+FGW	V+SLAAC+L	ink=Fthermet					
		00	76 VI Rodier.ii vo Base 7 Radi 7 Rom	.1011.1011	V · OL/ V (O · L	mix-Euromot					
	Self Contained or Composite SDOC? (Must indicate one).										
YES	All of the declared USGv6 cap				ies of this product are provided by the use and/or integration of umodified components that have their own relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indicate which						
	addressed by orginal test results reported in this SDOC.			ecific referenced components (product-id/stack-id).							
	A dalidia a al Da alamatica				-44114	t and the in the same of a					
8		ns / Attachments: (List		renced and attached test results in the case of composite products).							
	Component Supplier		Product ID:	Stack ID:		Notes:					
[1]											
[2]											
[3]											
[4]											
9	Supplementary Attestations (Answer all).										
YES	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4.		This SDOC contains a capabilities test report for each unique IPv6 stack in the product. If	YES	All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member						
			not, please document which stacks/ports are								
			not covered, and how their IPv6 capabilities			t family are provided in this SDOC. The SDOC attests to the fact that these tested					
			differ from those reported in this SDOC.	1	USGv6 capabilities are identical and unmodified for all the products cited above.						
10	Signaturo	Darryll Cadaca		Date							
10	Signature	Darryll Gadson		Date							
	Print Name / Title	Darryll Gadson, Lead l	JSGv6 Cisco Systems								

		ers Declaration of Conformity for USGv6 Pro		u Capab			Nesults Sullillally	1		GGv6-v1 SDOC-v1.1 Pag				
roduct Id	:	Cisco 4507R-E with SUP	Stack Id			IOS 15.0(2)SG								
			Context /	Suppo	rted Capa	bilities			Program Results					
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #,				
	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interopoperability	Component Ref				
P500-267	6.1	IPv6 Basic Requirements support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	ID. C Dees		Р		Designed * C	LINILI/IOL 0504	Dania VA + I	LINIU//OL OFOE				
		support of IPV6 base (IPV6;ICMPV6;PMT0;ND) support of stateless address auto-configuration	IPv6-Base SLAAC		P		Basic_v1.*_C SLAAC-V1.*_C	UNH/IOL-8501 UNH/IOL-8502	Basic_V1.*_I SLAAC-V1.0 I	UNH/IOL-8505 UNH/IOL-8506				
		support of Stateless address a	PrivAddr		Р		Self Test	UNH/IOL-6502	Self Test	UNH/IOL-6506				
		support of stateful (DHCP) address auto-configuration	DHCP-Client				Self Test		DHCP_Client_v1.*_I					
		support of stateful (BHe) / address auto-configuration	DHCP-Prefix				Self Test		Self Test					
		support of automated router prenx delegation support of neighbor discovery security extensions	SEND				Self Test		Self Test					
P500-267	6.6	Addressing Requirements	OLIND				Con root		con rect					
		support of addressing architecture regts	Addr-Arch		Р		Addr Arch v1.* C	UNH/IOL-8503	Addr Arch v1.* I	UNH/IOL-8507				
		support of cryptographically generated addresses	CGA				Self Test		Self Test					
2500-267	6.7	IP Security Requirements												
		support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I					
		support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2v1.0_I					
		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I					
500-267	6.11	Application Requirements												
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test					
		support of Socket application program interfaces	SOCK				Self Test		Self Test					
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test					
		support of a DNS server application	DNS-Server				Self Test		Self Test					
2500 267		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I					
2500-267	6.2	Routing Protocol Requirements support of the intra-domain (interior) routing protocols	IGW		NI		Calf Toot		OSPFv3_v1.*_I	LINE/IOL 9500 Coo Note 1.2.2				
		support of the intra-domain (interior) routing protocols support for inter-domain (exterior) routing protocols	EGW		N P		Self Test Self Test		BGP_v1.*_I	UNH/IOL-8509, See Note 1,2,3 UNH/IOL-8508				
500-267	6.4	Transition Mechanism Requirements	EGW		Р		Sell Test		BGP_VII	UNH/IOL-6506				
300-207	0.4	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test					
		support of fine-logeration with 1 v4-only systems support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test					
2500-267	6.8	Network Management Requirements	- OI L				Jeli Test		Self Test					
000 201	0.0	support of network management services	SNMP				Self Test		Self Test					
2500-267	6.9	Multicast Requirements	0				00111001							
		support of basic multicast	Mcast				Self Test							
		full support of multicast communications	SSM				Self Test		Self Test					
2500-267	6.10	Mobility Requirements												
		support of mobile IP capability.	MIP				Self Test		Self Test					
		support of mobile network capabilities	NEMO				Self Test		Self Test					
P500-267	6.3	Quality of Service Requirements												
		support of Differentiated Services capabilities	DS				Self Test		Self Test					
		PHB Id					Self Test							
2500-267	6.12	Network Protection Device Requirements												
		support of common NPD regts	NPD				N1 N2 N3 N4							
	1	support of basic firewall capabilities	FW				N1_FW							
	-	support of application firewall capabilities support of intrusion detection capabilities	APFW IDS				N2_App_FW N3_IDS							
		support of intrusion detection capabilities support of intrusion protection capabilities	IPS				N4_IPS							
2500-267	6.5	Link Specific Technologies	IFO				N4_IF3							
300-201	0.5	support of robust packet compression services	ROHC				Self Test		Self Test					
		support of lobdst packet compression services support of link technology [O:1]			Р		Self Test	Self Declaration	Self Test	Self Declaration				
		support of link tearniology [C:1]	Link Lutomot				Con root	Con Boolaration	Con Test	Con Boolaration				
		(repeat as needed) support of link technology	l ink=											
40	V			matics	about to	atad ac-	aphilitian and anti-	on on ottophed years 2 of year	too	<u> </u>				
12	Х	< Check HERE if this stack's DOC includes a	idditional infor	mation	about te	stea cap	pabilities and option	is on an attached page 3 of no	tes.					
Level	1	evel of support for USGv6-v1 Requirements for capability.						Indication of USGv6-v1 Recommended Level of Support for device type / stack role.						
	Blank - SDOC makes no declaration for this capability. Passed required tests of USGv6-V1 requirements for these capabilities.					Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile. Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.								
Р														
N	1	See notes page for details on the level of support of USGv6-v1 reequirements for this capability.					Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.							
		apability not supported in product.							Associated application of the option of the property of the coordinate of the coordi					
		A secondary of house.												
					.html			Note # - reference to						

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary									USGv6-v1 SDOC-v1.1 Page 3			
	Product Id:		Cisco 4507R-E with SUP	Stack lo	d:		IOS 15.0(2)SG					
0(Context /	Supported Capabilities		abilities		Notes about USGv6-v1 Capabi			
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interopoperability	Test Lab / Result ID, Note	
1	RFC2740	Cisco su	OSPF for IPv6 pports an older implementation of this RFC and we belie	IGW ve it is not a critical	l failure by	c(M) any mear	l is. Our pro	L ducts will function fine wh	l en implemented according to our g	OSPFv3_v1.*_I guidance. However, we will	UNH/IOL-8509; Test Case 4.3 take steps to modify our	
Discussion	1:	impleme	entation to correct this behavior in a future release.									
2	RFC2740		OSPF for IPv6	IGW		c(M)				OSPFv3_v1.*_I	UNH/IOL-8509 Test Case 3.2, 4.5	
Discussion		Cisco's implementation is in accordance with the RFC's for these tests. The testcase needs to be written and executed differently to get the desired result. Please contact Cisco to see the test report provided by UNH-IOL for additional details										
3	RFC4552		Authentication/Confidentiality for OSPFv3	IGW		c(M)				OSPFv3_v1.*_I	UNH/IOL-8509; Test Case 5.1, 5.2	
		This fea	sture is currently not supported on this specific device. Ple		h Cisco a		rogress on	implementation of this fe	eature.	00.110_111	0.2	
Discussion	ı:		I		I	I	ı		<u> </u>	T		
4												
Discussion	1:											
5												
Discussion	1:											
6												
Discussion	ı:											
7												
Discussion	1:											
8												
Discussion	1:											
9												
Discussion	ı:											
10												
Discussion												
General Notes / Discussion about this Product / Stack's capabilities:												

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field Description and Instructions 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completeable field. 2 Product Identifier: Supplier's concise name for the product declared.

3 Suppliers Name, Address and Contact Details: Company name and point of

contact for SDOC questions, street address, phone and email.

- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- **6 USGv6 Capability Summary**: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Field Description and Instructions

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent **Test Lab and Result Id** column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (*e.g.* "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

12 Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.