Suppli	ers Declara	tion of Conformity	for USGV8 Pro	ducts	USGv6-v1 SDCC-v1.10 Page 1								
1 The Document Requiring Conformity:							USGv6 Profile Version 1.0, July 2008. (NIST 8P500-287)						
2	Product Identifier: Arista DCS-7280R Series												
3		Name, Address as	nd SDOC Cont	act Details									
	M Jackson												
	ced Services	ngineering Team											
	Networks, In												
	rista.com												
	: 520-227-9 408-547-53												
			: Product (dent	llier, version/rev	ision information, deta	Na of confla	uration test	ed.					
-	11.1000001	. 1000000000000000000000000000000000000	. / 100001 10011		EOS Version								
5	Product F	amily (other produc	cts using same	IPv6 stack(s) to	which these results ar	e declared	to apply). (Check Product Family attestation below.					
(Mc	odular (DCS	-7280SR-4808, DC	S-7280SRA-48	24C2 DCS-72801	0.01B.48 DCS-70201R	A-48 DCS-	7280SE-72	AM-4808, DCS-7280QR-C38, DCS-72808RM-40CX2, DCS- , DCS-7280SE-68, DCS-7280SE-64, DCS-7280QR-C72, DCS-					
728	CORA-CRES	DCS-7280CR2K-3	0 DCS-728DC	R2A-30, DC3-72	280SR2-48YC6, DCS-	7280SR2A	48YC6, DC	S-7280CR2M-30, DCS-7280SR2K-48C6, DCS-7280CR2-60,					
DOS.	TORNERSA.	60 DCS-7280CR26	C-80, DCS-7280	0PR3-24, DCS-7	7280PR3K-24, DCS-72	280DR3-24	DCS-7280	DR3K-24, DCS-7280SR3-40YC8, DCS-7280TR3-40C8, DCS-					
7280	CR1-12P4	DCS-7280CR3K-32	P4 DCS-72800	CR3MK-32P4, D	CS-7280CR3-32D4, D	XCS-7280C	R3K-32D4	DCS-7280CR3MK-32D4, DCS-7280CR3-96, DCS-7280CR3K-					
36]X C	hassis DCS	-7504, DCS-7504N	DCS-7608, DC	CS-7508N, DCS	-7512N, DCS-7516N, I	DCS-7804-	CH, DCS-78	(08-CH]), (Line Cards [75488-LC, 7500E-360-LC, 7500E-468-					
LC, 75	00E-72S-L	C, 7500E-12CM-LC,	7500E-6C2-LC	3, 7500E-728-L	C, 7500E-485-LC, 750	2-18CO-LC	7500R2-3	6CFPX-LC, 7500E-48T-LC, 7500R-8CFPX-LC, 7500R-36Q-LC, 6CQ-LC, 7500R2A-36CQ-LC, 7500R2AK-36CQ-LC, 7500R2M-					
38	CO-LC 750	DR2AM-36CO-LC. 7	800R3-48CQ4	C. 7800R3K-4	BCQ-LC, 7800R3-48C	MLC, 750	0R3-24P-L	C, 7500R3-24D-LC, 7500R3-36CQ-LC, 7500R3K-36CQ-LC,					
					700000 20	DICH							
6	USGVE C	apability summary	. (For each dis	Inct IPVB stack	in the product provide v6-Base+Addr-Arch+//	Page-v3+JK	FUZ+SLAC	v6 capabilities below and include is detailed test result					
	[BUITTHBIY]	а.р. ехапира-рюс	HWatack-7. UG	USGv6-v1-Ro	uter: IPv6-Base+Addr	-Arch+SLA	AC+Link =	Ethernet					
	To 1/2	-110H	enors (La	ladicata anal			-						
7		ained or Composit		I Go	one or all of the USGuS cacetal	Urles of this pro-	act ere provide	at by the use enalty integration of umadified components that have their own unique					
Yes	All of the declared USGNB capabilities of this product are actorisesed by original heal results reported in this SDOC.			USG/5 SDOCs. All of the relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 wW indicate who									
				ere provided by specific referenced components (product-latitation-latit.									
8	Additions	I Declarations / At	tachmente: (Li	at supplier & pro	duct-ld/stack-id for refe	ld/stack-id for referenced and attached test results in the case of composite products).							
		int Supplier		Product ID:		Stack ID:	CARLES SO	Notes:					
[1]	COMPONE												
[2]													
[3]													
[4]													
9		entary Attestations				Iv	Inches de la contraction de la	- 6.4. 6 method in Khali only one becoming That is no cisimor appetition on					
	Yes	Yes This product is tally functional in dual stack environments. That is, no claimed capabilities are invalidated titles product is operated in a dual stack (8 and Gnetwork environment.				Yes	This product is fully functional to NPv6 only environments. That is, no claimed capabilities are unself-dated if this product is deployed in a network environment that does not support (pv4.						
	Yes	Yes This SOOC contains a capetablies item report for each unique iPvd stack in the product. If not, the stacks/ports not covered are obsumented, and how their god capabilities differ from those						All of the products Visted in the product family in section 5 are implemented such that their USG v6 capetalities are identical in form and function across the entire product family. The specific					
		see obcumered, an	d how their got case.	ENISES DIFF PUT SICES		conformance and interoperability test results for the USBv6 capabilities of an identified member of							
	0 32 2 12	reported are explained.					this product family are provided in this SDOC. The SDOC affects that these leated USGV6						
							capen Vileser	e identical and unmodified for all the products often above.					
10	Signature		4.	M Jaroka		Date 7-Jul-20							
	Print Nam		h M Jackson A	dela Networks I	nc. Advanced Services	s Engineer							
100000													
See has	runtions for fields	1-12 on Page 4											

		iers Declaration of Conformity for USGv6 I		nai eu C	Τ.		Test Nesults Suillill			Gv6-v1 SDOC-v1.10 Pag			
duct lo	d:	Arista DCS-7280R Seri	es		Stack I	ld:			EOS Version 4.24.1F	=			
		Context / Supported Capabi						USGv6 Testing Program Results					
Spec/			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #			
ference	Section	USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperability	Component Ref			
500-267		IPv6 Basic Requirements							' '				
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base		Р		Basic_v1.*_C	UNH-IOL/32112	Basic_V1.*_I	UNH-IOL/32113			
		support of PMTU Discovery Protocol requirements	PMTU		Р		Basic_v1.*_C	UNH-IOL/32112	Basic_V1.*_I	UNH-IOL/32113			
		support of stateless address auto-configuration	SLAAC		P		SLAAC-V1.*_C	UNH-IOL/32112	SLAAC-V1.*_I	UNH-IOL/32113			
		support of Creation of Global Addresses	SLAAC - c(M)		P		SLAAC-V1.*_C	UNH-IOL/32112	SLAAC-V1.* I	UNH-IOL/32113			
		support of SLAAC privacy extensions.	PrivAddr		<u> </u>		Self Test	01111102/02112	Self Test	0.11.102/02110			
		support of stateful (DHCP) address auto-	DHCP-Client				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I				
		support of stateful (Dirior) address addo-	DHCP-Prefix				Self Test		Self Test				
		support of automated router premy delegation support of neighbor discovery security extensions	SEND				Self Test		Self Test				
500-267	6.6	Addressing Requirements	SLIND				Sell Test		Sen rest				
000-207	0.0		Addr-Arch		P		Addu Arab v4 * C	LINILLIOL/22444	Addu Anala vet * I	LINII I IOI /22445			
		support of addressing architecture reqts			Р			UNH-IOL/32114	Addr_Arch_v1.*_I	UNH-IOL/32115			
-00.007		support of cryptographically generated addresses	CGA				Self Test		Self Test				
500-267	6.7	IP Security Requirements											
		support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C	1	IPsecv3_v1.*_I	1			
		support for automated key management	IKEv2				IKEv2_v1.*_C	1	IKEv2_v2.*_I				
		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I				
500-267	6.11	Application Requirements											
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test				
		support of Socket application program interfaces	SOCK				Self Test		Self Test				
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test				
		support of a DNS server application	DNS-Server				Self Test		Self Test				
		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I				
500-267	6.2	Routing Protocol Requirements											
		support of the intra-domain (interior) routing	IGW				Self Test		OSPFv3_v1.*_I				
		support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP_v1.*_I				
500-267	6.4	Transition Mechanism Requirements	2011										
000 201	0.7	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test				
		support of funneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test				
500 267	6.0		UFE				Sell Test		Self Test				
300-207	0.0	Network Management Requirements	SNMP				Colf Took		Self Test				
F00 007		support of network management services	SINIVIP				Self Test		Sell Test				
500-267	6.9	Multicast Requirements	Magat				Colf Took						
		support of basic multicast	Mcast				Self Test		Colf Tool				
F00 007	0.40	full support of multicast communications	SSM				Self Test		Self Test				
500-267	6.10	Mobility Requirements					2 15 - 1		2 " - 1				
		support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO				Self Test		Self Test				
500-267	6.3	Quality of Service Requirements											
		support of Differentiated Services capabilities	DS				Self Test		Self Test				
500-267	6.12	Network Protection Device Requirements											
		support of common NPD reqts	NPD				N1 N2 N3 N4_v1.3						
		support of basic firewall capabilities	FW				N1_FW_v1.3						
		support of application firewall capabilities	APFW				Self Test						
		support of intrusion detection capabilities	IDS				N3_IDS_v1.3						
		support of intrusion protection capabilities	IPS				N4_IPS_v1.3						
500-267	6.5	Link Specific Technologies											
		support of robust packet compression services	ROHC				Self Test		Self Test				
		support of link technology [O:1]			Р		Self Test	Self Declaration	Self Test	Self Declaration			
							3011 1000	CC. Social allon	301001				
		(repeat as needed) support of link technology	ink=						 	 			
	<u> </u>	, , , , , , , , , , , , , , , , , , ,							<u> </u>				
12		< Check HERE if this stack's DOC include	es additional i	nformat	tion abo	out teste	ed capabilities and o	ptions on an attached page 3	3 of notes.				
.evel	LovoLo	f cupport for USGv6 v4 Paguiroments for canabili	h			Color	Indication of USGv6-v1 Recommended Level of Support for device type / stack role.						
	Blank - SDOC makes no declaration for this capability.						Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.						
	Passed required tests of USGv6-V1 requirements for these capabilities.						Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.						
N See notes page for details on the level of support of USGv6-v1 reequirements for this capability.							Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.						
Χ	USGv6	capability not supported in product.											
est Suite - Specific USGv6 Test suite used for test. See: http://www.antd.nist.gov/usgv6/test-specifications.html						Note # - reference to a detailed note about this capability or result on attached page 1							
. Juile -		 Abbreviation of accredited laboratory and its local id 				14111	Component Bof	- Supplier / Product / Stack ID of dis					
Lah/P	Perilt ID	 AppleAlgilob of accredited laboratory and its local id 	EUIIIIEI IOI IOIG IBI										

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary USGv6-v1 SDOC-v1.10									-v1 SDOC-v1.10 Page 3		
Field Product Id:						Stack I	d:				
13				Context /	Supported Capabiliti				Notes about USG	v6-v1 Capabilities.	
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interoperability	Test Lab / Result ID, Note
NOTE #	Keierence	Section	030V0-V1 F10IIIe Requirements	Орион	11031	Kouter	NFD	Comormance/NFD	rest Lab / Nesult ID, Note	interoperability	rest Lab / Nesult ID, Note
1											
Discussion	n·										
Diocussio											
2											
Discussion	Discussion:										
3											
Discussion:											
4											
7					l						
Discussion	1:				I	1 1					
5											
Discussion	1:										
6											
Discussion											
DISCUSSIO	1:										
7											
Discussion	n:										
	<u></u>										
8											
Discussion	n:										
9											
Discussion	n:										
10											
					<u>I</u>	<u> </u>					
Discussion:											
Vendor's General Notes / Discussion about this Product / Stack's capabilities:											

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field

Field Description and Instructions

- 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completable field.
- 2 Product Identifier: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- **6 USGv6 Capability Summary**: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- **Signature Block**: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Description and Instructions

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.

Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.

Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.