1			enformity for USGv6 wiring Conformity:	Products			USGv6-v1 SDOC-v1-10 Page USGv6 Profile Version 1.0, July 2008, (NIST SP500-2				
2	2 Product Identifier: NSX-T Data Center										
3											
Vmwar 3401 F	re hillview Ave	2									
	Palo Alto, CA 94304										
4 Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.											
					3.0)					
5. Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.											
-											
6	USGV6 C	anability s	ummary /For each d	stinct IPv6 star	k in the product pro-	vide a sum	mmary of its USGv6 capabilities below and include a detailed test resul				
			nple-prod-id/stack-1: U	SGv6-v1-Host:	IPv6-Base+Addr-Ar	ch+/Psec-	:-v3+IKEv2+SLAC+Link=Ethernet.				
			USG	v6-v1-Router:	IPv6-Base+Addr-A	rch+SLAA	AC+EGW+Link = Ethernet				
7		o i se su se	omposite SDOC? (Mi		245						
YES			capabilities of this product est results reported in this				f this product are provided by the use and/or integration of umodified components that ha f the relevant referenced SDOCs are identified in section 8 and attached. This product's				
	SDOC.			pag	ge 2 will indicate which ca	pabilities are	re provided by specific referenced components (product-id/stack-id).				
8	Additiona	il Declarat	ons / Attachments: (/	.ist supplier & p	woduct-id/stack-id fo	r reference	ced and attached test results in the case of composite products).				
	ridial (dit co colora) (higipai (dit	ent Supplie		Product ID:		Stack ID:					
[1]											
[2]											
[3] [4]				1							
9	Suppleme	entary Atte	stations (Answer all)								
pinter maintable realized			A CONTRACTOR OF A CONTRACT	ck environments Tl	-,	NO					
l .	YES		,				This product is fully functional in IPv6 only environments. That is, no claimed capabili				
	YES		are invalidated ifthis product	is operated in a du	al stack (6 and		are invalidated if this product is deployed in a network environment that does not support lpv4.				
	YES	capabilities a 4)network ei This SDOC	are invalidated ifthis product ivironment. contains a cepabilities test re	port for each uniqu	ie IPv6 stack in the	N/A	are invalidated if this product is deployed in a network environment that does not support lpv4. All of the products listed in the product family in section 5 are implemented such that				
		capabilities a 4)network er This SDOC product. If n	are invalidated ifthis product avironment.	port for each uniqued are documented	ie IPv6 stack in the	N/A	are invalidated if this product is deployed in a network environment that does not support lpv4.				
		capabilities a 4)network er This SDOC product. If n	are invalidated ifthis product avironment. contains a cepabilities test re ol, the stacks/ports not cover	port for each uniqued are documented	ie IPv6 stack in the	N/A	 are invalidated if this product is deployed in a network environment that does not support lpv4. All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. 				
		capabilities a 4)network er This SDOC product. If n	are invalidated ifthis product avironment. contains a cepabilities test re ol, the stacks/ports not cover	port for each uniqued are documented	ie IPv6 stack in the	N/A	are invalidated if this product is deployed in a network environment that does not support lpv4. All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6				
10		capabilities a 4)network ei This SDOC product. If no capabilities o	are invalidated ifthis product avironment. contains a cepabilities test re ol, the stacks/ports not cover	port for each uniqued are documented	ie IPv6 stack in the	N/A Date	 are invalidated if this product is deployed in a network environment that does not support lpv4. All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilities are identical and unmodified to all the products cited above. 				
10	YES	capabilities a 4)network ei This SDOC (product. If n capabilities (are invalidated ifthis product avironment. contains a cepabilities test re ol, the stacks/ports not cover	port for each uniqu ed are documented explained.	ie IPv6 stack in the		 are invalidated if this product is deployed in a network environment that does not support lpv4. All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests that these tested USGv6 capabilitiesare identical and unmodified tall the products cited above. 				

- 11	Suppl	iers Declaration of Conformity for USGve	Products: De	clared 0	Capabili	ities an	d Test Results Summ	nary	US	Gv6-v1 SDOC-v1.10 Pag
Product lo	100 10 10 10 10 10 10 10 10 10 10 10 10	NSX-T Data Center			Stack				3.0	
			Context /	Suppo	orted Cap	abilities		USGv6 Testing	Program Results	
Spec /			Configuration		1.		Test Suite	Test Lab / Result ID, Note # or		Test Lab / Result ID. Note #
		USGv5-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperability	Component Ref
SP500-267	5.1	IPv6 Basic Requirements		1						
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND			P		Basic_v1.*_C	UNH-IOL/31753	Basic_V1.*_I	UNH-IOL/31754
		support of PMTU Discovery Protocol requirements			P		Basic_v1.*_C	UNH-IOL/31753	Basic_V1.*_I	UNH-IOL/31754
	·	support of stateless address auto-configuration			P		SLAAC-V1.*_C	UNH-IOL/31753	SLAAC-V1.*_I	UNH-IOL/31754
		support of Creation of Global Addresses			P		SLAAC-V1.*_C	UNH-IOL/31753	SLAAC-V1.*_I	UNH-IOL/31754
-		support of SLAAC privacy extensions	. PrivAddr				Self Test		Self Test	
		support of stateful (DHCP) address auto			.	-	DHCP_Client_v1.*_C		DHCP_Client_v1.*_i	
		support of automated router prefix delegation		+			Self Test		Self Test	
P500-267		support of neighbor discovery security extensions Addressing Requirements	s SEND		a de la companya de l	-	Self Test		Self Test	
LODA-401	1992.000 9310	Reducessing requirements		a <u>Stretter</u> (1913						
		support of addressing architecture reqts			P.		Addr_Arch_v1.*_C	UNH-IOL/31752	Addr_Arch_v1.*_I	UNH-IOL/31755
P500-267	67	support of cryptographically generated addresses IP Security Requirements					Self Test		Self Test	
1.000-2.07	9 -1	support of the IP security architecture	Deserve							- 1 N 1-18553 (* 1777)
							IPsecv3_v1.*_C		IPsecv3_v1.*_I	
		support for automated key management support for encapsulating security payloads in IP			L		IKEv2_v1.*_C		IKEv2_v2.*_I	
2500.267	6 4 4	Application Requirements					ESPv3_v1.*_C		ESP_v1.*_I	
U GOOTLUI		support of DNS client/resolver functions					and the second se			
		support of Socket application program interfaces			The Maler and Ang		Self Test		Self Test	
		support of IPv6 uniform resource identifiers					Self Test		Self Test	
		support of a DNS server application					Self Test Self Test		Self Test	
		support of a DHCP server application		{		l	Self Test		Self Test	······································
P500-267	6.2	Routing Protocol Requirements							DHCP_Serv_v1.*_I	
		support of the intra-domain (interior) routing	IGW				Self Test		OSPFv3 v1.* I	
		support for inter-domain (exterior) routing protocols	EGW	191 191 191	Р		Self Test		BGP_v1.*_I	UNH-IOL/32628
P500-267	6.4	Transition Mechanism Requirements				Linitis (B)			BGF_VII	
i una ta ta ta ta	and the second	support of interoperation with IPv4-only systems					Self Test		Self Test	
		support of tunneling IPv6 over IPv4 MPLS services				-	Self Test		Self Test	······
P500-267	6.8	Network Management Requirements				Sec.			Self Test	
	-6-14 (7-49-27 1-8)	support of network management services				CRIMENC + CRIC:	Self Test		Self Test	
2500-267	6.9	Multicast Requirements								
	arath / to 1 to 1 to 1	support of basic multicast			historia	L STORAGE BUT DEC	Self Test			Excession (MARINE) (1) Marine (MARINE) (MARINE (MARINE)
		full support of multicast communications		Canal And Addression	5.640 (196 Albert 1996)		Self Test		Self Test	
2500-267	6.10	Mobility Requirements								
		support of mobile IP capability.	MIP			and a second second	Self Test	a herbeneti vant stante parten fillen (her Fillen fillen fillen herbenet herb	Self Test	
		support of mobile network capabilities	NEMO				Self Test		Self Test	
P500-267	6.3	Quality of Service Requirements							vivere second	
		support of Differentiated Services capabilities	DS				Self Test	l line line line line line line line lin	Self Test	
P500-267	6.12	Network Protection Device Requirements					Private States and the second states of the second			
		support of common NPD regts					N1 N2 N3 N4_v1.3		CONTRACTOR AND ADDRESS OF TAXABLE PARTY OF TAXABLE PARTY.	
		support of basic firewall capabilities	FW			ang 111 pang 2003 38	N1_FW_v1.3			t
		support of application firewall capabilities					Self Test		· · ·	h
		support of intrusion detection capabilities					N3_IDS_v1.3	[
I	<u> </u>	support of intrusion protection capabilities	IPS				N4_IPS_v1.3			· · · · · · · · · · · · · · · · · · ·
2500-267	6.5	Link Specific Technologies					An exercise to the second s			
		support of robust packet compression services					Self Test		Self Test	
		support of link technology [0:1]	Link=Ethernet		S P		Self Test	Self Declaration	Self Test	Self Declaration
					5 decision decisione					· · · · · · · · · · · · · · · · · · ·
		(repeat as needed) support of link technology	Link≖							
			Ship in the same of the same of the set		ion sho	un taet	ed canabilities and a	mione on or attached name		
12		< Check HERE if this stack's DOC Includ	as additional in				on cahanumas and o	kazus virai⊨enačnica hače 3	VI NVICO.	
12		< Check HERE If this stack is DOC Includ	1. A first de fait (1. d'effe the care hormer e errers	\$ 22533 Cale 185 QL Sec 111.	tenting whereas the models	5007.111 V 00		Contraction of the second s	THE REPORT OF TH	A REAL AND A REAL PROPERTY AND A
	10.152.01			\$ 22533 Cale 185 QL Sec 111.						
Level L	_evel of	support for USGv6-v1 Requirements for capabili		\$ 22533 Cale 185 QL Sec 111.	tenting whereas the models	Color	Indicatio	n of USGv6-v1 Recommended Lev	el of Support for device	
Level L	_evel of Blank - S	support for USGv6-v1 Requirements for capabilit DOC makes no declaration for this capability.	ity.	\$ 22533 Cale 185 QL Sec 111.	tenting whereas the models	Color	Indicatio Indicates capability that is	n of USGv6-v1 Recommended Lev recommendend as mandatory (unco	el of Support for device nditional MUST) in the US	Gv6-v1 Profile.
Level L B P P	_evel of Blank - S Passed r	support for USGv6-v1 Requirements for capabilit DOC makes no declaration for this capability. equired tests of USGv6-V1 requirements for these c	apabilities.			Color	Indicatio Indicates capability that is	n of USGv6-v1 Recommended Lev recommendend as mandatory (unco	el of Support for device nditional MUST) in the US	Gv6-v1 Profile.
Level L B P P	_evel of Blank - S Passed r	support for USGv6-v1 Requirements for capabilit DOC makes no declaration for this capability.	apabilities.			Color	Indicatio Indicates capability that is Indicates cabability that is	n of USGv6-v1 Recommended Lev recommendend as mandatory (unco unusal for a given device type / stacl	el of Support for device nditional MUST) in the US k role. Do not select with	Gv6-v1 Profile. out careful analysis.
Level L B P P N S	_evel of Blank - S Passed r See note	support for USGv6-v1 Requirements for capabilit DOC makes no declaration for this capability. equired tests of USGv6-V1 requirements for these c	apabilities.			Color	Indicatio Indicates capability that is Indicates cabability that is	n of USGv6-v1 Recommended Lev recommendend as mandatory (unco	el of Support for device nditional MUST) in the US k role. Do not select with	Gv6-v1 Profile. out careful analysis.
Level L B P F N S X U	_evel of Blank - S Passed r See note JSGv6 c	support for USGv6-v1 Requirements for capability. DOC makes no declaration for this capability. equired tests of USGv6-V1 requirements for these c s page for details on the level of support of USGv6-v apability not supported in product.	i ty. apabilities. /1 reequirements fo	or this cap	pability.	Color	Indicates Indicates capability that is Indicates cabability that is Indicates capability that is	n of USGv6-v1 Recommended Lev recommendend as mandatory (unco unusal for a given device type / stacl left optional / ocnditional by the reco	el of Support for device nditional MUST) in the US k role. Do not select with mmedations of the USGv	GCv6-v1 Profile. out careful analysis. 3-v1 Profile.
Level L P F N S X U	Level of Blank - S Passed r See note JSGv6 c	support for USGv6-v1 Requirements for capability. DOC makes no declaration for this capability. equired tests of USGv6-V1 requirements for these c s page for details on the level of support of USGv6-v apability not supported in product.	ity. apabilities. /1 reequirements fo	or this cap	pability.	Color	Indicates Indicates capability that is Indicates cabability that is Indicates capability that is	n of USGv6-v1 Recommended Lev recommendend as mandatory (unco unusal for a given device type / stacl left optional / ocnditional by the reco	el of Support for device nditional MUST) in the US k role. Do not select with mmedations of the USGvk	SGv6-v1 Profile. out careful analysis. 3-v1 Profile.
Level L B P P N S X U	Level of Blank - S Passed r See note JSGv6 c	support for USGv6-v1 Requirements for capability. DOC makes no declaration for this capability. equired tests of USGv6-V1 requirements for these c s page for details on the level of support of USGv6-v apability not supported in product.	ity. apabilities. /1 reequirements fo	or this cap	pability.	Color	Indicates capability that is Indicates cabability that is Indicates cabability that is	n of USGv6-v1 Recommended Lev recommendend as mandatory (unco unusal for a given device type / stacl left optional / ocnditional by the reco	el of Support for device nditional MUST) in the US k role. Do not select with mmedations of the USGve	SGv6-v1 Profile. out careful analysis. 3-v1 Profile. Multiple and the second s

Supplier	s Declaratio	on of Cor	nformity for USGV8 Products Notes Page	and Detailed T	est Re	sults Si	immary			USGV6	-v1 SDOC-v1 10 Page 3
Field 13	Product Id:				1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Stack I				ム : 見動引為	
13	5pec/			Context / Configuration	Suppo	orted Cap	abilities	Tool Suite	Notes about US	376-v1 Capabilities:	
Note #	Reference	Section	USGv6-vt Profile Requirements	Configuration Option	Host	Router	NPD	Contormance/NPD	Test Lab / Result ID, Note	Interoperability	Test Lab / Result ID; Note
1										· ·	
Discussio	n:			- 2010					n and the state		
2											
Discussio	n:			-					NAMES OF ALL		
3	W =318	6									
Discussio	n.										
4		0*3									
Discussio			1	1		<u>tioni ses</u>	- 15 - E		1	<u> </u>	
	<u>n.</u>		T					1			
5		-	1	1		L			1	1	
Discussio	n:								52		
6			1	11.000				ļ		<u>1</u>	
Discussio	<u>n:</u>				· · · · ·	[
7		-11				I					1
Discussio	n;	-		1	<u>n n</u>	r				r	
8	 The sub-sub-sub-sub-sub-sub-sub-sub-sub-sub-	-									
Discussio	n:				1.	1.01					
9											
Discussio	n.										
10											
Discussio	n:		<u></u>	ا ا ر				I	kernen in felderen er en		
		/ Discussi	ion about this Product / Stack's capabilities:								200 - 20002391101 - DAI
	*** *****						52.145				

Suppliers Declaration of Conformity for USGv6 Description and Instructions General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field	Description and Instructions	Field	Description and Instructions
1	The Document Requiring ConformIty: Identifies the profile version implemented. Not a user completable field.	11	Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.
2	Product Identifier: Supplier's concise name for the product declared.		Product Id/Stack Id : The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.
3	Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.		Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.
4	Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).		Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.
5	Product Family : A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.		The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.
6	USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).		Cells marked Self Test have no associated public test suite. If implemented by the supplier, the required adjacent annotation is " <i>Self Declaration</i> ". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.
7	Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.	12	Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary. Headings and Special Notations: as described.
8	Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.		Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.
9	Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.	13	Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.
10	Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.		Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6- Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.

Further Description: http://www.antd.nist.gov/usgv6/testing.html, and NIST SP 500-267 USGv6 Testing Program Users Guide available at the website.