Supplie	ers Declaration of Conformity for	USGv6 Proc	ducts			USGv6-v1 SDOC-v1.1 Page					
1	The Document Requiring Confo		14013			USGv6 Profile Version 1.0, July 2008. (NIST SP500-26					
2	Product Identifier:			(	Cisco SC	· •					
3	Supplier's Name, Address and S	DOC Conta	ct Details								
Cisco S	ystems Inc.										
	est Tasman Dr.										
San Jos	se, CA 95134										
USA											
4	Product as Tested/Declared: Product Identifier, version/revision information, details of configuration tested.										
			1.	1							
5	Product Family (athor products a	oing come IF	by 6 stack(s) to which those requite	o doolared to	annly) Cha	ok Product Family attentation below					
J	Froduct Family (other products u	sing same in	vo stack(s) to which these results ar	e deciared (o	арріу). <b>Спе</b>	ck Product Family attestation below.					
			Ciaca CE200 VV Ciaca CO200 VV	Ciasa 05000	VV 0: 0	20200 VV					
	Cisco SF200-XX, Cisco SG200-XX, Cisco SF300-XX, Cisco SG300-XX										
6						apabilities below and include a detailed test result summary).					
	e.g. example-prod-id/stack-1: USG	3v6-v1-Host:	IPv6-Base+Addr-Arch+IPsec-v3+IK	<u>=v2+SLAC+Lii</u>	nk=Ethernet						
			USGv6-v1-Host: IPv6-Base+Ad	dr-Arch+SLAA	C+Link=Eth	nernet					
7	Self Contained or Composite SE	nnc2 (Must i	indicate one)								
	·	•	<u> </u>	nahilitiaa of thia n	raduat ara prov	yidad bu tha uga and/or integration of umadified companyon to that have their own					
YES	All of the declared USGv6 capabilities of this product are addressed by orginal test results reported in this SDOC.				abilities of this product are provided by the use and/or integration of umodified components that have their own f the relevant referenced SDOCs are identified in section 8 and attached. This product's page 2 will indicate d by specific referenced components (product-id/stack-id).						
			•								
8	Additional Declarations / Attachments: (List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).										
		illellis. (List	1		illacrieu lesi	<u> </u>					
	Component Supplier		Product ID:	Stack ID:		Notes:					
[1]											
[2]											
[3]											
[4]											
9	Supplementary Attestations (Answer all).										
YES	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4.		This SDOC contains a capabilities test repo		All of the products listed in the product family in section 5 are implemented such that their						
			for each unique IPv6 stack in the product. It not, please document which stacks/ports ar		USGv6 capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the USGv6 capabilities of an identified member of this product family are provided in this SDOC. The SDOC attests to the fact that						
			not covered, and how their IPv6 capabilities								
			differ from those reported in this SDOC.			JSGv6 capabilities are identical and unmodified for all the products cited above.					
40											
10	Signature Darryll Ga	ason		Date							
	Print Name / Title Darryll Ga	dson. Lead l	JSGv6 Cisco Systems								

		ers Declaration of Conformity for USGv6 Pro		. Оприн	milios un	ia rest	Results Sullillary			GV6-v1 SDOC-v1.1 Pag			
roduct ld	l:		Cisco SG300						1.1				
			Context /	Suppo	rted Capa	bilities		USGv6 Testing					
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #, c			
Reference		USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interopoperability	Component Ref			
P500-267	6.1	IPv6 Basic Requirements											
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	Р			Basic_v1.*_C	UNH/IOL - 9361	Basic_V1.*_I	UNH/IOL - 9362			
		support of stateless address auto-configuration	SLAAC	Р			SLAAC-V1.*_C	UNH/IOL - 9363	SLAAC-V1.0_I	UNH/IOL - 9364			
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test				
		support of stateful (DHCP) address auto-configuration	DHCP-Client				Self Test		DHCP_Client_v1.*_I				
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test				
		support of neighbor discovery security extensions	SEND				Self Test		Self Test				
SP500-267	6.6	Addressing Requirements											
		support of addressing architecture reqts	Addr-Arch	Р			Addr_Arch_v1.*_C	UNH/IOL - 9656	Addr_Arch_v1.*_I	UNH/IOL - 9657			
		support of cryptographically generated addresses	CGA				Self Test		Self Test				
SP500-267	6.7	IP Security Requirements											
		support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I				
		support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2v1.0_I				
		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I				
SP500-267	6.11	Application Requirements											
		support of DNS client/resolver functions	DNS-Client				Self Test		Self Test				
		support of Socket application program interfaces	SOCK				Self Test		Self Test				
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test				
		support of a DNS server application	DNS-Server				Self Test		Self Test				
		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I				
SP500-267	6.2	Routing Protocol Requirements	10111				0 11 = 1						
		support of the intra-domain (interior) routing protocols	IGW				Self Test		OSPFv3_v1.*_I				
DE00 007	0.4	support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP_v1.*_I				
P500-267	6.4	Transition Mechanism Requirements support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test				
		support of funneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test				
SP500-267	6.0	Network Management Requirements	OPE				Sell Test						
SP300-267	6.8		SNMP				Call Tast		Self Test Self Test				
SP500-267	6.9	support of network management services  Multicast Requirements	SINIVIP				Self Test		Sell Test				
3F 300-201	0.9	support of basic multicast	Mcast				Self Test						
		full support of multicast communications	SSM				Self Test		Self Test				
SP500-267	6.10	Mobility Requirements	COM				OCH TOSE		Gen Test				
J. 000 <u>L</u> 0.	0.10	support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO				Self Test		Self Test				
SP500-267	6.3	Quality of Service Requirements					00						
		support of Differentiated Services capabilities	DS				Self Test		Self Test				
		PHB Id					Self Test						
SP500-267	6.12	Network Protection Device Requirements					00						
000 201	0.12	support of common NPD regts	NPD				N1 N2 N3 N4						
		support of basic firewall capabilities	FW				N1 FW						
		support of application firewall capabilities	APFW				N2 App FW						
	1	support of intrusion detection capabilities	IDS				N3 IDS						
		support of intrusion protection capabilities	IPS				N4 IPS						
SP500-267	6.5	Link Specific Technologies											
		support of robust packet compression services	ROHC				Self Test		Self Test				
		support of link technology [O:1]	Link=Ethernet	Р			Self Test	Self Declaration	Self Test	Self Declaration			
		, , , , , , , , , , , , , , , , , , ,											
		(repeat as needed) support of link technology	Link=										
12	Х	< Check HERE if this stack's DOC includes a		motion	about to	stad aa	nabilities and antic	no on an attached nage 2 of no	too				
12	^	Check HERE II this stack's DOC includes a	idditional inior	mation	about tes	sieu ca	pabilities and option	ns on an attached page 3 of no	ies.				
	_						1						
Level	Level of	support for USGv6-v1 Requirements for capability.			Color								
	Blank - S	SDOC makes no declaration for this capability.				Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.							
Р	Passed	required tests of USGv6-V1 requirements for these capab			Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.								
N		es page for details on the level of support of USGv6-v1 rec	,		Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.								
X		6 capability not supported in product.					Translation depositing trial to fort optional 7 conditional by the reconfinitedations of the GOOVG-V1 1 folial.						
	100000	заравну посвирронов на рговиос.											
				161 11									
Test Suite - Specific USGv6 Test suite used for test. See: http://www.antd.nist.gov/usgv6/test-specifications.html  Test Lab / Result ID - Abbreviation of accredited laboratory and its local identifier for this test result.							Note # - reference to a detailed note about this capability or result on attached page  Component Ref - Supplier / Product / Stack ID of distinctly tested component that provides this capability.						

	Product Id:		nformity for USGv6 Products: Notes Page				v6-v1 SDOC-v1.1 Page				
			USGv6-v1 Profile Requirements	Context / Configuration Option	Stack Id: Supported Capabilities				Notes about USGv6-v1 Capabilities.		
Note #	Spec / Reference	Section				Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interopoperability	Test Lab / Result ID, Note
1											
iscussio	1:										<b>.</b>
2											
iscussio	1:										
3											
iscussio	1:										
4											
scussio	1:										
5											
iscussio	1:										
		ion about	this Product / Stack's capabilities:		•	•					

**General**: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usqv6/testing.html. Contact: usqv6-project@antd.nist.gov.

Field

## Field Description and Instructions

- 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completeable field.
- **2 Product Identifier**: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- 6 USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

## Description and Instructions

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

**Product Id/Stack Id**: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

**Test Suite Conformance and Interoperability** columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent **Test Lab and Result Id** column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

12 Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

**Options for Test Lab and Result Id**: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.