Suppliers Declaration of Conformity for USGv6 Products						USGv6-v1 SDOC-v1.10 Page 1				
1 The Document Requiring Conformity:							USGv6 Profile Version 1.0, July 2008.			
2	Product Identifier: Axis network devices									
3	Supplier's	Name, Ad	ddress and SDOC C	ontact Deta	ils					
5	Cukalevsk									
vangel.	cukalevski(@axis.com								
Dichory	d Andersso	_								
	andersson		1							
Grände										
223 69	Lund									
SWED	EN									
4	Product a	s Tested/E	Declared: Product Id	entifier, vers	ion/revision information,		configuratio	on tested.		
					P3227-					
					Firmware ver	rsion 10.8				
5	Product F	amily (oth	er products using sa	me IPv6 star	k(s) to which these resu	ilts are der	plared to an	pply). Check Product Family attestation below.		
								135-E, M1137, M1137-E, M3057-PLVE, M3057-PLVE Mk II,		
								13116-LVE, M3205-LVE, M3206-LVE, M4216-V, M4216-LV,		
M43	08-PLE, M7	104, P136	7, ExCam XF P1367	, F101-A XF	P1367, P1367-E, P136	8-E, P1375	5, P1375-E	, P1377, F101-A XF P1377, P1377-LE, P1378, P1378-LE,		
-	, -	- /	, - ,	,	,	-, -	, -	27-LVE, P3228-LV, P3228-LVE, P3245-V, P3245-VE, P3245-		
								5-LVE, P3715-PLVE, P3717-PLE, P3719-PLE, P3727-PLE,		
								4, P8815-2, Q1615 Mk III, Q1615-LE Mk III, Q1645, Q1645-		
								85, F101-A XF Q1785, XP40-Q1785, Q1785-LE, Q1786-LE,		
								VE, Q3527-LVE, Q3819-PVE, Q6010-E, Q6074, Q6074-E, Q6135-LE, Q6215-LE, Q6315-LE, Q8752-E, Q9216-SLV,		
	II 5, EXCall		75, Q0075-E, D201-		S3008, V592	-	Q0100-E, V	Q0133-LE, Q0213-LE, Q0313-LE, Q0732-E, Q9210-3EV,		
6	USGv6 Ca	pability s	ummary. (For each	distinct IPv6			nmary of its	USGv6 capabilities below and include a detailed test result		
	summary)	e.g. exar	nple-prod-id/stack-1:		Host: IPv6-Base+Addr-A					
				USGv6-v1-	Host: IPv6-Base+Addr	-Arch+SL	AAC+Link=	Ethernet		
7	Self Conta	ained or C	omposite SDOC? (Must indicate	e one).					
YES			capabilities of this product					provided by the use and/or integration of umodified components that have		
	are addresse SDOC.	d by orginal te	est results reported in this		· ·			erenced SDOCs are identified in section 8 and attached. This product's		
	3000.				page 2 will indicate which ca	papilities are j	orovided by sp	ecific referenced components (product-id/stack-id).		
8	Additiona	l Declarati	ons / Attachments:	(List supplie	er & product-id/stack-id f	or referenc	ed and atta	ached test results in the case of composite products).		
	Compone	nt Supplie	r	Product I	D:	Stack ID:		Notes:		
[1]										
[2]										
[3]										
[4]										
9	9 Supplementary Attestations (Answer all).									
	Yes		is fully functional in dual s			Yes		is fully functional in IPv6 only environments. That is, no claimed capabilities		
		environment.		t is operated in	a dual stack (6 and 4)network		are invalidate lpv4.	ed if this product is deployed in a network environment that does not support		
	Yes				Yes		ducts listed in the product family in section 5 are implemented such that			
		product. If not, the stacks/ports not covered are documented, and how their Ipv6 capabilities differ from those reported are explained.					capabilities are identical in form and function across the entire product			
		capabilities d	miler from those reported a	re explainea.			-	specific conformance and interoperability test results for the USGv6 of an identified member of this product family are provided in this SDOC. The		
SDOC attests that these tested USGv6 capabilitiesare iden							ts that these tested USGv6 capabilitiesare identical and unmodified for all			
40	Ciana - ta c						the products			
10	Signature		augel (Date	2022-02-09			
	Print Name	/ Title	Vangel Cukalevski	Engineering	g Manager					
See instr	uctions for field	ts 1-12 on Po								
Jee mal		10 1-12 UIIFa	90 A.							

-		iers Declaration of Conformity for USGv6			T				
Product Id:		Axis network devices Stack I							10.8
			Context /	Suppo	rted Capa	abilities		USGv6 Testing F	Program Results
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite
Reference			Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperabil
P500-267	6.1	IPv6 Basic Requirements							
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	P			Basic_v1.*_C	UNH-IOL/34610	Basic_V1.*
		support of PMTU Discovery Protocol requirements	PMTU	P			Basic_v1.*_C	UNH-IOL/34610	Basic_V1.*
		support of stateless address auto-configuration	SLAAC	P			SLAAC-V1.*_C	UNH-IOL/34610	SLAAC-V1.
		support of Creation of Global Addresses	SLAAC - c(M)	Р			SLAAC-V1.*_C	UNH-IOL/34610	SLAAC-V1.
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test
		support of stateful (DHCP) address auto-	DHCP-Client DHCP-Prefix				DHCP_Client_v1.*_C		DHCP_Client_ Self Test
		support of automated router prefix delegation	SEND				Self Test Self Test		Self Test
P500-267	6.6	support of neighbor discovery security extensions Addressing Requirements	SEND				Sen rest		3611 1631
-500-207	0.0	support of addressing architecture regts	Addr-Arch	Р			Addr_Arch_v1.*_C	UNH-IOL/34612	Addr_Arch_v
		support of addressing architecture requisions support of cryptographically generated addresses	CGA	F			Self Test	0101-101/34012	Self Test
P500-267	6.7	IP Security Requirements	UGA				Sen Test		3611 1631
300-207	0.7	support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1
		support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2 v2.*
		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*
2500-267	6.11	Application Requirements	LOF				E3FV3_V1C		
-500-207	0.11	support of DNS client/resolver functions	DNS-Client				Self Test		Self Test
		support of Socket application program interfaces	SOCK				Self Test		Self Test
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test
		support of a DNS server application	DNS-Server				Self Test		Self Test
		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_
P500-267	6.2	Routing Protocol Requirements	DITCF-Server				Sen Test		DHCP_Serv_V
-300-207	0.2	support of the intra-domain (interior) routing	IGW				Self Test		OSPFv3_v1
		support for inter-domain (exterior) routing protocols	EGW		-		Self Test		BGP_v1.*
P500-267	6.4	Transition Mechanism Requirements	EGW				Sen Test		BGF_VI.
-300-207	0.4	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test
P500-267	6.8	Network Management Requirements	UFE				36// 163/		Self Test
-500-207	0.0	support of network management services	SNMP				Self Test		Self Test
P500-267	6.9	Multicast Requirements	ONIM				Sen Test		Och rest
500-201	0.5	support of basic multicast	Mcast				Self Test		
		full support of multicast communications	SSM				Self Test		Self Test
P500-267	6.10	Mobility Requirements	00101						00111031
000-201	0.10	support of mobile IP capability.	MIP				Self Test		Self Test
		support of mobile network capabilities	NEMO				Self Test		Self Test
P500-267	6.3	Quality of Service Requirements	NEMIO						00111031
500-201	0.0	support of Differentiated Services capabilities	DS				Self Test		Self Test
P500-267	6.12	Network Protection Device Requirements	00						00111031
500-201	0.12	support of common NPD regts	NPD				N1 N2 N3 N4_v1.3		
		support of basic firewall capabilities	FW				N1_FW_v1.3		
		support of application firewall capabilities	APFW				Self Test		
		support of application mewall capabilities	IDS				N3_IDS_v1.3		
		support of intrusion protection capabilities	IPS				N4_IPS_v1.3		
P500-267	6.5	Link Specific Technologies	11 0				N4_IF3_V1.3		
500-201	0.5	support of robust packet compression services	ROHC				Self Test		Self Test
		support of link technology [O:1]		Р			Self Test	Self Declaration	Self Test
		support of link technology [0.1]					Gen rest		- Oeii Test
		(repeat as needed) support of link technology	l ink=						
							1		
12		< Check HERE if this stack's DOC include	es additional i	nforma	tion abo	out test	ed capabilities and o	ptions on an attached page :	3 of notes.
Level	l evel o	f support for USGv6-v1 Requirements for capabili	ity			Color	Indicatio	on of USGv6-v1 Recommended Le	vel of Support fo
		SDOC makes no declaration for this capability.				00101		recommendend as mandatory (unc	
			anabilition				,		
-	Passed required tests of USGv6-V1 requirements for these capabilities. See notes page for details on the level of support of USGv6-v1 reequirements for this capability.						unusal for a given device type / stat		
			r reequirements	tor this ca	apability.	 	indicates capability that is	left optional / ocnditional by the reco	ommedations of th
	USGV6	capability not supported in product.							
Х									
							1		
st Suite - :		USGv6 Test suite used for test. See: http://www.anto - Abbreviation of accredited laboratory and its local ic			fications.h	ntml		Note # - reference to a - Supplier / Product / Stack ID of dis	

USO	6v6-v1 SDOC-v1.10 Page 2							
\$								
ite	Test Lab / Result ID, Note #, or							
bility	Component Ref							
.*_I	UNH-IOL/34611							
l.*_I 1.* I	UNH-IOL/34611							
1.*_I 1.* I	UNH-IOL/34611 UNH-IOL/34611							
11 st	01011-102/34011							
s. t_v1.*_l								
st								
st								
_v1.*_I	UNH-IOL/34613							
st –								
′ 1.*_ I								
2.*_I								
*_								
st								
st								
st								
st								
_v1.*_l								
4 4 1								
/1.*_I * I								
.*_I								
st								
st								
st								
st								
st								
st								
st								
st								
ot								
st st	Self Declaration							
รเ								
or device	type / stack role.							
	SGv6-v1 Profile.							
	select without careful analysis.							
he USGv6-v1 Profile.								
out this capability or result on attached page.								
	ponent that provides this capability.							
pononi inai provideo inio capability.								

Suppliers Declaration of Conformity for USGv6 Products: Notes Page and Detailed Test Results Summary USGv6-v1 SDOC-v									-v1 SDOC-v1.10 Page 3		
Field Product Id:				Stack Id:							
13				Context /	Suppo	orted Capabilities			Notes about USG		
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interoperability	Test Lab / Result ID, Note
									,		,
1											
Discussio	1:				1	1					
2											
Discussio	1:										
3											
Discussion					1	1					
4											
	ı.		1	1	1	1		1			
5											
Discussion	.			I	1						
6											
				I							
Discussion	<u>ı.</u>										
Discussion			I								
8											
Discussion					I						
9											
Discussion	1:			1							
10											
Discussion	1:										
Vendor's (General Notes	/ Discussi	on about this Product / Stack's capabilities:								

Suppliers Declaration of Conformity for USGv6 Description and Instructions

USGv6-v1 SDOC-v1.10 Page 4

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field	Description and Instructions	Field	Description and Instructions
1	The Document Requiring Conformity : Identifies the profile version implemented. Not a user completable field.	11	Summary of Results : The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.
2	Product Identifier: Supplier's concise name for the product declared.		Product Id/Stack Id : The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.
3	Suppliers Name, Address and Contact Details : Company name and point of contact for SDOC questions, street address, phone and email.		Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.
4	Product as Tested/Declared : Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).		Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.
5	Product Family : A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.		The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.
6	USGv6 Capability Summary : The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).		Cells marked Self Test have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.
7	Self Contained or Composite SDOC : If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.	12	Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary. Headings and Special Notations: as described.
8	Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.		Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.
9	Supplementary Attestations : Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.	13	Stack-1 Notes Instructions : The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.
10	Signature Block : Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.		Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will

Further Description: http://www.antd.nist.gov/usgv6/testing.html, and NIST SP 500-267 USGv6 Testing Program Users Guide available at the website.

be disclosed to the buyer.