Supplie			nformity for USGv	6 Products			USGv6-v1 SDOC-v1.10 Page 1						
1	The Docu	ment Requ	uiring Conformity:				USGv6 Profile Version 1.0, July 2008. (NIST SP500-267						
		Product Identifier: Dell PowerVault ME5 Supplier's Name, Address and SDOC Contact Details											
		Name, Ac	Idress and SDOC (Contact Detai	ls								
	chnologies Vay Round	Rock TX 7	8682										
Bob Da	-	TOOK 17. 7	0002										
		.com / 512	-723-6193"□										
4	Product a	s Tested/D	Declared: Product Id	<u>dentifier, versi</u>	on/revision information, o		onfiguration	tested.					
					ME5.1.0	0.0.0							
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.												
	product raining totales products using same involstack(s) to which these results are declared to apply). Check Product Failing attestation below.												
					MEEO42 MEEO	24 MEE00	.4						
	ME5012, ME5024, ME5084												
		-	- `		•			JSGv6 capabilities below and include a detailed test result					
	summary).	e.g. exan	nple-prod-id/stack-1		ost: IPv6-Base+Addr-Ar								
					-Host: IPv6-Base+Add								
				[2] 036	/6-v1-Host: IPv6-Base+	Auur-Arci	ITLIIIK – EL	nemet					
7	Self Conta	ained or Co	omposite SDOC? (Must indicate	one)								
			capabilities of this produc	•		nahilities of th	nis product are	provided by the use and/or integration of umodified components that have					
ES			est results reported in thi					erenced SDOCs are identified in section 8 and attached. This product's					
	SDOC.				page 2 will indicate which cap	pabilities are _l	provided by sp	ecific referenced components (product-id/stack-id).					
0	A d d : 4 : 0 : 0 = 0	l Declarati	ana / Attackmente	· // ist supplier	· O must sale to the sale and the	u uafauanaa	ad a sad a 44 a a						
8		Additional Declarations / Attachments: (List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).											
	Compone	nt Supplie	r	Product I	D:	Stack ID:		Notes:					
[1]		Dell Tec	nnologies	Dell	PowerVault ME5	ME5.	1.0.0.0	Ethernet management interface					
[2]		Dell Tecl	nnologies	Dell	Dell PowerVault ME5		1000	iSCSI 25Gb optical interface and iSCSI 10GBaseT, R.					
	Dell Technologies			Dell	1 Owel vadit in E5	ME5.1.0.0.0		copper interface					
[3]													
[4]													
9	Suppleme	ntary Atte	stations (Answer all).									
			is fully functional in dual		·			is fully functional in IPv6 only environments. That is, no claimed capabilities					
	YES			uct is operated in	a dual stack (6 and 4)network	YES		ed if this product is deployed in a network environment that does not support					
		environment.		s test report for each unique IPv6 stack in the			Ipv4. All of the products listed in the product family in section 5 are implemented such that						
					ented, and how their lpv6		All of the products listed in the product family in section 5 are implemented such that their USGv6 capabilities are identical in form and function across the entire product						
		YES capabilities differ from those reported are			,	YES	family. The s	pecific conformance and interoperability test results for the USGv6					
	123					123		of an identified member of this product family are provided in this SDOC.					
								attests that these tested USGv6 capabilitiesare identical and unmodified for cts cited above.					
10	Signature	1	Robert Dawson	,		Date	2/11/20						
					Date								
	Print Name	/ Title	Robert Dawson / S	Software Seni	vare Senior Principal Engineer								
See instr	uctions for field	ds 1-12 on Pa	ı ae 4										
1110111	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	10 1-12 UII Pa	g∪ 7.										

		ers Declaration of Conformity for USGv6						Ī	MEETOO			
Product Id:		Dell PowerVault ME5		Stack I				ME5.1.0.0.0				
			Context /	Suppo	rted Capa	abilities		USGv6 Testing Program Results				
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #		
eference		USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperability	Component Ref		
P500-267	6.1	IPv6 Basic Requirements										
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	P				UNH-IOL/34397	Basic_V1.*_I	UNH-IOL/34399		
		support of PMTU Discovery Protocol requirements	PMTU	Р				UNH-IOL/34397	Basic_V1.*_I	UNH-IOL/34399		
		support of stateless address auto-configuration	SLAAC	P				UNH-IOL/34397	SLAAC-V1.*_I	UNH-IOL/34399		
		support of Creation of Global Addresses	SLAAC - c(M)	Р			_	UNH-IOL/34397	SLAAC-V1.*_I	UNH-IOL/34399		
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test			
		support of stateful (DHCP) address auto-	DHCP-Client				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I			
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test	<u> </u>		
2500 007	0.0	support of neighbor discovery security extensions	SEND				Self Test		Self Test			
2500-267	6.6	Addressing Requirements	A -1 -1 - A 1-	P			Adda Anabard + O	LINII I IOI /24200	Addu Ande od * I	LINIL IOL /24400		
		support of addressing architecture reqts	Addr-Arch	Р			Addr_Arch_v1.*_C Self Test	UNH-IOL/34398	Addr_Arch_v1.*_I Self Test	UNH-IOL/34400		
2500 267	C 7	support of cryptographically generated addresses	CGA				Seir Test		Self Test			
2500-267	6.7	IP Security Requirements	IPsecv3				IDeeev2 v4 * C		IDeeev2 v4 * I			
		support for automated key management	IKEv2				IPsecv3_v1.*_C		IPsecv3_v1.*_I			
	<u> </u>	support for automated key management	ESP				IKEv2_v1.*_C ESPv3 v1.* C		IKEv2_v2.*_I			
2500-267	6.11	support for encapsulating security payloads in IP Application Requirements	ESP				ESPVS_VI."_C		ESP_v1.*_I			
300-207	0.11	support of DNS client/resolver functions	DNS-Client				Self Test		Self Test			
	+	support of DNS client/resolver functions support of Socket application program interfaces	SOCK	-			Self Test	 	Self Test	+		
		support of 30cket application program interfaces support of IPv6 uniform resource identifiers	URI				Self Test		Self Test	+		
		support of a DNS server application	DNS-Server				Self Test		Self Test	+		
		support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I			
2500-267	6.2	Routing Protocol Requirements	DITOT -OCIVCI				Gen Test		Diloi _ociv_vii			
300-201	0.2	support of the intra-domain (interior) routing	IGW				Self Test		OSPFv3_v1.*_I			
	1	support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP_v1.*_I	+		
2500-267	6.4	Transition Mechanism Requirements	LOW				Gen Test		DOI _VIII			
000 201	0.4	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test			
		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test			
2500-267	6.8	Network Management Requirements	0. 2						Self Test			
000 201	0.0	support of network management services	SNMP				Self Test		Self Test			
2500-267	6.9	Multicast Requirements										
		support of basic multicast	Mcast				Self Test					
		full support of multicast communications	SSM				Self Test		Self Test			
P500-267	6.10	Mobility Requirements										
		support of mobile IP capability.	MIP				Self Test		Self Test			
		support of mobile network capabilities	NEMO				Self Test		Self Test			
2500-267	6.3	Quality of Service Requirements										
		support of Differentiated Services capabilities	DS				Self Test		Self Test			
2500-267	6.12	Network Protection Device Requirements										
		support of common NPD reqts	NPD				N1 N2 N3 N4_v1.3					
		support of basic firewall capabilities	FW				N1_FW_v1.3					
		support of application firewall capabilities	APFW				Self Test					
		support of intrusion detection capabilities	IDS				N3_IDS_v1.3					
		support of intrusion protection capabilities	IPS				N4_IPS_v1.3					
P500-267	6.5	Link Specific Technologies										
		support of robust packet compression services	ROHC				Self Test		Self Test			
		support of link technology [O:1]	_ink=Ethernet	Р			Self Test	Self Declaration	Self Test	Self Declaration		
		(repeat as needed) support of link technology	_ink=									
12		< Check HERE if this stack's DOC include	s additional i	nformat	tion abo	out teste	ed capabilities and o	ptions on an attached page 3	3 of notes.			
	I											
	1	f support for USGv6-v1 Requirements for capabili		Color		n of USGv6-v1 Recommended Le						
	Blank - SDOC makes no declaration for this capability. Passed required tests of USGv6-V1 requirements for these capabilities.						Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile. Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.					
Р												
N		es page for details on the level of support of USGv6-v		for this ca	pabilitv.		Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.					
		capability not supported in product.	,.		The second of the country and the second of the country and th							
		. , 11 [
4 Ci4a	Specific	USGv6 Test suite used for test. See: http://www.anto	l.nist.gov/usav6/te	est-specif	ications h	tml		Note # - reference to a	detailed note about this ca	apability or result on attached p		
st 2011e -				2. 560011					azoat tino ot			

		ers Declaration of Conformity for USGv6			T i		. Jot Roodito Guillin			Gv6-v1 SDOC-v1.10 Pa			
Product Id:		Dell PowerVault ME5			Stack I	d:	ME5.1.0.0.0						
			Context / Supported Capabi					USGv6 Testing Program Results					
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note			
eference		USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interoperability	Component Ref			
2500-267	6.1	IPv6 Basic Requirements	IDv6 Daga	P			Pasia vd * C	UNH-IOL/34194	Decis V4 * I	LINIL IOI /24406			
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND) support of PMTU Discovery Protocol requirements	IPv6-Base PMTU	P			Basic_v1.*_C Basic_v1.*_C	UNH-IOL/34194	Basic_V1.*_I Basic_V1.*_I	UNH-IOL/34196 UNH-IOL/34196			
		support of stateless address auto-configuration	SLAAC	P			SLAAC-V1.* C	UNH-IOL/34194	SLAAC-V1.* I	UNH-IOL/34196			
		support of stateless address address addresses	SLAAC - c(M)	ŗ			SLAAC-V1C	0111-101/34194	SLAAC-V1I	ONTI-10L/34190			
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test				
		support of stateful (DHCP) address auto-	DHCP-Client				DHCP_Client_v1.*_C		DHCP_Client_v1.*_I				
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test				
		support of neighbor discovery security extensions	SEND				Self Test		Self Test				
500-267	6.6	Addressing Requirements											
		support of addressing architecture reqts	Addr-Arch	Р			Addr_Arch_v1.*_C	UNH-IOL/34195	Addr_Arch_v1.*_I	UNH-IOL/34197			
		support of cryptographically generated addresses	CGA				Self Test		Self Test				
500-267	6.7	IP Security Requirements											
		support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I				
		support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2_v2.*_I				
		support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I				
500-267	6.11	Application Requirements											
	ļ	support of DNS client/resolver functions	DNS-Client				Self Test		Self Test				
		support of Socket application program interfaces	SOCK				Self Test		Self Test				
		support of IPv6 uniform resource identifiers	URI				Self Test		Self Test				
		support of a DNS server application	DNS-Server				Self Test		Self Test				
E00 267	6.0	support of a DHCP server application	DHCP-Server				Self Test		DHCP_Serv_v1.*_I				
500-267	6.2	Routing Protocol Requirements	IGW				Self Test		OSPFv3_v1.*_I				
		support of the intra-domain (interior) routing support for inter-domain (exterior) routing protocols	EGW		-		Self Test		BGP_v1.*_I				
P500-267	6.4	Transition Mechanism Requirements	EGW				Sell Test		BGP_VII				
300-201	0.4	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test				
SP500-267		support of tunneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test				
	6.8	Network Management Requirements	<u> </u>						Self Test				
		support of network management services	SNMP				Self Test		Self Test				
2500-267	6.9	Multicast Requirements											
		support of basic multicast	Mcast				Self Test						
		full support of multicast communications	SSM				Self Test		Self Test				
500-267	6.10	Mobility Requirements											
		support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO				Self Test		Self Test				
500-267	6.3	Quality of Service Requirements											
		support of Differentiated Services capabilities	DS				Self Test		Self Test				
500-267	6.12	Network Protection Device Requirements	NDD										
		support of common NPD regts	NPD				N1 N2 N3 N4_v1.3						
		support of basic firewall capabilities	FW				N1_FW_v1.3						
		support of application firewall capabilities support of intrusion detection capabilities	APFW IDS				Self Test						
		support of intrusion detection capabilities support of intrusion protection capabilities	IPS				N3_IDS_v1.3 N4_IPS_v1.3		+	+			
500-267	6.5	Link Specific Technologies	IFO				N4_IF3_V1.3						
300-201	0.5	support of robust packet compression services	ROHC				Self Test		Self Test				
		support of link technology [O:1]		Р			Self Test	Self Declaration	Self Test	Self Declaration			
		(repeat as needed) support of link technology	Link=							1			
12		< Check HERE if this stack's DOC include		nformat	tion abo	ut teste	ed capabilities and o	ptions on an attached page	3 of notes.				
.evel	Level o	support for USGv6-v1 Requirements for capabili	tv			Color	Indication	n of USGv6-v1 Recommended Le	vel of Support for device	tyne / stack role			
		SDOC makes no declaration for this capability.	-7.				Indication of USGv6-v1 Recommended Level of Support for device type / stack role. Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.						
D		required tests of USGv6-V1 requirements for these ca	anahilitiaa				Indicates capability that is recommended as mandatory (unconditional MOST) in the OSGVo-VT Profile. Indicates capability that is unusal for a given device type / stack role. Do not select without careful analysis.						
		,		C Al. !			Indicates capability that is unusal for a given device type / stack role. Do not select without careful analysis. Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.						
N		es page for details on the level of support of USGv6-v	reequirements	ior this ca	apability.		indicates capability that is	।eπ optional / ocnditional by the rec	ommedations of the USG	/o-v1 Profile.			
X	JUSGV6	capability not supported in product.											
4.0. "	0	HOO O Test with me I feet to Continue	1 -1 -1			t1		N 4 " 2	4-4-9-4				
t Suite -		USGv6 Test suite used for test. See: http://www.anto- Abbreviation of accredited laboratory and its local id			ications.h	ımı	0 45.4	Note # - reference to a detailed note about this capability or result on attached pa Component Ref - Supplier / Product / Stack ID of distinctly tested component that provides this capability.					
	Duerilt ID	// NNTA//IGIAN AT GEORGALICA IGNATOTOR/ ANALITA IGNALIC	antitiar tar thia tar	דוו וספו זיי			[AMNANANI DAI		TINCTILL TACTOR COMPONENT				

Supplier	s Declaration	on of Con	formity for USGv6 Products: Notes Page	USGv6	-v1 SDOC-v1.10 Page 3						
Field	Product Id:					Stack I	d:				
13				Context /	Suppo	orted Cap	abilities		Notes about USG	v6-v1 Capabilities.	
Note #	Spec / Reference	Section	USGv6-v1 Profile Requirements	Configuration Option	Host	Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interoperability	Test Lab / Result ID, Note
									, , , , , , , , , , , , , , , , , , , ,		,
1				<u> </u>		<u> </u>					
Discussio	n:										
2											
Discussio	n:			T	1						
3											
Discussio	n:			T			<u> </u>	<u> </u>			
4											
Discussio	n:										
5											
Discussio	n:										
6											
Discussio	n:										
7											
Discussio	n:										
8											
Discussio	n:										
9											
Discussio	n:										
10											
Discussio											
Vendor's (General Notes	/ Discussion	on about this Product / Stack's capabilities:								

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usgv6/testing.html. Contact: usgv6-project@antd.nist.gov.

Field

Field Description and Instructions

- 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completable field.
- 2 Product Identifier: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- 5 Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- 6 USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- **Signature Block**: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Description and Instructions

11 Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent Test Lab and Result Id column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.

13 Stack-1 Notes Instructions: The supplier may choose to use the Notes (page 3) in order to clarify unsupported features or non passing results. Each Note # must reference the same Note # from Page 2.

Complete the Note by including the Spec/Reference and Section (i.e. RFC or USGv6 Profile version), USGv6-v1 Profile Requirements, Config Option (i.e. IPv6-Base), choosing Host/Router/NPD, and Test Selection table version along with Test Lab Result ID. The Discussion includes details about the test result that will be disclosed to the buyer.

Further Description: http://www.antd.nist.gov/usqv6/testing.html, and NIST SP 500-267 USGv6 Testing Program Users Guide available at the website.