	SUPP		INFORMATION SUPPLIER SIGNATURE					
SUPPL	IER NAME	Dell Technologies	DocuSigned by:	0 /12 /2022				
SUPPL	IER CONTACT EMAIL	George.Dilger@dell.com	George Dilger 294E1E303CF84F0	9/13/2023				
	ACCREDITED L	•	ACCREDITED LABORATORY SIGN	NATURE				
LABO	RATORY NAME	UNH InterOperability Laborator	DocuSigned by:	0 /12 /2022				
LABOI	RATORY CONTACT EMAIL	usgv6-sdoc@iol.unh.edu		9/13/2023				
	[2] PRODUCT VE		[3] PRODUCT ID					
	1.2	.0.0	PowerVault M	E5				
		[4] PRODI	JCT FAMILY					
	APPLICABLE SER	RIES HARDWARE	APPLICABLE SERIES SOFTW	ARE				
ME50	012, ME5024, ME50		1.2.0.0					
			COMPOSITE SDOC					
	i itary : All of the declared ca ssed by original test results	apabilities of this product are reported in this SDoC.	are provided by the use and/or integration of ur components that have their own unique SDoCs relevant referenced SDoCs are identified in seclinked.	modified . All of the				
[6] REF	SUPPLIER	PRODUCT ID/STACK ID	CAPABILITY SUMMARY	COMPOSITE SDOC LINK				
i.	Dell Technologies	PowerVault ME5/1.2.0.0	JSGv6-r1:Host+Core+SLAAC+Addr-Arch+Link=Etherne	t				
		[7] USGV6-CAPAB	LE REQUIREMENTS					
U:	SGv6-r1-Capable-Host	USGv6-r1-Capable-Router	USGv6-r1-Capable-SwitchUSGv6-r1-Ca	apable-NPP				
	NIOT OF TOO STEEL STEEL) REFERENCED					
i.	NIST SP 500-267Br1, U	SGv6 Profile						
ii.		[9] SUPPLEMENTA	ARY ATTESTATIONS					
X This product is fully functional in dual stack environments. That is, no claimed capabilities are invalidated if this product is operated in a dual stack (IPv6 and IPv4) network environment. This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is operated in a dual stack (IPv6 and IPv4) network environment.								
unique covere	operated in a dual stack (IPv6 and IPv4) network environment. X This SDoC contains a capabilities test report for each unique IPv6 stack in the product. If not, the stacks/ports not covered are documented, and how their IPv6 capabilities differ from those reported are explained. X All of the products listed in the product family implemented such that their capabilities are ident function across the entire product family. The specific conformance and interoperability test results for to fan identified member of this product family are SDoC. The SDoC attests that these tested capabilities are ident function across the entire product family are specified member of this product family are							

Host Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
	Powe	erVault ME5/1	.2.0.0		USGv6-	r1:Host+Core+SLAAC+Addr-Arch+Link=Ethernet	
[11]	CAPABILITY	CONFORMANCE		INTEROPERABIL	ITY/FUNCTIONAL	NOTES	
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID		
-	IPv6-ONLY	OLLEGIION		IPv6- ONLY_R1v1.*_F			
PASS	Core	Core_R1v1.*_C	UNH-IOL/36601	Core_R1v1.*_I	UNH-IOL/36603		
-	Extended-ICMP	Self-Test		Self-Test			
-	PLPMTUD	Self-Test		Self-Test			
-	ND-Ext	Self-Test		Self-Test			
-	ND-WL	Self-Test		Self-Test			
-	SEND	Self-Test		Self-Test			
PASS	SLAAC	SLAAC_R1v1.*_C	UNH-IOL/36601	SLAAC_R1v1.*_I	UNH-IOL/36603		
-	PriAddr	Self-Test		Self-Test			
-	DHCP- Stateless	DHCP- Stateless_R1v1 .*_C		DHCP- Stateless_R1v1 .*_I			
-	DHCP-Client	DHCP- Client_R1v1.*_C		DHCP- Client_R1v1.*_I			
-	DHCP-Client- Ext	Self-Test		Self-Test			
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I			
-	DHCP-Prefix- Ext	Self-Test		Self-Test			
-	6Lo	Self-Test		Self-Test			

Host Capabilities

-	Happy-Eyeballs	Self-Test		Self-Test	
PASS	Addr-Arch	Addr- Arch_R1v1.*_C	UNH-IOL/36602	Addr- Arch_R1v1.*_I	UNH-IOL/36604
-	CGA	Self-Test		Self-Test	
-	DNS-Client	Self-Test		Self-Test	
-	URI	Self-Test		Self-Test	
-	NTP-Client	Self-Test		Self-Test	
-	NTP-Server	Self-Test		Self-Test	
-	DNS-Server	Self-Test		Self-Test	
-	DHCP-Server	DHCP- Server_R1v1.*_C		DHCP- Server_R1v1.*_I	
-	DHCP-Server- Ext	Self-Test		Self-Test	
-	DHCP-Relay	DHCP- Relay_R1v1.*_C		DHCP- Relay_R1v1.*_I	
-	IPsec	IPsec_R1v1.*_C		IPsec_R1v1.*_I	
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C		IPsec-SHA- 512_R1v1.*_I	
-	SSHV2	Self-Test		Self-Test	
-	TLS	Self-Test		Self-Test	
-	TLS-1.3	Self-Test		Self-Test	
-	Tunneling-IP	Self-Test		Self-Test	

Host Capabilities

		Self-Test		Self-Test		
-	Tunneling-UDP					
-	XLAT	Self-Test		Self-Test		
-	NAT64	Self-Test		Self-Test		
-	DNS64	Self-Test		Self-Test		
-	SNMP	Self-Test		Self-Test		
-	Tunneling	Self-Test		Self-Test		
-	DiffServ	Self-Test		Self-Test		
-	NETCONF	Self-Test		Self-Test		
-	SSM	Self-Test		Self-Test		
-	Multicast	Multicast_R1v1 .*_C		Multicast_R1v1 .*_I		
-	ECN	Self-Test		Self-Test		
PASS	Link = Ethernet	Self-Test	Self Declaration	Self-Test	Self Declaration	

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY
[11] SUPPORTED		CONFOR TEST	MANCE RESULT ID	INTEROPERABIL TEST	TY/FUNCTIONAL RESULT ID	NOTES
CAPABILITY	CAPABILITY	SELECTION		SELECTION		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F		
-	Core	Core_R1v1.*_C		Core_R1v1.*_I		
-	Extended-ICMP	Self-Test		Self-Test		
-	PLPMTUD	Self-Test		Self-Test		
-	ND-Ext	Self-Test		Self-Test		
-	ND-WL	Self-Test		Self-Test		
-	SEND	Self-Test		Self-Test		
-	SLAAC	SLAAC_R1v1.*_C		SLAAC_R1v1.*_I		
-	PrivAddr	Self-Test		Self-Test		
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I		
-	DHCP-Prefix- Ext	Self-Test		Self-Test		
-	6Lo	Self-Test		Self-Test		
-	Addr-Arch	Addr- Arch_R1v1.*_C		Addr- Arch_R1v1.*_I		
-	CGA	Self-Test		Self-Test		

USGv6 Profile Supplier's Declaration of Conformity (SDoC) R1.1

DNS-Client	Self-Test	Self-Test	
URI	Self-Test	Self-Test	
NTP-Client	Self-Test	Self-Test	
NTP-Server	Self-Test	Self-Test	
DNS-Server	Self-Test	Self-Test	
DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_I	
DHCP-Server- Ext	Self-Test	Self-Test	
DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_I	
OSPF	Self-Test	OSPF_R1v1.*_I	
OSPF-IPsec	Self-Test	Self-Test	
OSPF-Auth	Self-Test	OSPF- Auth_R1v1.*_I	
OSPF-Ext	Self-Test	Self-Test	
OSPF-Trans	Self-Test	Self-Test	
OSPF-Graceful	Self-Test	Self-Test	
ISIS	Self-Test	Self-Test	
IS-IS-Auth	Self-Test	Self-Test	
IS-IS-Ext	Self-Test	Self-Test	
IS-IS-MT	Self-Test	Self-Test	
	URI NTP-Client NTP-Server DNS-Server DHCP-Server-Ext DHCP-Relay OSPF OSPF-IPsec OSPF-Auth OSPF-Trans OSPF-Graceful ISIS IS-IS-Auth IS-IS-Ext	DNS-Client URI Self-Test NTP-Client NTP-Server DNS-Server DHCP-Server DHCP-Server-Ext DHCP-Relay DHCP-Relay DHCP-Relay Cospf Cospf Cospf-IPsec Cospf-Auth Cospf-Ext Cospf-Test Cospf-	DNS-Client URI Self-Test Self-Test Self-Test NTP-Client NTP-Server Self-Test DNS-Server DHCP-Server DHCP-Server-R1v1.*_C DHCP-Server-R1v1.*_C DHCP-Relay DHCP-Relay DHCP-Relay CSPF-IPsec OSPF-Auth Self-Test OSPF-Auth Self-Test OSPF-Trans OSPF-Trans OSPF-Graceful Self-Test Self-Test

		Self-Test	BGP_R1v1.*_I	
-	BGP			
-	BGP-Reflect	Self-Test	Self-Test	
-	BGP-Graceful	Self-Test	Self-Test	
-	BGP-FlowSpec	Self-Test	Self-Test	
-	BGP-OV	Self-Test	Self-Test	
-	BGP-VPLS	Self-Test	Self-Test	
-	BGP-EVPN	Self-Test	Self-Test	
-	BGP-6VPE	Self-Test	Self-Test	
-	BGP-MVPN	Self-Test	Self-Test	
-	MPLS	Self-Test	Self-Test	
-	CE-Router	CE_Router_R1v 1.*_C	CE_Router_R1v 1.*_I	
-	VRRP	Self-Test	Self-Test	
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I	
-	IPsec-VPN	IPsec- VPN_R1v1.*_C	IPsec- VPN_R1v1.*_I	
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I	
-	IPsec-SHA-512- VPN	IPsec-SHA-512- VPN_R1v1.*_C	IPsec-SHA-512- VPN_R1v1.*_I	
-	SSHV2	Self-Test	Self-Test	
-	TLS	Self-Test	Self-Test	

USGv6 Profile Supplier's Declaration of Conformity (SDoC) R1.1

-	TLS-1.3	Self-Test	Self-Test		
-	Tunneling-IP	Self-Test	Self-Test		
-	Tunneling-UDP	Self-Test	Self-Test		
-	GRE	Self-Test	Self-Test		
-	DS-Lite	Self-Test	Self-Test		
-	LW4over6	Self-Test	Self-Test		
-	MAP-E	Self-Test	Self-Test		
-	MAP-T	Self-Test	Self-Test		
-	XLAT	Self-Test	Self-Test		
-	NAT64	Self-Test	Self-Test		
-	DNS64	Self-Test	Self-Test		
-	6PE	Self-Test	Self-Test		
-	LISP	Self-Test	Self-Test		
-	SNMP	Self-Test	Self-Test		
-	Tunneling	Self-Test	Self-Test		
-	DiffServ	Self-Test	Self-Test		
-	NETCONF	Self-Test	Self-Test		
-	SSM	Self-Test	Self-Test		

NIST.SP.500-281Ar1s

-	PIM-SM	Self-Test	Self-Test	
-	PIM-SM-IPsec	Self-Test	Self-Test	
-	PIM-SM-BiDir	Self-Test	Self-Test	
_	Multicast	Multicast_R1v1.	Multicast_R1v1.	
	Widiticast	*_C	"_I	
-	ECN	Self-Test Self-Test	Self-Test Self-Test	

Application Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11] SUPPORTED CAPABILITY	CAPABILITY	CONFO	RMANCE RESULT ID	INTEROPERABIL TEST SELECTION	ITY/FUNCTIONAL RESULT ID	NOTES	
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	App-Serv=			APP- ONLY_R1v1.*_F			
-	Link =			Self-Test			

NPP Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFOR		INTEROPERABILI		NOTES	
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	FW	FW_R1v1.*_C					
-	APFW	Self-Test					
-	IDS	FW_R1v1.*_C					
-	IPS	FW_R1v1.*_C					
-	Link =	Self-Test					

Switch Capabilities

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFOR	MANCE	INTEROPERABILI7				
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	NOTES		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F				
-	DHCPv6-Guard	Self-Test		Self-Test				
-	RA-Guard	Self-Test		Self-Test				
-	MLD-Snooping	Self-Test		Self-Test				
-	Link =	Self-Test		Self-Test				

1	CONTACT INFORMATION	Supplier name, email and signature (digital recommended). Include printed name and date if wet ink signed. Accredited laboratory name, email and signature (digital recommended). Include printed name and date if wet ink signed
2	PRODUCT VERSION TESTED	Firmware/ software version of product declared
3	PRODUCT ID	Suppliers concise name for product declared
4	PRODUCT FAMILY	Applicable hardware or software with an unmodified IPv6 stack from "PRODUCT VERSION TESTED"
5	UNITARY OR COMPOSITE	Indicate if this is a unitary or composite SDoC. If composite is checked, composite SDoC must be linked in section 6.
6	REF	Reference number to profile(s) reference in this SDoC
	SUPPLIER	Supplier name
	PRODUCT ID/STACK ID	Product ID must match field 3. As there may be more than one unique IPv6 stack, stack ID identifies particular stack described in CAPABILITY SUMMARY. Each unique stack requires a CAPABILTY SUMMARY.
	CAPABILITY SUMMARY	The strong notation as described in NIST-SP-500-267Ar1 that describes the product capabilities of the given stack.
	COMPOSITE SDOC LINK	URL link to composite SDoC referenced.
7	USGV6-CAPABLE REQUIREMENTS	Refer to section 5 in NIST-SP-500-267Br1 for CSS strings referenced in this section. Check the appropriate box if the product meets the requirements.
8	PROFILE(S) REFERENCED	Profile(s) referenced in the SDoC.
9	SUPPLEMENTARY ATTESTATIONS	Attestations made by the supplier. Check all that apply.
10	PRODUCT ID/STACK ID	PRODUCT ID/STACK ID for stack documented on given page.
	CAPABILITY SUMMARY	CAPABILITY SUMMARY for stack documented on given page.
11	SUPPORTED CAPABILITY	"PASS" – All requirements of the capability have been met
		"NOTES" – See notes for details regarding the level of support for this capability
		"X" – Capability not supported
		BLANK – No declaration for this capability
	CAPABILITY	IPv6 Capability as described in NIST-SP-500-267Ar1.
	TEST SELECTION	Test Selection Tables version of capabilities with existing test programs. Capabilities without an existing test program are
		indicated with "Self-Test"
	RESULT ID	Abbreviation of accredited laboratory and unique identifier of test result. Capabilities with "Self-Test" can be self-declared
		writing "Self Declaration" in the cell.
	NOTES	The cell must be filled out if "NOTE" is indicated for SUPPORTED CAPABILITY. Suppliers may use notes to clarify
		unsupported features or non-passing results.

SUPPLIER GENERAL NOTES