	01100		INFORMATION CLUBBLIEB CLOUATURE	
CUDDI	SUPP LIER NAME		SUPPLIER SIGNATURE	
		Dell Technologies	Carrae Dilaur	9/22/2023
SUPPL	LIER CONTACT EMAIL	George.Dilger@dell.com		IATUDE
LADO	ACCREDITED L		ACCREDITED LABORATORY SIGN	IATURE
	RATORY NAME	UNH InterOperability Laboratory	Michaula Newcounter	9/22/2023
LABOR	RATORY CONTACT EMAIL	usgv6-sdoc@iol.unh.edu		
	[2] PRODUCT VE		[3] PRODUCT ID	
	19.	7.0	Avamar	
		[4] PRODL	JCT FAMILY	
	APPLICABLE SER	RIES HARDWARE	APPLICABLE SERIES SOFTWA	ARE
Gen4	1T, Gen5A		19.7.x	
			COMPOSITE SDOC	
	litary : All of the declared ca ssed by original test results	apabilities of this product are reported in this SDoC.	Composite: Some or all of the capabilities of are provided by the use and/or integration of un components that have their own unique SDoCs relevant referenced SDoCs are identified in sec linked.	modified . All of the
[6] REF	SUPPLIER	PRODUCT ID/STACK ID	CAPABILITY SUMMARY	COMPOSITE SDOC LINK
i.	Dell Technologies	Avamar/19.7.0	JSGv6-r1:Host+Core+SLAAC+Addr-Arch+Link=Ethernet	i
		[7] USGV6-CAPAB	LE REQUIREMENTS	
	SGv6-r1-Capable-Host	USGv6-r1-Capable-Router	USGv6-r1-Capable-Switch USGv6-r1-Ca	pable-NPP
	NIOT OF FOR COTT) REFERENCED	
i. ii.	NIST SP 500-267Br1, U	ISGV6 Profile		
11.		[9] SUPPLEMENTA	ARY ATTESTATIONS	
That is operat	s, no claimed capabilities a ted in a dual stack (IPv6 an	Il in dual stack environments. re invalidated if this product is d IPv4) network environment.	This product is fully functional in IPv6 only entry is, no claimed capabilities are invalidated if deployed in a network environment that does no	this product is t support IPv4.
unique covere	nis SDoC contains a capable IPv6 stack in the product. ed are documented, and ho hose reported are explained	If not, the stacks/ports not w their IPv6 capabilities differ	X All of the products listed in the product family implemented such that their capabilities are iden function across the entire product family. The sp conformance and interoperability test results for of an identified member of this product family are SDoC. The SDoC attests that these tested capal identical and unmodified for all the products cited	tical in form and ecific the capabilities e provided in this bilities are

Host Capabilities

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY
	,	Avamar/19.7.0)		USGv6-	r1:Host+Core+SLAAC+Addr-Arch+Link=Ethernet
[11]	CAPABILITY	CONFORMANCE		INTEROPERABILITY/FUNCTION/		NOTES
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	
-	IPv6-ONLY	SELECTION		IPv6- ONLY_R1v1.*_F		
PASS	Core	Core_R1v1.*_C	UNH-IOL/36718	Core_R1v1.*_I	UNH-IOL/36720	
-	Extended-ICMP	Self-Test		Self-Test		
-	PLPMTUD	Self-Test		Self-Test		
-	ND-Ext	Self-Test		Self-Test		
-	ND-WL	Self-Test		Self-Test		
-	SEND	Self-Test		Self-Test		
PASS	SLAAC	SLAAC_R1v1.*_C	UNH-IOL/36718	SLAAC_R1v1.*_I	UNH-IOL/36720	
-	PriAddr	Self-Test		Self-Test		
-	DHCP- Stateless	DHCP- Stateless_R1v1 .*_C		DHCP- Stateless_R1v1 .*_I		
-	DHCP-Client	DHCP- Client_R1v1.*_C		DHCP- Client_R1v1.*_I		
-	DHCP-Client- Ext	Self-Test		Self-Test		
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I		
-	DHCP-Prefix- Ext	Self-Test		Self-Test		
-	6Lo	Self-Test		Self-Test		

Host Capabilities

-	Happy-Eyeballs	Self-Test		Self-Test		
	Addr-Arch	Addr- Arch_R1v1.*_C	UNH-IOL/36719	Addr- Arch_R1v1.*_I	UNH-IOL/36721	
-	CGA	Self-Test		Self-Test		
-	DNS-Client	Self-Test		Self-Test		
-	URI	Self-Test		Self-Test		
-	NTP-Client	Self-Test		Self-Test		
-	NTP-Server	Self-Test		Self-Test		
-	DNS-Server	Self-Test		Self-Test		
-	DHCP-Server	DHCP- Server_R1v1.*_C		DHCP- Server_R1v1.*_I		
	DHCP-Server- Ext	Self-Test		Self-Test		
-	DHCP-Relay	DHCP- Relay_R1v1.*_C		DHCP- Relay_R1v1.*_I		
-	IPsec	IPsec_R1v1.*_C		IPsec_R1v1.*_I		
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C		IPsec-SHA- 512_R1v1.*_I		
-	SSHV2	Self-Test		Self-Test		
-	TLS	Self-Test		Self-Test		
-	TLS-1.3	Self-Test		Self-Test		
-	Tunneling-IP	Self-Test		Self-Test		

Host Capabilities

-	Tunneling-UDP	Self-Test		Self-Test		
-	XLAT	Self-Test		Self-Test		
-	NAT64	Self-Test		Self-Test		
-	DNS64	Self-Test		Self-Test		
-	SNMP	Self-Test		Self-Test		
-	Tunneling	Self-Test		Self-Test		
-	DiffServ	Self-Test		Self-Test		
-	NETCONF	Self-Test		Self-Test		
-	SSM	Self-Test		Self-Test		
-	Multicast	Multicast_R1v1 .*_C		Multicast_R1v1 .*_I		
-	ECN	Self-Test		Self-Test		
PASS	Link = Ethernet	Self-Test	Self Declaration	Self-Test	Self Declaration	

Router Capabilities

[10] PRODUCT ID/ STACK ID **CAPABILITY SUMMARY** NOTES [11] SUPPORTED CONFORMANCE INTEROPERABILITY/FUNCTIONAL TEST **RESULT ID** TEST RESULT ID **CAPABILITY** CAPABILITY **SELECTION** SELECTION IPv6-**IPv6-ONLY** ONLY R1v1.* F Core_R1v1.*_C Core_R1v1.*_I Core Self-Test Self-Test Extended-ICMP Self-Test Self-Test PLPMTUD Self-Test Self-Test ND-Ext Self-Test Self-Test ND-WL Self-Test Self-Test **SEND** SLAAC_R1v1.*_C SLAAC_R1v1.*_I SLAAC Self-Test Self-Test PrivAddr DHCP-DHCP-**DHCP-Prefix** Prefix_R1v1.*_C Prefix_R1v1.*_I Self-Test Self-Test **DHCP-Prefix-**Ext Self-Test Self-Test 6Lo Addr-Addr-Addr-Arch Arch R1v1.* C Arch R1v1.* I Self-Test Self-Test **CGA**

Router Capabilities

USGv6 Profile Supplier's Declaration of Conformity (SDoC) R1.1

-	DNS-Client	Self-Test	Self-Test	
-	URI	Self-Test	Self-Test	
-	NTP-Client	Self-Test	Self-Test	
-	NTP-Server	Self-Test	Self-Test	
-	DNS-Server	Self-Test	Self-Test	
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_I	
-	DHCP-Server- Ext	Self-Test	Self-Test	
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_I	
-	OSPF	Self-Test	OSPF_R1v1.*_I	
-	OSPF-IPsec	Self-Test	Self-Test	
-	OSPF-Auth	Self-Test	OSPF- Auth_R1v1.*_I	
-	OSPF-Ext	Self-Test	Self-Test	
-	OSPF-Trans	Self-Test	Self-Test	
-	OSPF-Graceful	Self-Test	Self-Test	
-	ISIS	Self-Test	Self-Test	
-	IS-IS-Auth	Self-Test	Self-Test	
-	IS-IS-Ext	Self-Test	Self-Test	
-	IS-IS-MT	Self-Test	Self-Test	

USGv6 Profile Supplier's Declaration of Conformity (SDoC) R1.1

		Self-Test	BGP_R1v1.*_I	T T		
-	BGP					
-	BGP-Reflect	Self-Test	Self-Test			
-	BGP-Graceful	Self-Test	Self-Test			
-	BGP-FlowSpec	Self-Test	Self-Test			
-	BGP-OV	Self-Test	Self-Test			
-	BGP-VPLS	Self-Test	Self-Test			
-	BGP-EVPN	Self-Test	Self-Test			
-	BGP-6VPE	Self-Test	Self-Test			
-	BGP-MVPN	Self-Test	Self-Test			
-	MPLS	Self-Test	Self-Test			
-	CE-Router	CE_Router_R1v 1.*_C	CE_Router_R1v 1.*_I			
-	VRRP	Self-Test	Self-Test			
-	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I			
-	IPsec-VPN	IPsec- VPN_R1v1.*_C	IPsec- VPN_R1v1.*_I			
-	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I			
-	IPsec-SHA-512- VPN	IPsec-SHA-512- VPN_R1v1.*_C	IPsec-SHA-512- VPN_R1v1.*_I			
-	SSHV2	Self-Test	Self-Test			
-	TLS	Self-Test	Self-Test			

USGv6 Profile Supplier's Declaration of Conformity (SDoC) R1.1

-	TLS-1.3	Self-Test	Self-Test	
-	Tunneling-IP	Self-Test	Self-Test	
-	Tunneling-UDP	Self-Test	Self-Test	
-	GRE	Self-Test	Self-Test	
-	DS-Lite	Self-Test	Self-Test	
-	LW4over6	Self-Test	Self-Test	
-	MAP-E	Self-Test	Self-Test	
-	МАР-Т	Self-Test	Self-Test	
-	XLAT	Self-Test	Self-Test	
-	NAT64	Self-Test	Self-Test	
-	DNS64	Self-Test	Self-Test	
-	6PE	Self-Test	Self-Test	
-	LISP	Self-Test	Self-Test	
-	SNMP	Self-Test	Self-Test	
-	Tunneling	Self-Test	Self-Test	
-	DiffServ	Self-Test	Self-Test	
-	NETCONF	Self-Test	Self-Test	
-	SSM	Self-Test	Self-Test	

USGv6 Profile Supplier's Declaration of Conformity (SDoC) R1.1

Router Capabilities

NIST.SP.500-281Ar1s

-	PIM-SM	Self-Test	Self-Test	
-	PIM-SM-IPsec	Self-Test	Self-Test	
-	PIM-SM-BiDir	Self-Test	Self-Test	
-	Multicast	Multicast_R1v1. *_C	Multicast_R1v1. *_I	
-	Multicast	Multicast_R1v1. *_C Self-Test		

Application Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFO	RMANCE	INTEROPERABI	LITY/FUNCTIONAL	NOTES	
SUPPORTED		TEST	RESULT ID	TEST	RESULT ID		
CAPABILITY		SELECTION		SELECTION			
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	App-Serv=			APP- ONLY_R1v1.*_F			
-	Link =			Self-Test			

NPP Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFORMANCE INTEROPERABIL			NOTES		
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	FW	FW_R1v1.*_C					
-	APFW	Self-Test					
-	IDS	FW_R1v1.*_C					
-	IPS	FW_R1v1.*_C					
-	Link =	Self-Test					

Switch Capabilities

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY
[11]	CAPABILITY	CONFOR	MANCE	INTEROPERABILITY	//FUNCTIONAL	
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	NOTES
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F		
-	DHCPv6-Guard	Self-Test		Self-Test		
-	RA-Guard	Self-Test		Self-Test		
-	MLD-Snooping	Self-Test		Self-Test		
-	Link =	Self-Test		Self-Test		

1	CONTACT INFORMATION	Supplier name, email and signature (digital recommended). Include printed name and date if wet ink signed. Accredited laboratory name, email and signature (digital recommended). Include printed name and date if wet ink signed.
2	PRODUCT VERSION TESTED	Firmware/ software version of product declared
3	PRODUCT ID	Suppliers concise name for product declared
4	PRODUCT FAMILY	Applicable hardware or software with an unmodified IPv6 stack from "PRODUCT VERSION TESTED"
5	UNITARY OR COMPOSITE	Indicate if this is a unitary or composite SDoC. If composite is checked, composite SDoC must be linked in section 6.
6	REF	Reference number to profile(s) reference in this SDoC
	SUPPLIER	Supplier name
	PRODUCT ID/STACK ID	Product ID must match field 3. As there may be more than one unique IPv6 stack, stack ID identifies particular stack described in CAPABILITY SUMMARY. Each unique stack requires a CAPABILTY SUMMARY.
	CAPABILITY SUMMARY	The strong notation as described in NIST-SP-500-267Ar1 that describes the product capabilities of the given stack.
	COMPOSITE SDOC LINK	URL link to composite SDoC referenced.
7	USGV6-CAPABLE REQUIREMENTS	Refer to section 5 in NIST-SP-500-267Br1 for CSS strings referenced in this section. Check the appropriate box if the product meets the requirements.
8	PROFILE(S) REFERENCED	Profile(s) referenced in the SDoC.
9	SUPPLEMENTARY ATTESTATIONS	Attestations made by the supplier. Check all that apply.
10	PRODUCT ID/STACK ID	PRODUCT ID/STACK ID for stack documented on given page.
	CAPABILITY SUMMARY	CAPABILITY SUMMARY for stack documented on given page.
11	SUPPORTED CAPABILITY	"PASS" – All requirements of the capability have been met "NOTES" – See notes for details regarding the level of support for this capability "X" – Capability not supported BLANK – No declaration for this capability
	CAPABILITY	IPv6 Capability as described in NIST-SP-500-267Ar1.
	TEST SELECTION	Test Selection Tables version of capabilities with existing test programs. Capabilities without an existing test program are indicated with "Self-Test"
	RESULT ID	Abbreviation of accredited laboratory and unique identifier of test result. Capabilities with "Self-Test" can be self-declared b writing "Self Declaration" in the cell.
	NOTES	The cell must be filled out if "NOTE" is indicated for SUPPORTED CAPABILITY. Suppliers may use notes to clarify unsupported features or non-passing results.

SUPPLIER GENERAL NOTES