	SUPP		INFORMATION SUPPLIER SIGNATURE					
SUPP	LIER NAME	Cisco Systems Inc.	DocuSigned by:					
SUPP	LIER CONTACT EMAIL	kweerakk@cisco.com	tanishka Weerakkody	10/19/2023				
	ACCREDITED L	ABORATORY	ACCREDITED LABORATORY SIG	NATURE				
LABO	RATORY NAME	UNH InterOperability Laborator		10/19/2023				
LABO	RATORY CONTACT EMAIL	usgv6-sdoc@iol.unh.ed	U Michayla Newcombe 	10/ 13/ 2023				
	[2] PRODUCT VE	RSION TESTED	[3] PRODUCT ID					
	IOS XE	17.12.1	C9130AXI					
	APPLICABLE SER		APPLICABLE SERIES SOFTW	ARE				
C9130 C9124 C9130	AXI, C9130AXE, C9130AXI- AXE-STA, C9124AXI, C9124 AXI-EWC, C9124AXE-EWC, AXI-EWC, C9136I, CW9166I 7I, IW9167E	AXE, C9124AXD,	IOS XE 17.12.1					
		[5] UNITARY OR	COMPOSITE SDOC					
	<b>hitary</b> : All of the declared ca ssed by original test results	apabilities of this product are reported in this SDoC.	<b>Composite:</b> Some or all of the capabilities are provided by the use and/or integration of un components that have their own unique SDoCs relevant referenced SDoCs are identified in sec linked.	nmodified a. All of the				
[6] REF	SUPPLIER	PRODUCT ID/STACK ID	CAPABILITY SUMMARY	COMPOSITE SDOC LINK				
i.	Cisco Systems Inc.	C9130AXI/IOS XE 17.12.1	USGv6-r1: Host+IPv6-Only+Core+SLAAC+Addr-Arch+Link=Etherne	et				
		[7] USGV6-CAPAE						
UU	SGv6-r1-Capable-Host	USGv6-r1-Capable-Router		apable-NPP				
i.	NIST SP 500-267Br1, U		6) REFERENCED					
ii.								
		[9] SUPPLEMENT	ARY ATTESTATIONS					
That i opera	s, no claimed capabilities a ted in a dual stack (IPv6 an	l in dual stack environments. re invalidated if this product is d IPv4) network environment.	That is, no claimed capabilities are invalidated in deployed in a network environment that does not a network envint environment that does not a network envit environment env	X This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4.				
unique cover	his SDoC contains a capab e IPv6 stack in the product. ed are documented, and ho hose reported are explained	If not, the stacks/ports not w their IPv6 capabilities differ	X All of the products listed in the product family in section 4 are implemented such that their capabilities are identical in form and function across the entire product family. The specific conformance and interoperability test results for the capabilities of an identified member of this product family are provided in this SDoC. The SDoC attests that these tested capabilities are identical and unmodified for all the products cited above.					

# Host Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY			
	C9130	AXI/IOS XE 1	7.12.1		USGv6-r1: Host+IPv6-Only+Core+SLAAC+Addr-Arch+Link=Ethernet			
[11]	CAPABILITY	CONFORMANCE		INTEROPERABIL	ITY/FUNCTIONAL	NOTES		
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID			
PASS	IPv6-ONLY			IPv6- ONLY_R1v1.*_F	UNH-IOL/37333			
PASS	Core	Core_R1v1.*_C	UNH-IOL/37329	Core_R1v1.*_I	UNH-IOL/37331			
-	Extended-ICMP	Self-Test		Self-Test				
-	PLPMTUD	Self-Test		Self-Test				
-	ND-Ext	Self-Test		Self-Test				
-	ND-WL	Self-Test		Self-Test				
-	SEND	Self-Test		Self-Test				
PASS	SLAAC	SLAAC_R1v1.*_C	UNH-IOL/37329	SLAAC_R1v1.*_I	UNH-IOL/37331			
-	PriAddr	Self-Test		Self-Test				
-	DHCP- Stateless	DHCP- Stateless_R1v1 _*_C		DHCP- Stateless_R1v1 .*_I				
-	DHCP-Client	DHCP- Client_R1v1.*_C		DHCP- Client_R1v1.*_I				
-	DHCP-Client- Ext	Self-Test		Self-Test				
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I				
-	DHCP-Prefix- Ext	Self-Test		Self-Test				
-	6Lo	Self-Test		Self-Test				

#### Host Capabilities

		Self-Test		Self-Test	
-	Happy-Eyeballs				
		Addr-		Addr-	
PASS	Addr-Arch	Arch_R1v1.*_C	UNH-IOL/37330		UNH-IOL/37332
		Self-Test		Self-Test	
-	CGA				
		Self-Test		Self-Test	
-	DNS-Client				
_	URI	Self-Test		Self-Test	
-	UKI				
_	NTP-Client	Self-Test		Self-Test	
-	NIP-Client				
	NTP-Server	Self-Test		Self-Test	
-	NTF-Server				
	DNS-Server	Self-Test		Self-Test	
-	Divo-Server				
_	DHCP-Server	DHCP- Server_R1v1.*_C		DHCP- Server_R1v1.*_I	
-	Diff Gerver				
	DHCP-Server-	Self-Test		Self-Test	
-	Ext				
_	DHCP-Relay	DHCP- Relay_R1v1.*_C		DHCP- Relay_R1v1.*_I	
-	Differ-itelay				
	IPsec	IPsec_R1v1.*_C		IPsec_R1v1.*_I	
-	11 300				
_	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C		IPsec-SHA- 512_R1v1.*_I	
-	11 360-3HA-312				
-	SSHV2	Self-Test		Self-Test	
-	551142				
_	TLS	Self-Test		Self-Test	
-					
_	TLS-1.3	Self-Test		Self-Test	
-	120-1.0				
	Tunneling-IP	Self-Test		Self-Test	
-	runnening-ir				

#### Host Capabilities

-	Tunneling-UDP	Self-Test		Self-Test		
-	XLAT	Self-Test		Self-Test		
-	NAT64	Self-Test		Self-Test		
-	DNS64	Self-Test		Self-Test		
-	SNMP	Self-Test		Self-Test		
-	Tunneling	Self-Test		Self-Test		
-	DiffServ	Self-Test		Self-Test		
-	NETCONF	Self-Test		Self-Test		
-	SSM	Self-Test		Self-Test		
-	Multicast	Multicast_R1v1 .*_C		Multicast_R1v1 .*_I		
-	ECN	Self-Test		Self-Test		
PASS	Link = Ethernet	Self-Test	Self Declaration	Self-Test	Self Declaration	

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY
[11]		CONFOR	MANCE		ITY/FUNCTIONAL	NOTES
SUPPORTED CAPABILITY	CAPABILITY	TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID	
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F		
-	Core	Core_R1v1.*_C		Core_R1v1.*_I		
-	Extended-ICMP	Self-Test		Self-Test		
-	PLPMTUD	Self-Test		Self-Test		
-	ND-Ext	Self-Test		Self-Test		
-	ND-WL	Self-Test		Self-Test		
-	SEND	Self-Test		Self-Test		
-	SLAAC	SLAAC_R1v1.*_C		SLAAC_R1v1.*_I		
-	PrivAddr	Self-Test		Self-Test		
-	DHCP-Prefix	DHCP- Prefix_R1v1.*_C		DHCP- Prefix_R1v1.*_I		
-	DHCP-Prefix- Ext	Self-Test		Self-Test		
-	6Lo	Self-Test		Self-Test		
-	Addr-Arch	Addr- Arch_R1v1.*_C		Addr- Arch_R1v1.*_I		
-	CGA	Self-Test		Self-Test		

		Colf Teet	Oald Test			
-	DNS-Client	Self-Test	Self-Test			
-	URI	Self-Test	Self-Test			
-	NTP-Client	Self-Test	Self-Test			
-	NTP-Server	Self-Test	Self-Test			
-	DNS-Server	Self-Test	Self-Test			
-	DHCP-Server	DHCP- Server_R1v1.*_C	DHCP- Server_R1v1.*_	I		
-	DHCP-Server- Ext	Self-Test	Self-Test			
-	DHCP-Relay	DHCP- Relay_R1v1.*_C	DHCP- Relay_R1v1.*_			
-	OSPF	Self-Test	OSPF_R1v1.*_			
-	OSPF-IPsec	Self-Test	Self-Test			
-	OSPF-Auth	Self-Test	OSPF- Auth_R1v1.*_I			
-	OSPF-Ext	Self-Test	Self-Test			
-	OSPF-Trans	Self-Test	Self-Test			
-	OSPF-Graceful	Self-Test	Self-Test			
-	ISIS	Self-Test	Self-Test			
-	IS-IS-Auth	Self-Test	Self-Test			
-	IS-IS-Ext	Self-Test	Self-Test			
-	IS-IS-MT	Self-Test	Self-Test			

		Self-Test	BGP_R1v1.*_I	
-	BGP			
		Self-Test	Self-Test	
-	BGP-Reflect			
		Self-Test	Self-Test	
-	BGP-Graceful			
		Self-Test	Self-Test	
-	BGP-FlowSpec	Sell-Test	Sell-Test	
-	BGP-OV	Self-Test	Self-Test	
_	BGP-VPLS	Self-Test	Self-Test	
_	BGP-EVPN	Self-Test	Self-Test	
-	BOF-EVEN			
		Self-Test	Self-Test	
-	BGP-6VPE			
		Self-Test	Self-Test	
-	BGP-MVPN			
		Self-Test	Self-Test	
-	MPLS			
		CE_Router_R1v	CE_Router_R1v	
-	CE-Router	1.*_C		
		Self-Test	Self-Test	
-	VRRP	Ucil-Test	Generest	
		IBaaa B1v1 * C		
_	IPsec	IPsec_R1v1.*_C	IPsec_R1v1.*_I	
_	IPsec-VPN	IPsec- VPN_R1v1.*_C	IPsec- VPN_R1v1.*_I	
	IPsec-SHA-512	IPsec-SHA- 512_R1v1.*_C	IPsec-SHA- 512_R1v1.*_I	
-	IFSEC-38A-312			
	IPsec-SHA-512-	IPsec-SHA-512-	IPsec-SHA-512-	
-	VPN	VPN_R1v1.*_C	VPN_R1v1.*_I	
		Self-Test	Self-Test	
-	SSHV2			
		Self-Test	Self-Test	
-	TLS			

-	TLS-1.3	Self-Test	Self-Test	
-	Tunneling-IP	Self-Test	Self-Test	
-	Tunneling-UDP	Self-Test	Self-Test	
-	GRE	Self-Test	Self-Test	
-	DS-Lite	Self-Test	Self-Test	
-	LW4over6	Self-Test	Self-Test	
-	MAP-E	Self-Test	Self-Test	
-	MAP-T	Self-Test	Self-Test	
-	XLAT	Self-Test	Self-Test	
-	NAT64	Self-Test	Self-Test	
-	DNS64	Self-Test	Self-Test	
-	6PE	Self-Test	Self-Test	
-	LISP	Self-Test	Self-Test	
-	SNMP	Self-Test	Self-Test	
-	Tunneling	Self-Test	Self-Test	
-	DiffServ	Self-Test	Self-Test	
-	NETCONF	Self-Test	Self-Test	
-	SSM	Self-Test	Self-Test	

-	PIM-SM	Self-Test	Self-Test	
-	PIM-SM-IPsec	Self-Test	Self-Test	
-	PIM-SM-BiDir	Self-Test	Self-Test	
-	Multicast	Multicast_R1v1. *_C	Multicast_R1v1. *_I	
-	ECN	Self-Test	Self-Test	
-	Link =	Self-Test	Self-Test	

# Application Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11] SUPPORTED CAPABILITY	CAPABILITY	CONFO TEST SELECTION	RMANCE RESULT ID	INTEROPERABIL TEST SELECTION IPv6-	LITY/FUNCTIONAL RESULT ID	NOTES	
-	IPv6-ONLY			ONLY_R1v1.*_F			
-	App-Serv=			APP- ONLY_R1v1.*_F			
-	Link =			Self-Test			

# NPP Capabilities

[10] PRODUC	T ID/ STACK ID				CAPABILITY SUMMARY		
[11]	CAPABILITY	CONFOR	MANCE	INTEROPERABILI	TY/FUNCTIONAL	NOTES	
SUPPORTED CAPABILITY		TEST SELECTION	RESULT ID	TEST SELECTION	RESULT ID		
-	IPv6-ONLY			IPv6- ONLY_R1v1.*_F			
-	FW	FW_R1v1.*_C					
-	APFW	Self-Test					
-	IDS	FW_R1v1.*_C					
-	IPS	FW_R1v1.*_C					
-	Link =	Self-Test					

#### Switch Capabilities

[10] PRODUC	T ID/ STACK ID					CAPABILITY SUMMARY		
[11] SUPPORTED CAPABILITY	CAPABILITY	CONFOR TEST SELECTION	MANCE RESULT ID	INTEROPERABILIT	RESULT ID	NOTES		
-	IPv6-ONLY		1	IPv6- ONLY_R1v1.*_F				
-	DHCPv6-Guard	Self-Test		Self-Test				
-	RA-Guard	Self-Test		Self-Test				
-	MLD-Snooping	Self-Test		Self-Test				
-	Link =	Self-Test		Self-Test				

1	CONTACT INFORMATION	Supplier name, email and signature (digital recommended). Include printed name and date if wet ink signed. Accredited laboratory name, email and signature (digital recommended). Include printed name and date if wet ink signed
2	PRODUCT VERSION TESTED	Firmware/ software version of product declared
3	PRODUCT ID	Suppliers concise name for product declared
4	PRODUCT FAMILY	Applicable hardware or software with an unmodified IPv6 stack from "PRODUCT VERSION TESTED"
5	UNITARY OR COMPOSITE	Indicate if this is a unitary or composite SDoC. If composite is checked, composite SDoC must be linked in section 6.
6	REF	Reference number to profile(s) reference in this SDoC
	SUPPLIER	Supplier name
	PRODUCT ID/STACK ID	Product ID must match field 3. As there may be more than one unique IPv6 stack, stack ID identifies particular stack described in CAPABILITY SUMMARY. Each unique stack requires a CAPABILTY SUMMARY.
	CAPABILITY SUMMARY	The strong notation as described in NIST-SP-500-267Ar1 that describes the product capabilities of the given stack.
	COMPOSITE SDOC LINK	URL link to composite SDoC referenced.
7	USGV6-CAPABLE REQUIREMENTS	Refer to section 5 in NIST-SP-500-267Br1 for CSS strings referenced in this section. Check the appropriate box if the product meets the requirements.
8	PROFILE(S) REFERENCED	Profile(s) referenced in the SDoC.
9	SUPPLEMENTARY ATTESTATIONS	Attestations made by the supplier. Check all that apply.
10	PRODUCT ID/STACK ID	PRODUCT ID/STACK ID for stack documented on given page.
	CAPABILITY SUMMARY	CAPABILITY SUMMARY for stack documented on given page.
11	SUPPORTED CAPABILITY	"PASS" – All requirements of the capability have been met
		"NOTES" – See notes for details regarding the level of support for this capability
		"X" – Capability not supported
		BLANK – No declaration for this capability
	CAPABILITY	IPv6 Capability as described in NIST-SP-500-267Ar1.
	TEST SELECTION	Test Selection Tables version of capabilities with existing test programs. Capabilities without an existing test program are indicated with "Self-Test"
	RESULT ID	Abbreviation of accredited laboratory and unique identifier of test result. Capabilities with "Self-Test" can be self-declared writing "Self Declaration" in the cell.
	NOTES	The cell must be filled out if "NOTE" is indicated for SUPPORTED CAPABILITY. Suppliers may use notes to clarify unsupported features or non-passing results.

#### SUPPLIER GENERAL NOTES