Supplie	ers Declaration of Confe	ormity for USGv6 Prod	lucts			USGv6-v1 SDOC-v1.1 Page 1					
1	The Document Requir	ing Conformity:				USGv6 Profile Version 1.0, July 2008. (NIST SP500-267)					
2	Product Identifier:			Cisco VX	(C Virtuali	zation Client					
3	Supplier's Name, Add	ress and SDOC Conta	ct Details								
	ystems Inc.										
	st Tasman Dr.										
	se, CA 95134										
	Product as Tosted/Do	alarad: Product Identific	er, version/revision information, details	of configure	ation tootad						
4	Flounci as Testeu/Dec	cialeu. Product identine	er, version/revision imormation, details	or cornigura	alion lesteu.						
			7.0_62	27							
			7.0 <u>_</u> 0.	_,							
5	Product Family (other products using same IPv6 stack(s) to which these results are declared to apply). Check Product Family attestation below.										
			0		40.01	va a					
			Cisco VXC 2212, Cisco VXC 2112, C	Disco VXC 2	x12, Cisco V	XC 2xx2					
6	USGv6 Canability sum	mary (For each distin	ct IPv6 stack in the product provide a	summary of	its USGv6 c	apabilities below and include a detailed test result summary).					
· ·	•	• ,	IPv6-Base+Addr-Arch+IPsec-v3+IKEv			•					
			USGv6-v1-Host: IPv6-Base+Addr	-Arch+SLAA	AC+Link=Eth	ernet					
				7							
7	Self Contained or Con	Self Contained or Composite SDOC? (Must indicate one).									
	All of the declared USGv6 cap	· · · · · · · · · · · · · · · · · · ·	<u>, </u>	bilities of this p	roduct are prov	ided by the use and/or integration of umodified components that have their own					
	addressed by orginal test results reported in this SDOC.		unique USGv6 SDOCs. All of t	s are identified in section 8 and attached. This product's page 2 will indicate							
			which capabilities are provided	by specific refe	erenced compo	nents (product-id/stack-id).					
1 T 2 F 3 S Cisco Sys 170 West San Jose, USA 4 F 5 F 6 L 6 [1] [2] [3] [4] 9 S YES 7 6 6 6 6 6 7 10 S	Additional Declarations / Attachments: (List supplier & product-id/stack-id for referenced and attached test results in the case of composite products).										
	Component Supplier		Product ID:	Stack ID:		Notes:					
[1]											
[2]											
[3]											
[4]											
9	Supplementary Attest	ations (Answer all).									
YES	This product is fully functional in IPv6 only environments. That is, no claimed capabilities are invalidated if this product is deployed in a network environment that does not support IPv4.			YES		ucts listed in the product family in section 5 are implemented such that their					
			for each unique IPv6 stack in the product. If not, please document which stacks/ports are			ilities are identical in form and function across the entire product family. The rmance and interoperability test results for the USGv6 capabilities of an identified					
			not covered, and how their IPv6 capabilities		member of this product family are provided in this SDOC. The SDOC attests to the fact that						
			differ from those reported in this SDOC.			JSGv6 capabilities are identical and unmodified for all the products cited above.					
10	Signature	Darryll Gadson	<u> </u>	Date		2/3/12					
		•				210,12					
	Print Name / Title	Darryll Gadson, Lead U	JSGv6 Cisco Systems								

	•	ers Declaration of Conformity for USGv6 Pro					,						
Product Id	l:	Cisco VXC Virtualization C	lient		Stack Id	d:			7.0_627				
			Context /	Suppo	rted Capa	bilities		USGv6 Testing	Program Results				
Spec /			Configuration				Test Suite	Test Lab / Result ID, Note #, or	Test Suite	Test Lab / Result ID, Note #, o			
Reference		USGv6-v1 Profile Requirements	Option	Host	Router	NPD	Conformance/NPD	Component Ref	Interopoperability	Component Ref			
P500-267	6.1	IPv6 Basic Requirements											
		support of IPv6 base (IPv6;ICMPv6;PMTU;ND)	IPv6-Base	Р			Basic_v1.*_C	UNH/IOL - 10109	Basic_V1.*_I	UNH/IOL - 10110			
		support of stateless address auto-configuration	SLAAC	Р			SLAAC-V1.*_C	UNH/IOL - 10111	SLAAC-V1.0_I	UNH/IOL - 10112			
		support of SLAAC privacy extensions.	PrivAddr				Self Test		Self Test				
		support of stateful (DHCP) address auto-configuration	DHCP-Client				Self Test		DHCP_Client_v1.*_I				
		support of automated router prefix delegation	DHCP-Prefix				Self Test		Self Test				
ND500.007		support of neighbor discovery security extensions	SEND				Self Test		Self Test				
SP500-267	6.6	Addressing Requirements								100000			
		support of addressing architecture reqts	Addr-Arch	Р			Addr_Arch_v1.*_C	UNH/IOL - 10107	Addr_Arch_v1.*_I	UNH/IOL - 10108			
		support of cryptographically generated addresses	CGA				Self Test		Self Test				
SP500-267	6.7	IP Security Requirements	ID 0				ID 0 1 1 0		15 0 1 1				
	-	support of the IP security architecture	IPsecv3				IPsecv3_v1.*_C		IPsecv3_v1.*_I				
	-	support for automated key management	IKEv2				IKEv2_v1.*_C		IKEv2v1.0_I	<u> </u>			
DE00.007	0.44	support for encapsulating security payloads in IP	ESP				ESPv3_v1.*_C		ESP_v1.*_I				
SP500-267	6.11	Application Requirements	DNO Olivert				O - 15 T 4		0-15 T1				
	-	support of DNS client/resolver functions	DNS-Client	1			Self Test		Self Test	<u> </u>			
		support of Socket application program interfaces support of IPv6 uniform resource identifiers	SOCK URI				Self Test		Self Test				
		support of 12vo uniform resource identifiers support of a DNS server application	DNS-Server				Self Test Self Test		Self Test Self Test				
	1	support of a DNS server application	DHCP-Server				Self Test		DHCP Serv v1.* I				
SP500-267	6.2	Routing Protocol Requirements	DI ICF-Server				Sell Test		DHCF_Selv_VII				
5P500-267	0.2	support of the intra-domain (interior) routing protocols	IGW				Self Test		OSPFv3 v1.* I				
	1	support of the intra-domain (interior) routing protocols support for inter-domain (exterior) routing protocols	EGW				Self Test		BGP v1.* I				
P500-267	6.4	Transition Mechanism Requirements	EGW				Sell Test		BGF_VII				
F 300-201	0.4	support of interoperation with IPv4-only systems	IPv4				Self Test		Self Test				
		support of funneling IPv6 over IPv4 MPLS services	6PE				Self Test		Self Test				
SP500-267	6.8	Network Management Requirements	01 L				OCH TCSI		Self Test				
01 000-201	0.0	support of network management services	SNMP				Self Test		Self Test				
SP500-267	6.9	Multicast Requirements	OINIVII				Jell Test		Jeli Test				
51 000 <u>2</u> 01	0.0	support of basic multicast	Mcast				Self Test						
		full support of multicast communications	SSM				Self Test		Self Test				
SP500-267	6.10	Mobility Requirements					00111000		50 7 GC				
		support of mobile IP capability.	MIP				Self Test		Self Test				
		support of mobile network capabilities	NEMO				Self Test		Self Test				
SP500-267	6.3	Quality of Service Requirements											
		support of Differentiated Services capabilities	DS				Self Test		Self Test				
		PHB Id					Self Test						
SP500-267	6.12	Network Protection Device Requirements											
		support of common NPD regts	NPD				N1 N2 N3 N4						
		support of basic firewall capabilities	FW				N1 FW						
		support of application firewall capabilities	APFW				N2 App FW						
		support of intrusion detection capabilities	IDS				N3 IDS						
		support of intrusion protection capabilities	IPS				N4_IPS						
SP500-267	6.5	Link Specific Technologies											
		support of robust packet compression services	ROHC				Self Test		Self Test				
		support of link technology [O:1]	Link=Ethernet	Р			Self Test	Self Declaration	Self Test	Self Declaration			
		(repeat as needed) support of link technology	Link=										
12	Х	< Check HERE if this stack's DOC includes a		mation	about to	etad ca	nahilities and entic	ne on an attached nage 2 of ne	itas				
12	^	CHECK HERE II this stack's DOC includes a	additional infor	mation	about te	Sieu ca	pabilities and optio	ns on an attached page 3 of no	nes.				
Level	Level of	support for USGv6-v1 Requirements for capability.				Color	India	cation of USGv6-v1 Pecommended L	evel of Support for device	e type / stack role			
FEAGI		nk - SDOC makes no declaration for this capability.					Indication of USGv6-v1 Recommended Level of Support for device type / stack role. Indicates capability that is recommendend as mandatory (unconditional MUST) in the USGv6-v1 Profile.						
P		ed required tests of USGv6-V1 requirements for these capabilities.					Indicates cabability that is unusal for a given device type / stack role. Do not select without careful analysis.						
N		notes page for details on the level of support of USGv6-v1 reequirements for this capability.					Indicates capability that is left optional / ocnditional by the recommedations of the USGv6-v1 Profile.						
Χ	USGv6	Gv6 capability not supported in product.											
st Suite -	Specific L	SGv6 Test suite used for test. See: http://www.antd.nist.	gov/usgv6/test-spe	cifications	.html			Note # - reference t	to a detailed note about thi	s capability or result on attached p			
Test Lab / Result ID - Abbreviation of accredited laboratory and its local identifier for this test result.							Component Ref - Supplier / Product / Stack ID of distinctly tested component that provides this capability.						

	Product Id:		nformity for USGv6 Products: Notes Page			v6-v1 SDOC-v1.1 Page					
	Spec / Reference		USGv6-v1 Profile Requirements	Context / Configuration Option	Stack Id: Supported Capabilities				Notes about USG	6v6-v1 Capabilities.	
Note #						Router	NPD	Test Suite Conformance/NPD	Test Lab / Result ID, Note	Test Suite Interopoperability	Test Lab / Result ID, Note
1											
iscussio	1:										.
2											
iscussio	1:										
3											
iscussio	1:										
4											
scussio	1:										
5											
iscussio	1:										
		ion about	this Product / Stack's capabilities:		•	•					

General: This document describes network product from the identified supplier that claims support of USGv6 capabilities. General product and supplier identification is given on Page 1. Overall results of testing USGv6 capabilities for conformance, interoperability and network protection are given on Page 2. Detailed instructions for completing and interpreting each numbered field are given below. Note USGv6 Testing website at: http://www.antd.nist.gov/usqv6/testing.html. Contact: usqv6-project@antd.nist.gov.

Field

Field Description and Instructions

- 1 The Document Requiring Conformity: Identifies the profile version implemented. Not a user completeable field.
- **2 Product Identifier**: Supplier's concise name for the product declared.
- 3 Suppliers Name, Address and Contact Details: Company name and point of contact for SDOC questions, street address, phone and email.
- 4 Product as Tested/Declared: Product Identifier and detailed version information. If this SDOC reports oringal test results (page 2), include information about the specific product configuration(s) that was actually tested (e.g., hardware configuration, operating system, etc).
- Product Family: A list of other products that use the same, unmodified IPv6 stacks such that their USGv6 capabilities are identical in form and function to the specific product configuration above. Test labs are only required to affirm the results for specific products tested. Test labs optionally may affirm recognized product families.
- 6 USGv6 Capability Summary: The USGv6 stack implementation summary as identified by the '+' notation described in the USGv6 profile, Appendix A. For each IPv6 stack implementation in the product, a distinct Stack Id and reference to the attached Results Summary page (Page 2).
- 7 Self Contained or Composite SDOC: If this SDOC relies on the test results of other disinct products, list the Supplier & Product ID/Stack IDs referenced and attach those original SDOCs to this one.
- 8 Additional Declarations / Attachements: List the supplier / product ID / Stack ID of any test results of composite components referenced by this SDOC.
- 9 Supplementary Attestations: Suppliers disclosure of IPv6 only capabilities; multiple stacks present; product family applicabilities. These are not included to qualify or disqualify a product from purchase considerations, but to inform network administrators of potential configuration options relevant to USGv6 interoperability. Check all that apply.
- Signature Block: Wet ink signature of the responsible product manager, dated. Printed name and position title on the line below.

Description and Instructions

Summary of Results: The format of this table mirrors the USGv6-v1.0 capabilities checklist (USGv6 Profile, Appendix A). The 12 categories of USGv6 capabilities are listed as subheadings, with subsidiary functions as line items. Configuration options related to conditional implementation of selected capabilities.

Product Id/Stack Id: The identification line of this page includes space for Product Id and Stack Id labels. Product Id is the same as given on Page 1. As there may be more than one unique IPv6 stack implemented in the product, the Stack Id field identifies the particular stack described. One Results Summary page per stack is required.

Host, Router and Network Protection (NPD) columns identify 'preferred' options: cells in green represent the NIST recommendations. Cells in grey denote atypical options, very unlikely to be implemented. The procuring Agency may additionally tailor these fields to indicate requirements for this acquisition.

Test Suite Conformance and Interoperability columns identify capability sets for which a public test suite exists, and the versions applicable to USGv6-v1.0 test results. Major version v1 and all its minor versions are deemed acceptable. Over time, new versions will be added and older ones retired. There may be periods when more than one major version is acceptable concurrently.

The supplier completes the adjacent **Test Lab and Result Id** column with the test lab acronym and unique result identifier (See Test Lab and Accreditor page on the Website). The buyer may opt to query results with the test laboratory using the specified Result Id(s). The supplier may opt to provide particular explanation of some results (partial results, additional options) in which case reference to note on an attached page 3. (e.g. "See Note# N"). See the USGv6 testing website to identify the test lab, and find contact details.

Cells marked **Self Test** have no associated public test suite. If implemented by the supplier, the required adjacent annotation is "Self Declaration". Note that vendors declaring support for such a capability are declaring support for the associated specific requirements in the USGv6 Profile.

12 Additional Options Tested: Vendor checks if it is desired to record tested options not part of the 'Musts' in the profile. Explanations on the page following the results summary.

Headings and Special Notations: as described.

Options for Test Lab and Result Id: Currently 3 cases: (1) the test lab acronym and alphanumeric Id of the result set as assigned by the test laboratory; (2) 'Self declaration' denoting the supplier attests to adequate QA testing of the capability; (3) See attachment or note 'N', where the supplier explains variations in greater detail.